

## **VOC Content Test Certificate**

Thursday 17<sup>th</sup> December 2020

Supplier: Laticrete Pty Ltd (29 Telford Street, Virginia, QLD, 4014, Australia).

Sample Description: LATICRETE® PRIMER

Date Tested: December 2020 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960-05 Standard Practice for Determining Volatile Organic Compound

(VOC) Content of Paints and Related Coatings. ASTM D3960 as detailed for paints as

well as South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

Specification Green Building Council of Australia Green Star Design & As Built V1.3-13.1.1B Green Star Interiors V1.3-12.1.1B	LATICRETE® PRIMER
Primers, Sealers, and Prep Coats: 65 grams per Litre	3 grams per Litre as VOC content per material

We hereby certify that LATICRETE® PRIMER is below the VOC Content limits of chosen categories specified by Green Star Design, Green Building Council of Australia

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Tuan Duong PhD (Chem. Eng.)

Senior Consultant

Travis Hale BSc (Biotech)

Senior Consultant

V2012001