



Globally Proven
Construction Solutions

335 Premium Flexible Adhesive



CERTIFIED
LOW VOC

FEATURES

- One component — mix with water
- Versatile
- Suitable for submerged installations
- High performance adhesive
- Improved flexural and adhesive strength
- Smooth, creamy formula
- Part of the LATICRETE System Warranties

BENEFITS

- Mixes only with water - no additive required.
- Covers a wide range of tile, stone and substrates.
- Ideal for submerged applications such as swimming pool and water features.
- Meets and exceeds the requirements of AS ISO13007.1 as a C2TES1.
- Allows bonding to low porosity tiles and substrates including LATICRETE LataCoustic Sound Control.
- Easy to mix for greater workability.
- Performance backed by LATICRETE means peace of mind for trouble-free installations in both interior and exterior applications.

Uses

- Swimming pools and continuously submerged applications
- Interior and exterior installations

Suitable Substrates

- Porcelain tile
- Ceramic tile and stone
- Mosaic
- Quarry tile
- Concrete masonry
- Cement plaster
- Cement backer board[†]
- Gypsum wallboard *
- Marble
- Brick and concrete pavers
- Granite
- Concrete
- Cement mortar beds
- Brick masonry
- Cement terrazzo
- Suitable waterproof membrane

Packaging

20 kg bag; 56 bags per pallet

Available Colours

Off-White and White

Approximate Coverage Per Bag

6 mm x 6 mm notched trowel	7 – 8 m ²
10 mm x 10 mm notched trowel	4.5 – 5.5 m ²

(Based on product wet densities with a trowel at 45°)

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au



Snap for information.