



Globally Proven
Construction Solutions

SPECTRALOCK® 2000 IG



CERTIFIED
LOW VOC

FEATURES

- Easy to install
- Non-sag formula
- 80 minute working time
- Expanded colour availability
- Meets ANSI A118.3 and A118.5 and conforms to AS ISO 13007.3&4 R2 classifications

BENEFITS

- Creamy consistency, easy to spread and clean.
- Stays in the joint for easy installation and cleaning.
- Allows you more time to install.
- A full range of 39 colour options now available in an industrial grout.*
- Meets requirements for both epoxy and furan grouts.

Uses

- Designed as a highly chemical resistant industrial grade epoxy grout for ceramic tile, pavers, floor brick, packing house tile and stone
- Designed for installations in corrosive environments such as: Bakeries, dairies, cheese factories, breweries, CIP rooms, meat packing plants, soft drink plants, confectioneries, canneries, distilleries, pharmaceutical factories, veterinary hospitals, clinics, kennels, institutional kitchens, fast food restaurants, cafeterias, laboratories, supermarkets

Packaging

#4 Resin (Liquid Only) Commercial Unit
6 kg carton; 56 cartons per pallet
Part A: 4 x 0.5 kg
Part B: 4 x 1 kg

Available Colours

39 colours available in an industrial grout*

Approximate Coverage Per Carton - m²

Tile Size	Joint Width		
	6 mm	9 mm	12 mm
100 mm x 200 mm x 12 mm	14.0	9.4	7.2
100 mm x 200 mm x 30 mm	5.6	3.8	2.9
150 mm x 150 mm x 9 mm	21.0	14.2	10.7

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au



Snap for information.

* Bright White not available in industrial grout.