

For The Builders of A Better World

PERMACOLOR® Grout

PERMACOLOR[®] Grout is a high performance grout that provides a grout joint that is dense, hard and will resist cracking.



FEATURES

Consistent colour
1 step – mix with water
Stain-resistant
Versatile
Equipped with antimicrobial properties
Strong and durable cement-based grout

Uses

- Ceramic tile and stone applications
- Interior and exterior
- Floors and walls
- Swimming pools

Suitable Substrates

- Marble
- Porcelain tile
- Granite
- Quarry tile

D	EN			C
D		U.	41	Э

No blotchiness, resists efflorescence (compared to other Portland cement-based grout).
Easy to install, no additive required.
Easy to clean, highly stain–resistant for a cement–based grout.
Covers a wide range of joint widths; 1.5 mm — 12 mm.
Inhabits the growth of stain-causing mould and mildew growth in the grout joints.
Resists cracking and powdering.

Packaging / Colours

- 5 kg bag; 4 bags per carton; 40 cartons per pallet. Available in top 12 colours.
- 10 kg bag; 100 bags per pallet Available in top 20 colours.

(please refer to colour chart)

Approximate Coverage Per 10 kg Bag – m²

	•		•	•		
Tile Size	Joint Width					
	1.5 mm	3 mm	6 mm	9 mm	12 mm	
25 x 25 x 6 mm	9.4	5.1	3.0	2.3	1.9	
50 x 50 x 6 mm	18.1	9.4	5.1	3.7	3.0	
100 x 100 x 8 mm	26.6	13.6	7.1	4.9	3.8	
150 x 150 x 9 mm	35.2	17.8	9.2	6.3	4.9	
200 x 200 x 9 mm	46.7	23.6	12.1	8.2	6.3	
300 x 300 x 9 mm	69.8	35.2	17.8	12.1	9.2	
325 x 325 x 9 mm	75.6	38.0	19.3	13.0	9.9	
400 x 400 x 9 mm	92.9	46.7	23.6	15.9	12.1	
450 x 450 x 9 mm	104.4	52.5	26.5	17.8	13.5	
600 x 600 x 9 mm	139.0	69.3	35.2	23.6	17.8	

Snap for information

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au

- Ceramic tile

- Glass mosaic

Stone

Cartain types of stane and file are more absorbent than others and will trap colour pigment during grouting. Prior to grouting, test for absorption of colour pigment. Parous files will need to be sealed prior to grouting, this includes polished porcelain. Care should be taken when using sanded grouts or soft faced files as scratching can occur.