



# STONETECH® Enhancer & Sealer

STONETECH® Enhancer & Sealer is the standard sealer that seals and enhances the surface to a rich colour.

**Globally Proven  
Construction Solutions**



## FEATURES/BENEFITS

- Deepens colour
- Standard protection against most stains
- Interior use
- Easy-to-use, water-based formula

## PACKAGING

- 946 mL, 6 units per Case, 600 units per Pallet
- 3.8 L, 4 units per Case, 160 units per Pallet
- 18.9 L, 1 unit per Case, 48 units per Pallet

## USES (INTERIOR)

- Countertops
- Splashbacks
- Floors
- Walls

## RECOMMENDED SURFACES

Natural stone such as:

- Bluestone
- Slate
- Travertine
- Limestone
- Flagstone
- Textured stone
- Flamed stone
- Tumbled stone
- Concrete

## MANUFACTURER

LATICRETE Australia Pty Ltd  
29 Telford Street  
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599  
Toll Free: 1800 331 012  
Fax: 07 3865 2250  
Internet: [www.laticrete.com.au](http://www.laticrete.com.au)

### Approximate Coverage

Depending on stone type, texture and porosity; the site conditions at the time of installation; and the method of installation, the following rates of coverage will vary.

- Up to 6 m<sup>2</sup>/946 ml, depending on porosity of stone.
- Up to 23 m<sup>2</sup>/3.8 L, depending on porosity of stone.
- Up to 116 m<sup>2</sup> /18.9L, depending on porosity of stone.

### Expected Wear

- Up to 5 years on interior surfaces

### VOC Content

<150 g/L (excluding water) for EPA purposes.

<25 g/L (including water) for other regulatory purposes (Low Solids Coating).

### Cautions

- Consult SDS for more safety information.
- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Wash skin with soap and water. Get medical attention if symptoms occur.
- Eye contact: Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if symptoms persist.
- Ingestion: Rinse mouth. Do not induce vomiting. Get medical attention if any discomfort continues.

### Storage and Handling Instructions

WARNING: HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Avoid prolonged exposure to vapours. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 38 °C. Do not mix with other chemicals. Do not release to waterways.

## TECHNICAL DATA

### Physical Properties

Form	Liquid
Colour	Milky White
Odour	Ether-like
pH	4.5
Specific Gravity	1.00
Flash Point	110°C

### Working Properties

Full cure	24 – 72 Hours
-----------	---------------

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## INSTALLATIONS

### Surface Preparation

Read entire label before using. Use only as directed. Test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 72 hours prior to application. Be sure surface is clean, thoroughly dry and free of sealers, waxes and coatings. Not recommended for exterior surfaces. Surface temperature should be between 10°C-27°C. Avoid skin and eye contact. Wear protective eyewear and gloves. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area during application and drying.

### Application

- Shake well before using.
- Apply STONETECH® Enhancer & Sealer evenly and liberally using a paint pad, low-pressure chemical-resistant sprayer, roller or brush. Avoid applying sealer on unintended surfaces.
- Allow sealer to penetrate surface for 15–30 minutes; denser material may require maximum time to penetrate surface. Spread excess sealer over entire area for even penetration.
- Following penetration time, completely wipe surface dry with a clean dry towel. DO NOT ALLOW EXCESS TO DRY COMPLETELY ON SURFACE.
- A second coat may be needed for porous, absorbent surfaces or if a darker appearance is required. Apply second coat 1 hour after start of initial application following directions in steps 1–4.
- A full cure is achieved after 24–72 hours. Surface traffic may begin in 6–8 hours. If needed sooner, cover the floor with single ply builders protection paper to protect it until the recommended time periods have passed.
- Clean tools used during application with water.

## AVAILABILITY AND COST

### Availability

LATICRETE® and LATAPOXY® materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at [www.laticrete.com.au](http://www.laticrete.com.au)

### Cost

Contact a LATICRETE Distributor in your area.

## MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the STONETECH sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KLENZALL™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 1262 Stone and Tile Care Guide.

## TECHNICAL SERVICES

### Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

### Technical and safety literature

To acquire technical and safety literature, please visit our website at

**[www.laticrete.com.au](http://www.laticrete.com.au)**

## DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and LATICRETE® is not responsible for any loss or damage arising from the incorrect use of this product.
- Efflorescence is a normal condition of Portland cement and is not covered by any warranty.

---

### LATICRETE Australia Pty Ltd

29 Telford Street, Virginia

QLD 4014 Australia

1800 331 012

[www.laticrete.com.au](http://www.laticrete.com.au)