



# STONETECH® Impregnator Pro® Sealer

STONETECH® Impregnator Pro® is a solvent based sealer which preserves the natural look of stone surfaces.

**Globally Proven  
Construction Solutions**



## FEATURES/BENEFITS

- Heavy duty protection against most stains
- Preserves natural look of stone
- Solvent-based formula
- Interior and exterior use

## PACKAGING

- 473 mL, 12 units per Case, 1008 units per Pallet
- 946 mL, 6 units per Case, 600 units per Pallet
- 3.8 L, 4 units per Case, 160 units per Pallet
- 18.9 L, 1 unit per Case, 48 units per Pallet

## USES (INTERIOR/EXTERIOR)

- Countertops
- Splashbacks
- Floors
- Walls

## RECOMMENDED SURFACES

Natural stone such as:

- Granite
- Limestone
- Slate
- Bluestone
- Travertine
- Sandstone

## MANUFACTURER

LATICRETE Australia Pty Ltd  
29 Telford Street  
Virginia, QLD 4014 Australia

Telephone: 07 3865 1599  
Toll Free: 1800 331 012  
Fax: 07 3865 2250  
Internet: [www.laticrete.com.au](http://www.laticrete.com.au)

## Approximate Coverage

Depending on stone type, texture and porosity; the site conditions at the time of installation; and the method of installation, the following rates of coverage will vary.

- Up to 11 m<sup>2</sup>/473 mL, depending on porosity of stone.
- Up to 23 m<sup>2</sup>/946 mL, depending on porosity of stone.
- Up to 93 m<sup>2</sup>/3.8 L, depending on porosity of stone.
- Up to 464 m<sup>2</sup>/18.9 L, depending on porosity of stone.

## Expected Wear

- Up to 5 years on interior surfaces
- Up to 3 years on exterior surfaces

For best results, reapply annually.

## VOC Content

748 g/L.

## Cautions

- Consult SDS for more safety information.
- Inhalation: Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
- Skin contact: Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical attention if irritation develops and persists.
- Eye contact: Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately. May cause eye irritation.
- Ingestion: Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.
- DISPOSAL INFORMATION: For disposal guidance for unused product, contact a household hazardous waste program or your local or state government environmental control agency.

## Storage and Handling Instructions

COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED. Do not ingest. HARMFUL VAPORS. Avoid prolonged exposure to vapours. Use only in a well-ventilated area. For spray application, use a pump-up garden sprayer. DO NOT USE A POWER SPRAYER. Use a respirator if unsure that work area is well-ventilated. Use a AS/NZS 1716 or NIOSH approved respirator with a combination HEPA/organic vapour cartridge is recommended. Follow respirator manufacturer's instructions for use. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Avoid contact with eyes and skin. Wear solvent-resistant gloves such as nitrile gloves. KEEP OUT OF THE REACH OF CHILDREN. Do not store above 38 °C. Do not mix with other chemicals. Do not release to natural waterways.

## TECHNICAL DATA

### Physical Properties

Form	Liquid
Colour	Colourless
Odour	Mild
Specific Gravity	0.761
Flash Point	42°C

## Working Properties

Full cure	24 – 72 Hours
Surface Use	6 – 8 Hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## INSTALLATIONS

### Surface Preparation

Read entire label before using. Use only as directed. Test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 72 hours prior to application. Be sure surface is clean, thoroughly dry and free of sealers, waxes and coatings. Not recommended for exterior surfaces. Surface temperature should be between 10°C-27°C. Avoid skin and eye contact. Wear protective eyewear and gloves. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area during application and drying.

### Application

- Ensure area is well-ventilated during application and until the surface is dry. Use a AS/NZS 1716 or NIOSH approved respirator with a combination HEPA/organic vapour cartridge is recommended. Follow respirator manufacturer's instructions for use.
- Mask any surfaces not intended to be treated.
- Liberal apply an even coat of STONETECH® Impregnator Pro® Sealer using a paint pad, roller, brush or pump-up garden sprayer. DO NOT USE A POWER SPRAYER. See method of application for more information. Do not thin before using.
- Allow sealer to penetrate surface for 15–30 minutes; denser stone may require more time for sealer to penetrate. During this time, distribute excess sealer over entire area to ensure even penetration. DO NOT ALLOW EXCESS STONETECH Impregnator Pro TO DRY ON SURFACE.
- Thoroughly wipe entire surface with dry cloth to remove excess STONETECH Impregnator Pro Sealer from surface.
- A second coat may be needed for more porous surfaces and should be applied one hour after initial application, as directed in steps 3 through 5.
- If excess sealer was not completely wiped off and a residue appears, wipe entire surface with a towel dampened with sealer. Use a white nylon scrubbing pad to loosen residue and follow with white absorbent towel to remove.
- Full cure is achieved after 24–72 hours. Surface use may begin in 6-8 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure is achieved.
- Rags and equipment that are wet with product may be combustible. Clean up promptly after job is complete. Clean equipment with mineral spirits and allow to dry in a well-ventilated area. Allow rags to dry in a well-ventilated area out of the reach of children and pets. When dry, dispose of in accordance with local waste disposal regulations.

**METHOD OF APPLICATION: DO NOT USE A POWER SPRAYER.** Power sprayers increase exposure hazard. Power sprayers also create a significant amount of overspray resulting in wasted product and the need for additional clean-up. A pump-up garden sprayer will reduce the potential for overexposure to vapours and produce better results. For small jobs, use a paint pad, roller or brush. Trigger spray bottles are not recommended. Trigger sprayers create overspray and may not give a uniform application. Better results will be obtained using a pad, roller or brush. For larger jobs, use a pump-up garden sprayer available at your local garden centre, hardware store, or home improvement centre.

### Cleaning

Rags and equipment that are wet with product may be combustible. Clean up promptly after job is complete. Clean equipment with mineral spirits and allow to dry in a well-ventilated area. Allow rags to dry in a well-ventilated area out of the reach of children and pets. When dry, dispose of in accordance with local waste disposal regulations.

## AVAILABILITY AND COST

### Availability

LATICRETE®, STONETECH® and LATAPOXY® materials are available worldwide.

For Distributor information:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

For online distributor information, visit LATICRETE at [www.laticrete.com.au](http://www.laticrete.com.au)

### Cost

Contact a LATICRETE Distributor in your area.

## MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the STONETECH sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 1262 Stone and Tile Care Guide.

## TECHNICAL SERVICES

### Technical assistance

Information is available by calling:

Toll Free: 1800 331 012

Telephone: 07 3865 1599

Fax: 07 3865 2250

### Technical and safety literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com.au](http://www.laticrete.com.au)

## DISCLAIMER

The information contained in this document is given in good faith and to the best of our knowledge is true and accurate. This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information. The use of this product is beyond our control and LATICRETE is not responsible for any loss or damage arising from the incorrect use of this product. Efflorescence is a normal condition of Portland cement and is not covered by any warranty.

---

## LATICRETE Australia Pty Ltd

29 Telford Street, Virginia

QLD 4014 Australia

1800 331 012

[www.laticrete.com.au](http://www.laticrete.com.au)