

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

Products Regulation (February 11, 2015).

Date of Issue: 27/11/2022 Version: 1.0

# **SECTION 1: IDENTIFICATION**

# **Product Identifier**

**Product Form:** Mixture

**Product Name:** LATASIL™ White

#### Intended Use of the Product

Sealant. For professional use only.

#### 1.3. Name, Address, and Telephone of the Manufacturer - Importer

Company Company

LATICRETE International LATICRETE Australia Pty Ltd.

1 Laticrete Park, N 29 Telford Street Bethany, CT 06524 **VIRGINIA QLD 4014** T (+61) (07) 3865 1599 T (203)-393-0010 www.laticrete.com www.laticrete.com.au

#### **Emergency Telephone Number** 1.4.

**Emergency Number** : Australian Poisons Information Centre 24 Hour Service 13 11 26

Police or Fire Brigade 000

# **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the Substance or Mixture 2.1.

# **GHS-US/CA Classification**

Skin Sens. 1 H317 H351 Carc. 2 Repr. 2 H361

Full text of hazard classes and H-statements: see section 16

#### 2.2. **Label Elements**

**GHS-US/CA Labeling** 

Hazard Pictograms (GHS-US/CA)





Signal Word (GHS-US/CA) : Warning

Hazard Statements (GHS-US/CA) : H317 - May cause an allergic skin reaction.

H351 - Suspected of causing cancer.

H361 - Suspected of damaging fertility or the unborn child.

Precautionary Statements (GHS-US/CA) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing vapors, mist, or spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and

international regulations.

27/11/2022 EN (English US) 1/8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

#### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

## 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
2-Butanone, oxime	(CAS-No.) 96-29-7	< 1	Flam. Liq. 4, H227
			Acute Tox. 4 (Dermal), H312
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			Carc. 2, H351
			Aquatic Acute 3, H402
Octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	< 1	Flam. Liq. 3, H226
			Repr. 2, H361
			Aquatic Chronic 4, H413
Titanium dioxide	(CAS-No.) 13463-67-7	< 1	Carc. 2, H351

Full text of H-phrases: see section 16

### **SECTION 4: FIRST AID MEASURES**

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists. If exposed or concerned: Get medical advice/attention.

**Eye Contact:** Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

# 4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Skin sensitization. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child.

**Inhalation:** Prolonged exposure may cause irritation.

**Skin Contact:** May cause an allergic skin reaction.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Repeated or prolonged exposure to titanium dioxide dust via inhalation is suspected of causing cancer of the respiratory tract.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# **SECTION 5: FIRE-FIGHTING MEASURES**

### 5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical. Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

27/11/2022 EN (English US) 2/8

<sup>\*</sup>Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

 $\label{lem:precautionary Measures Fire:} \textbf{Exercise caution when fighting any chemical fire.}$ 

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Nitrogen oxides. Toxic vapors.

## 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe dust.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

## 6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

#### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

### **SECTION 7: HANDLING AND STORAGE**

# 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Water.

#### 7.3. Specific End Use(s)

Sealant. For professional use only.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

2-Butanone, oxime (96-29-7)			
USA AIHA	WEEL TWA [ppm]	10 ppm	
USA AIHA	AIHA chemical category	Skin sensitizer	
Octamethylcyclotetrasiloxane (556-67-2)			
USA AIHA WEEL TWA [ppm] 10 ppm			
Titanium dioxide (13463-67-7)			<u> </u>

27/11/2022 EN (English US) 3/8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2.4 mg/m³ (CIB 63-fine)
		0.3 mg/m³ (CIB 63-ultrafine, including engineered
		nanoscale)
USA IDLH	US IDLH (mg/m³)	5000 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
		3 mg/m³ (respirable fraction)
Manitoba	OEL TWA (mg/m³)	10 mg/m³
New Brunswick	OEL TWA (mg/m³)	10 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³
Nunavut	OEL STEL (mg/m³)	20 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	10 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m³

# 8.2. Exposure Controls

**Appropriate Engineering Controls:** Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on Basic Physical and Chemical Properties

Physical State: SolidAppearance: White pasteOdor: OximeOdor Threshold: Not available

pH : 8.4

**Evaporation Rate** : Not available

27/11/2022 EN (English US) 4/8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available Flash Point 96 °C (204.8 °F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Not available Vapor Pressure Relative Vapor Density at 20°C Not available **Relative Density** Not available **Specific Gravity** 1.03

Solubility: Not availablePartition Coefficient: N-Octanol/Water: Not availableViscosity: Not available

# **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

**10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

**10.5.** Incompatible Materials: Strong acids, strong bases, strong oxidizers. Water.

10.6. Hazardous Decomposition Products: In contact with water or humidity, the mixture will decompose to form

methylethylketoxime.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified

**pH:** 8.4

Eye Damage/Irritation: Not classified

pH: 8.4

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified **Carcinogenicity:** Suspected of causing cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes. Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

**Chronic Symptoms:** Suspected of causing cancer. Suspected of damaging fertility or the unborn child. Repeated or prolonged exposure to titanium dioxide dust via inhalation is suspected of causing cancer of the respiratory tract.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

27/11/2022 EN (English US) 5/8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

2-Butanone, oxime (96-29-7)		
LD50 Oral Rat	2326 mg/kg (Species: Sprague-Dawley)	
LD50 Dermal Rabbit	> 1000 mg/kg	
LC50 Inhalation Rat	> 4.83 mg/l/4h	
ATE US/CA (dermal)	1,100.00 mg/kg body weight	
Octamethylcyclotetrasiloxane (556-67-2)		
LD50 Oral Rat	> 4800 mg/kg (No mortality)	
LD50 Dermal Rat	> 2375 mg/kg	
LD50 Dermal Rabbit	> 2.5 ml/kg (No mortality)	
LC50 Inhalation Rat	36 g/m³ (Exposure time: 4 h)	
Titanium dioxide (13463-67-7)		
LD50 Oral Rat	> 10000 mg/kg	
Titanium dioxide (13463-67-7)		
IARC Group	2B	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

Ecology - General: Not classified.

2-Butanone, oxime (96-29-7)	
LC50 Fish 1	777 – 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
ErC50 (algae)	16 mg/l
NOEC Chronic Algae	2.6 mg/l
Octamethylcyclotetrasiloxane	(556-67-2)
LC50 Fish 1	> 500 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
LC50 Fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

### 12.2. Persistence and Degradability

LATASIL™ White	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

LATASIL™ White	
Bioaccumulative Potential	Not established.
2-Butanone, oxime (96-29-7)	
BCF Fish 1	0.5 – 5.8
Partition coefficient n-octanol/water	0.65 (at 25 °C)
(Log Pow)	
Octamethylcyclotetrasiloxane (556-67-2)	
BCF Fish 1	12400
Partition coefficient n-octanol/water	5.1
(Log Pow)	

# **12.4. Mobility in Soil** Not available

## 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

27/11/2022 EN (English US) 6/8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

# **SECTION 14: TRANSPORT INFORMATION**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT
 14.2. In Accordance with IMDG
 14.3. In Accordance with IATA
 14.4. In Accordance with TDG
 Not regulated for transport
 Not regulated for transport
 Not regulated for transport

### **SECTION 15: REGULATORY INFORMATION**

# 15.1. US Federal Regulations

LATASIL™ White		
SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization	
	Health hazard - Carcinogenicity	
2-Butanone, oxime (96-29-7)		
Listed on the United States TSCA (Toxic Substances	Control Act) inventory	
Octamethylcyclotetrasiloxane (556-67-2)		
Listed on the United States TSCA (Toxic Substances	Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA	
	section 4 test rule.	
Titanium dioxide (13463-67-7)		
Listed on the United States TSCA (Toxic Substances	Control Act) inventory	

# 15.2. US State Regulations

### **California Proposition 65**



**WARNING:** This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Titanium dioxide (13463-67-7)	X			

### Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

#### 15.3. Canadian Regulations

2-Butanone, oxime (96-29-7)
Listed on the Canadian DSL (Domestic Substances List)
Octamethylcyclotetrasiloxane (556-67-2)
Listed on the Canadian DSL (Domestic Substances List)
Titanium dioxide (13463-67-7)
Listed on the Canadian DSL (Domestic Substances List)

# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 27/11/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

# **GHS Full Text Phrases:**

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4

27/11/2022 EN (English US) 7/8

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Sens. 1	Skin sensitization, Category 1
H226	Flammable liquid and vapor
H227	Combustible liquid
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H402	Harmful to aquatic life
H413	May cause long lasting harmful effects to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

27/11/2022 EN (English US) 8/8