MATERIAL SAFETY DATA SHEET

Classified as hazardous according to criteria of NOHSC & Worksafe Australia. Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code for transport by Road & Rail.

1. Product and Company identification

Product Name : LATAPOXY Moisture Shield Vapour Reduction Membrane Part B

Manufacturer/

Supplier Name : LATICRETE Australia Pty Ltd.

29 Telford Street, Virginia, QLD 4014

Telephone : 1800 331 012

Emergency

Contact : 13 11 26

Recommended Use Use as the epoxy resin in 2-Pack Epoxy coatings for concrete substrate

2. Hazards Identification

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to NOHSC, Worksafe Australia and ADG Code.

GHS Classification: Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Skin Sensitiser Carcinogenicity Category 1A

Label element







SIGNAL WORD : DANGER

Hazard Statements	H315	Causes skin irritation
Hazaru Statements	11313	Causes skill illitation

H318 Causes serious eye damage

H317 May cause an allergic skin reactionH335 May cause respiratory irritation

H350 May cause cancer

Precautionary P280 Wear protective gloves, clothing, eye and face protection **Statements** P261 Avoid breathing dust, fumes, mist, vapour and spray

Prevention P271 Use only outdoor or in well ventilated areas

P272 Contaminated work clothing should not be allowed out of

the work place

P264 Wash face, hands and any exposed skin thoroughly after

handling

Precautionary Statements Response	P305/P351 P338 P310 P302/P352 P333/P313 P362/P364	If in eyes rinse cautiously with water for several minutes Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTRE or doctor/physician If on skin wash with plenty of water and soap If skin irritation or rash occurs, get medical advice/ attention Take off contaminated clothing and wash it before reuse
Precautionary Statement Disposal	P501	Dispose of contents/containers to authorised chemical landfill or if organic to high temperature incineration

Other Hazards Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

<u>Name</u>	CAS Number	<u>%</u>
Polyamide resin	68410-23-1	10-30

4. First Aid Measures

Swallowed Do not induce vomiting. If vomiting occurs lean patient forward or place

on left side to maintain open airway and prevent aspiration. Never give liquids to a person showing signs of being sleepy. Give water to rinse mouth. For advice contact the Poison Information Centre or a physician.

Eye Get immediately medical advice/attention. Rinse immediately with plenty

of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eyes wide open while rinsing. Do not rub affected area. Get medical attention if irritation

develops and persists.

Skin Remove all contaminated clothing/footwear. Wash off immediately with

soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists. Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reaction see

a doctor.

Inhaled Remove to fresh air. Get medical attention immediately if symptoms

occur.

Symptoms Burning sensation. Itching. Rashes. Hives.

First Aid Facilities Eye wash and safety shower facilities should be available.

Advice to doctor May cause sensitisation in susceptible persons. Treat

symptomatically.

Emergency Telephone

Poison Information Centre – Australia: 13 11 26

5. Fire Fighting Measures

Extinguishing Media Fire fighting advice

Non-combustible. Use foam, dry chemical, carbon dioxide. Avoid contamination with oxidising agents. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and protective suit

Specific hazards:

Product is or contains a sensitiser. May cause sensitisation by skin contact. Incomplete combustion may form carbon monoxide. May generate ammonia gas or/and toxic nitrogen oxide gases.

6. Accidental release measures

Personal Precaution Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

Minor Spills

Clean up all spills immediately. Contain spill with sand, earth or vermiculite Avoid breathing vapours and contact with skin and eyes. Place in a suitable labelled container for waste disposal.

Major Spills

Prevent further leakage or spillage if safe to do so. Contain/prevent run off into drains and waterways. Contain spill with sand, earth or vermiculite. Fire fighters and others exposed to vapours or products of combustion should wear self-contained breathing apparatus and protective suit Alert Fire Brigade if necessary. Collect recoverable material and seal in properly labelled containers or drums for disposal.

7. Handling and storage

Handling

Avoid contact with skin, eyes or clothing. Wear suitable protective clothing, gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wear nitrile rubber gloves. In case of insufficient ventilation wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Always wash hands with soap and water after handling. Avoid breathing vapours and/or aerosols.

Storage Store in cool dry well ventilated place and out of direct sunlight. Keep

containers tightly closed when not in use. Avoid contact with strong acids, strong bases and oxidising agents. Checked all containers are clearly

labelled & free from leaks. Keep out of reach of children.

8. Exposure controls/Personal protection

Exposure Limits No exposure limits set by NOHSC.

Engineering Control Provide readily accessible eye wash stations and safety showers. Ensure

adequate ventilated, especially in confined areas.

Personal Protection

Eye/face Tight sealing safety goggles.

Skin/body Suitable protective clothing. Long sleeve shirt and trousers without cuffs.

Respiratory Where respiratory protection is required, use a respirator selected and in

accordance with AS/NZS 1715 and AS/NZS 1716.

Hand Wear nitrile, neoprene or butyl rubber gloves. Wash hands prior to

smoking, eating and drinking.









9. Physical and chemical properties

PHYSICAL DESCRIPTION & PROPERTIES

Appearance : Viscous white/grey liquid

Odour : Mild amine

Boiling Point : Approximately 100°C

Melting Point : Not Applicable
Specific Gravity : 1.17 – 1.22
Flash Point : Not Applicable
Flammability Limits : Not Applicable
Solubility in water : Miscible with water

pH as supplied : 9.0-10.5

Vapour pressure : 18 mmHg @ 21°C Evaporation rate : Not Applicable Autoignition Temp.(C) : Not Applicable Decomposition Temp(C) : Not Available

VOC Level : Zero

10. Stability and reactivity

Stability Product is considerable stable and hazardous polymerisation will not occur under

normal conditions. Hazardous decomposition products include nitric acid,

ammonia, nitrogen oxides, carbon monoxide.

Incompatible Strong acids. Strong bases. Oxidising agents **Materials**

11. Toxicological Information

No adverse effects expected if the product is handled in accordance with this Safety Data Sheet and the label of this product. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Eye Severely irritating to eyes. Causes serious eye damage. May cause burns. May

cause irreversible damage to eyes.

Skin Cause skin irritation. May cause sensitisation by skin contact. Repeated or

prolonged skin contact may cause allergic reactions with susceptible persons.

Inhaled May cause irritation of respiratory tract.

Swallowed Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

12. Ecotoxicological information

Avoid contaminating waterways and dispose of paint or washings into drains or stormwater Not channels.

13. Disposal considerations

Recycle wherever possible. Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Unwanted paint should be mixed with epoxy component and allowed to dry and then disposal of via domestic waste collection. Empty paint cans should be left open in a good ventilated area to dry before disposal. Consult your State Land Waste Management Authority prior to disposal.

14. Transport information

ADG NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

IMDG NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

IATA NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

15. Regulatory information

Classification: Not classified as dangerous goods in accordance with Australian Code for

the Transport of Dangerous Goods by Rail and Rail (ADG). Classified as a hazardous substance in accordance with criteria of Safe Work Australia

- Globally Harmonised System.

Poisons Schedule: S5

A.I.C.S. Status: All components of the finished product are listed on the Australian

Inventory of Chemical Substances (AICS).

16. Other information

Date of Issue : 20 November 2025

Revision : 1.0

This information has been prepared in good faith using the best data available at the time of issue. It is based on the current state of knowledge and is believed to be accurate.

However, no warranty, guarantee, or representation is made as to its accuracy, reliability, or completeness, since conditions of use are beyond the manufacturer's control. All information is provided without warranty and is intended for guidance only.

The manufacturer/Supplier accepts no responsibility for any unauthorized use, modification, or alteration of this information. Employers are responsible for informing their employees and any other persons who may be affected of the hazards described in this sheet and of the precautions that should be taken to ensure safe handling and use of the product.