Issue date: 04-February-2015 Revision date: 21-October-2021 Supersedes date: 01-October-2020 Version number: 04



## SAFETY DATA SHEET

## 1. Identification

LATICRETE Permacolor Grout

**Product identifier** 

**Restrictions on use** 

None. Other means of identification

Recommended use of the chemical and restrictions on use

Grout. **Recommended use** 

> Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Details of manufacturer or importer		
Manufacturer		
Company Name	LATICRETE International	
Address	1 Laticrete Park, N	
	Bethany, CT 06524	
Telephone	(203)-393-0010	
Contact person	Steve Fine	
Website	www.laticrete.com	
Emergency phone number	Call CHEMTREC day or night	
	USA/Canada - 1.800.424.9300	
	Mexico - 1.800.681.9531	
	Outside USA/Canada	
	1.703.527.3887	
Supplier		
Company Name	LATICRETE Australia	
Address	P.O. Box 508	
	Virginia Business Mail Centre	
	29 Telford Street	
	VIRGINIA QLD 4014	
	AUSTRALIA	
Telephone	(61) (7) 3865-1599	
Website	www.laticrete.com	
Emergency phone number	1.703.527.3887	

## 2. Hazard(s) identification

## Classification of the hazardous chemical

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1A
	Specific target organ toxicity, repeated exposure	Category 2 (Lung)
Environmental hazards	Not classified.	

### Label elements, including precautionary statements

## Hazard symbol(s)



	hazard mark	
Signal word	Danger	
Hazard statement(s)	Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause damage to organs (Lung) through prolonged or repeated exposure.	
Precautionary statement(s)		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	IF exposed or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Other hazards which do not result in classification	None known.	
Supplemental information	None.	

## 3. Composition/information on ingredients

## Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Silica Sand	14808-60-7	55 - 65
Calcium aluminate cement	65997-16-2	5 - 15
Calcium sulfate	7778-18-9	5 - 7
Titanium dioxide	13463-67-7	0 - 8
Portland Cement	65997-15-1	10 -20
Dolomite	16389-88-1	1 - 4
Calcium sulfate hemihydrate	26499-65-0	1 - 2
Sodium aluminium sulfosilicate	57455-37-5	0 - 2
Iron oxide	1309-37-1	0 - 1
Lithium Carbonate	554-13-2	0.15-0.25

**Composition comments** 

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

Description of necessary f	first aid measures
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.

Personal protection for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.
Symptoms caused by exposure	Rash. Coughing. Irritant effects. Permanent eye damage including blindness could result. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Medical attention and special treatment	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.

Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for fire fighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes.	
Hazchem code	None.	

No unusual fire or explosion hazards noted.

6. Accidental release measures

General fire hazards

#### Personal precautions, protective equipment and emergency procedures

i oloollai procaaliollo, procociiro	requipinent and entergency procedules
For non-emergency personnel	Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation.
For emergency responders	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.
7. Handling and storage	

Precautions for safe handlingDo not handle until all safety precautions have been read and understood. Minimize dust<br/>generation and accumulation. Wear appropriate personal protective equipment. Do not breathe<br/>dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good<br/>industrial hygiene practices.Conditions for safe storage,Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

including any incompatibilities

## 8. Exposure controls and personal protection

## **Control parameters**

Follow standard monitoring procedures.

### Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable dust.
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Fume.
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	Inhalable dust.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Inhalable dust.

# Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inspirable dust.
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Fume.
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	Inspirable dust.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Inspirable dust.
ACGIH			
Components	Туре	Value	Form
Sodium aluminium sulfosilicate (CAS 57455-37-5)	TWA	3 mg/m3	RESPIRABLE PARTICLES
US. ACGIH Threshold Limit Values	5	10 mg/m3	INHALABLE PARTICLES
Components	Туре	Value	Form
Calcium sulfate (CAS	TWA	10 mg/m3	Inhalable fraction.
7778-18-9)		Ũ	
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
UK. EH40 Workplace Exposure Lin	mits (WELs)		
Components	Туре	Value	Form
Iron oxide (CAS 1309-37-1)	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Fume.
		4 mg/m3	Respirable.
		10 mg/m3	Inhalable
Portland Cement (CAS 65997-15-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Respirable.
		10 mg/m3	Inhalable
Germany. DFG MAK List (advisory in the Work Area (DFG)	/ OELs). Commission for the	Investigation of Health Hazard	s of Chemical Compounds
Components	Туре	Value	Form
Calcium sulfate (CAS	TWA	4 mg/m3	Inhalable fraction.

		1.5 mg/m3	Respirable fraction.
Biological limit values	No biological exposure limits noted for the ingredie	ent(s).	
Exposure guidelines	Occupational exposure to nuisance dust (total and should be monitored and controlled.	respirable) and resp	birable crystalline silica
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		

LATICRETE Permacolor Grout

7778-18-9)

917279 Version #: 04 Revision date: 21-October-2021 Issue date: 04-February-2015

Individual protection measures, for example personal protective equipment (PPE)		
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear chemical-resistant, impervious gloves.	
Other	Wear appropriate chemical resistant clothing.	
<b>Respiratory protection</b>	Wear a dust mask if dust is generated above exposure limits.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.	

## 9. Physical and chemical properties

AppearancePhysical stateSolid.FormPowder.ColorColored.OdorNot available.Odor thresholdNot available.pHNot available.	
FormPowder.ColorColored.OdorNot available.Odor thresholdNot available.	
ColorColored.OdorNot available.Odor thresholdNot available.	
OdorNot available.Odor thresholdNot available.	
Odor threshold Not available.	
nH Not available	
Melting point/freezing point Not available.	
Initial boiling point and boiling Not available. range	
Flash point         Not flammable or combustible.	
Evaporation rate Not available.	
Flammability (solid, gas) Not available.	
Upper/lower flammability or explosive limits	
Flammability limit - lower Not available. (%)	
Flammability limit - upper Not available. (%)	
Explosive limit - lower (%) Not available.	
Explosive limit - upper (%) Not available.	
Vapor pressure Not available.	
Vapor density Not available.	
Relative density Not available.	
Solubility(ies)	
Solubility (water) Insoluble	
Partition coefficient       Not available.         (n-octanol/water)       Not available.	
Auto-ignition temperature Not available.	
Decomposition temperature Not available.	
Viscosity Not available.	
10. Stability and reactivity	
Reactivity The product is stable and non-reactive under normal conditions of use, storage and transpor	t.
Chemical stability Material is stable under normal conditions.	
Possibility of hazardousNo dangerous reaction known under conditions of normal use.reactions	
Conditions to avoid Contact with incompatible materials.	
Incompatible materials Strong oxidizing agents.	
Hazardous decomposition       No hazardous decomposition products are known.         products       Image: Composition product are known.	

## 11. Toxicological information

## Information on possible routes of exposure

Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.
Skin contact	Causes skin irritation. Prolonged contact with wet cement/mixture may cause burns.
Eye contact	Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.
Ingestion	Swallowing may cause gastrointestinal irritation.
Symptoms related to exposure	Rash. Coughing. Irritant effects. Permanent eye damage including blindness could result. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

Acute toxicity May cause respiratory irritation.

Components	Species Test Results		
Calcium sulfate (CAS 7778-18-9)			
Acute			
Inhalation			
LC50	Rat	> 3.26 mg/l, 4 Hours	
Oral			
LD50	Rat > 1581 mg/kg		
Lithium Carbonate (CAS 554-13-2	2)		
Acute			
Oral			
LD50	Rat	525 mg/kg	
Sodium aluminium sulfosilicate (C	AS 57455-37-5)		
Acute	,		
Dermal			
LD50	Rabbit	> 3000 mg/kg	
Oral			
LD50	Rat	> 2000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/irritation	Causes serious eye damage.		
Respiratory or skin sensitizatio			
Respiratory sensitization	No data available.		
Skin sensitization	May cause an allergic skin reaction.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003)		
ACGIH Carcinogens			
Iron oxide (CAS 1309-37-1)		A4 Not classifiable as a human carcinogen.	
Portland Cement (CAS 6		A4 Not classifiable as a human carcinogen.	
Silica Sand (CAS 14808 Titanium dioxide (CAS 1		A2 Suspected human carcinogen. A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall		0	
Iron oxide (CAS 1309-37	-	3 Not classifiable as to carcinogenicity to humans.	
Silica Sand (CAS 14808	,	1 Carcinogenic to humans.	
LATICRETE Permacolor Grout	,	SDS Australi	

Titanium dioxide (CAS 1	3463-67-7)	2B Possibly carcinogenic to humans.
Reproductive toxicity	This product is not expected	to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	May cause damage to organs	(Lung) through prolonged or repeated exposure.
Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.	
Chronic effects	Prolonged or repeated exposure may cause lung injury, including silicosis.	
Other information	Inhalation of high concentration with cough and shortness of the second strategy of the sec	ons of quartz dust can lead to the lung disease known as silicosis, preath.

## 12. Ecological information

Ecotoxicity	Not expected to be harmful to aquatic organisms.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available for this product.
Mobility in soil	The product is insoluble in water and will sediment in water systems.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Disposal methods	Dispose of contents/container in accordance with local/regional/national/international regulations. Do not contaminate ponds, waterways or ditches with chemical or used container.
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

## ADG

Not regulated as dangerous goods.

## RID

Not regulated as dangerous goods.

## ΙΑΤΑ

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

Transport in bulk according to This substance/mixture is not intended to be transported in bulk. Annex II of MARPOL 73/78 and the IBC Code

## 15. Regulatory information

## Safety, health and environmental regulations

National regulationsThis Safety Data Sheet was prepared in accordance with the Australia National Code of Practice<br/>for the Preparation of Material Safety Data Sheets (NOHSC: 2011.)

High Volume Industrial Chemicals (HVIC)	
Calcium aluminate cement (CAS 65997-16-2)	1000 - 9999 TONNES See the regulation for additional information.
Calcium sulfate (CAS 7778-18-9)	10000 - 99999 TONNES See the regulation for additional information.
Iron oxide (CAS 1309-37-1)	1000 - 9999 TONNES See the regulation for additional information.
Portland Cement (CAS 65997-15-1)	> 1000000 TONNES See the regulation for additional information
Silica Sand (CAS 14808-60-7)	100000 - 999999 TONNES See the regulation for additional information.

Titanium dioxide (CAS 13463-67-7)	100000 - 999999 TONNES See the regulation for additional information.
Importation of Ozone Deleting Substances (Customs(Pro	hibited imports) Regulations 1956, Schedule 10)
Not listed.	
National Pollutant Inventory (NPI) substance reporting lis	st
Not listed.	
Prohibited Carcinogenic Substances	
Not regulated. Prohibited Substances (National Model Regulation for th NOHSC:1005 (1994) as amended)	e control of Workplace Hazardous Substances, Schedule 2
Not listed. Resricted Importation of Organochlorine Chemicals (Cus	toms(Prohibited Imports) Regulations 1956, Schedule 9)
Not listed. Restricted Carcinogenic Substances	
Not regulated.	
International regulations	
Stockholm Convention	
Not applicable. Rotterdam Convention	
Not applicable. <b>Kyoto protocol</b>	
Not applicable. Montreal Protocol	
Not applicable. Basel Convention	
Calcium sulfate (CAS 7778-18-9)	WASTE GYPSUM ARISING FROM CHEMICAL INDUSTRY PROCESSES, WHEN CONTAINING ANNEX I CONSTITUENTS TO THE EXTENT THAT IT EXHIBITS AN ANNEX III HAZARDOUS CHARACTERISTIC
International Inventories	

### In

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

Issue date	04-February-2015
Revision date	21-October-2021
References	HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)
Disclaimer	The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.