



STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
Date of Issue: 01/08/2024

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: STONETECH® Heavy Duty Grout Sealer

1.2. Intended Use of the Product

Seal cement-based grout.

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International
1 Laticrete Park, N
Bethany, CT 06524
T (203)-393-0010
www.laticrete.com

Company

LATICRETE Australia Pty Ltd
29 Telford St, Virginia, QLD, 4014
Australia
(07)-3865-1599
www.laticrete.com.au

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call ChemTel Inc. day or night:
(800)255-3924 (North America)
(800)-099-0731 (Mexico)
Australian Poisons Information Centre on 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Skin Sens. 1A H317
Aquatic Acute 2 H401

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)

:



GHS07

Signal Word (GHS-US/CA)

: Warning

Hazard Statements (GHS-US/CA)

: H317 - May cause an allergic skin reaction.
H401 - Toxic to aquatic life.

Precautionary Statements (GHS-US/CA)

: P261 - Avoid breathing vapors, mist, or spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P321 - Specific treatment (see section 4 on this SDS).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Fluorinated Acrylic Copolymer	(CAS-No.) Trade secret	0.5 - 1.5	Acute Tox. 4 (Inhalation:dust,mist), H332
Zinc pyrithione	(CAS-No.) 13463-41-7	0.009 – 0.015	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Inhalation:dust,mist), H330 Eye Dam. 1, H318 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Comb. Dust
3(2H)-Isothiazolone, 2-methyl-	(CAS-No.) 2682-20-4	0.007 – 0.0094	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Zinc oxide (ZnO)	(CAS-No.) 1314-13-2	0.006 – 0.009	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

An exemption has been granted from the Hazardous Materials Information Review Act (HMIRA) for the components indicated above as Trade Secret. See below for registry number(s) and their corresponding date(s) that exemption(s) were granted :

Fluorinated Acrylic Copolymer – 12090; 04/13/2018

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Skin sensitization.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: May cause an allergic skin reaction.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause an allergic skin reaction.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Hydrogen Fluoride (HF). Fluorinated hydrocarbons. Aldehydes. Ketones. Organic acids.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers, water-reactive materials.

7.3. Specific End Use(s)

Seal cement-based grout.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Zinc oxide (ZnO) (1314-13-2)		
USA ACGIH	ACGIH OEL TWA	2 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH OEL STEL	10 mg/m ³ (respirable particulate matter)
USA OSHA	OSHA PEL (TWA) [1]	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA)	5 mg/m ³ (dust and fume)
USA NIOSH	NIOSH REL (STEL)	10 mg/m ³ (fume)
USA NIOSH	NIOSH REL (Ceiling)	15 mg/m ³ (dust)
USA IDLH	IDLH	500 mg/m ³
Alberta	OEL STEL	10 mg/m ³ (respirable)
Alberta	OEL TWA	2 mg/m ³ (respirable)
British Columbia	OEL STEL	10 mg/m ³ (respirable)
British Columbia	OEL TWA	2 mg/m ³ (respirable)
Manitoba	OEL STEL	10 mg/m ³ (respirable particulate matter)
Manitoba	OEL TWA	2 mg/m ³ (respirable particulate matter)
New Brunswick	OEL STEL	10 mg/m ³ (fume)
New Brunswick	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica, dust) 5 mg/m ³ (fume)
Newfoundland & Labrador	OEL STEL	10 mg/m ³ (respirable particulate matter)
Newfoundland & Labrador	OEL TWA	2 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL STEL	10 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA	2 mg/m ³ (respirable particulate matter)
Nunavut	OEL STEL	10 mg/m ³ (dust and fume; respirable fraction)
Nunavut	OEL TWA	2 mg/m ³ (dust and fume; respirable fraction)
Northwest Territories	OEL STEL	10 mg/m ³ (dust and fume; respirable fraction)
Northwest Territories	OEL TWA	2 mg/m ³ (dust and fume; respirable fraction)
Ontario	OEL STEL	10 mg/m ³ (respirable particulate matter)
Ontario	OEL TWA	2 mg/m ³ (respirable particulate matter)
Prince Edward Island	OEL STEL	10 mg/m ³ (respirable particulate matter)
Prince Edward Island	OEL TWA	2 mg/m ³ (respirable particulate matter)
Québec	VECD (OEL STEL)	10 mg/m ³ (respirable dust)
Québec	VEMP (OEL TWA)	2 mg/m ³ (respirable dust)
Saskatchewan	OEL STEL	10 mg/m ³ (dust and fume, respirable fraction)
Saskatchewan	OEL TWA	2 mg/m ³ (dust and fume, respirable fraction)
Yukon	OEL STEL	10 mg/m ³ (fume)
Yukon	OEL TWA	5 mg/m ³ (fume) 30 mppcf (dust) 10 mg/m ³ (dust)

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Cloudy white
Odor	: Mild
Odor Threshold	: No data available
pH	: 4.0 – 5.0
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 1.003
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers, water-reactive materials.

10.6. Hazardous Decomposition Products:

Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

pH: 4.0 – 5.0

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Eye Damage/Irritation: Not classified

pH: 4.0 – 5.0

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause an allergic skin reaction

Potential Adverse human health effects and symptoms: Based on available data, the classification criteria are not met.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
LD50 Oral Rat	120 mg/kg
LD50 Dermal Rabbit	242 mg/kg
LC50 Inhalation Rat	0.11 mg/l/4h
Fluorinated Acrylic Copolymer (Trade secret)	
LD50 Oral Rat	> 5000 mg/kg
LC50 Inhalation Rat	1.5 mg/l/4h
Zinc pyrithione (13463-41-7)	
LD50 Oral Rat	177 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	1.03 mg/l
Zinc oxide (ZnO) (1314-13-2)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg (no deaths)
LC50 Inhalation Rat	> 5700 mg/m ³ (Exposure time: 4 h)

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Toxic to aquatic life.

Fluorinated Acrylic Copolymer (Trade secret)	
EC50 - Crustacea [1]	> 120 mg/l (Water flea)
Zinc pyrithione (13463-41-7)	
LC50 Fish 1	0.0026 mg/l
ErC50 algae	0.0026 mg/l
NOEC Chronic Fish	0.00122 mg/l
Zinc oxide (ZnO) (1314-13-2)	
LC50 Fish 1	970 µg/l (780 ug Zn/L; Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	1.793 mg/l (Exposure time: 96 h - Species: Zebrafish)
NOEC Chronic Fish	0.026 mg/l (Species: Jordanella floridae)

12.2. Persistence and Degradability

STONETECH® Heavy Duty Grout Sealer	
Persistence and Degradability	Not established.

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

12.3. Bioaccumulative Potential

STONETECH® Heavy Duty Grout Sealer

Bioaccumulative Potential	Not established.
---------------------------	------------------

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS: Zinc oxide (ZnO) ; Zinc pyrrhione)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

ERG Number : 171



14.2. In Accordance with IMDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS: Zinc oxide (ZnO) ; Zinc pyrrhione)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-F



14.3. In Accordance with IATA

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS: Zinc oxide (ZnO) ; Zinc pyrrhione)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

ERG Code (IATA) : 9L



14.4. In Accordance with TDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS: Zinc oxide (ZnO) ; Zinc pyrrhione)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

STONETECH® Heavy Duty Grout Sealer

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance. SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.
Zinc pyrithione (13463-41-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Zinc oxide (ZnO) (1314-13-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	

15.2. US State Regulations

STONETECH® Heavy Duty Grout Sealer	
State or local regulations	
Zinc oxide (ZnO) (1314-13-2)	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	

15.3. Canadian Regulations

3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Zinc pyrithione (13463-41-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Zinc oxide (ZnO) (1314-13-2)	
Listed on the Canadian DSL (Domestic Substances List)	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 01/08/2024

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1A	Skin sensitization, category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H301	Toxic if swallowed
H311	Toxic in contact with skin

STONETECH® Heavy Duty Grout Sealer

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)