

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE Ultra X8 Polymer Fortified Adhesive

Other means of identification None.

Recommended use of the chemical and restrictions on use

Recommended use Adhesive.

Restrictions on use Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Details of manufacturer or importer

Manufacturer

LATICRETE International Company name

Address 1 Laticrete Park, N

Bethany, CT 06524

(203)-393-0010 **Telephone**

Contact person Steve Fine

www.laticrete.com Website

Emergency phone number Call CHEMTREC day or night

> USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada

1.703.527.3887

Supplier

LATICRETE Australia Company name

Address P.O. Box 508

Virginia Business Mail Centre

29 Telford Street VIRGINIA QLD 4014

Australia

(61) (7) 3865-1599 **Telephone** Website www.laticrete.com **Emergency phone number** 1.703.527.3887

2. Hazard(s) identification

Classification of the hazardous chemical

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 1 Sensitization, skin Category 1 Carcinogenicity Category 1A

Specific target organ toxicity following single

exposure

Specific target organ toxicity following

repeated exposure

Category 2 (lung)

Category 3 respiratory tract irritation

Environmental hazards Not classified.

Label elements, including precautionary statements

Hazard symbol(s)



Signal word Danger

Hazard Statement(s) Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. May cause damage to organs (lung) through

prolonged or repeated exposure.

Precautionary Statement(s)

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove victim to fresh air Response

and keep at rest in a position comfortable for breathing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

Not classified.

Supplemental information None.

3. Composition/information on ingredients

Mixture

Identity of chemical ingredients	CAS number and other unique identifiers	Concentration of ingredients
Silica Sand	14808-60-7	55 - 65
Portland Cement	65997-15-1	30 - 40
Calcium formate	544-17-2	1 - 2
Kaolin clay	1332-58-7	1 - 2

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First-aid measures

Description of necessary first aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician Inhalation

if symptoms develop or persist.

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical Skin contact

advice/attention. Take off contaminated clothing and wash before reuse.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eye contact

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

centre immediately.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Personal protection for first-aid

responders

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated

clothing before reuse.

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and Symptoms caused by exposure

blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Medical attention and special

treatment

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

LATICRETE Ultra X8 Polymer Fortified Adhesive

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire

fighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

Hazchem Code None

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate

protective equipment and clothing during clean-up. Ensure adequate ventilation.

For emergency responders

Do not touch damaged containers or spilled material unless wearing appropriate protective

Environmental precautions

Methods and materials for

containment and cleaning up

Avoid discharge into drains, water courses or onto the ground.

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery,

flush area with water.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls and personal protection

Control parameters

Follow standard monitoring procedures.

Occupational exposure limits

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Туре	Value	Form	
Kaolin clay (CAS 1332-58-7)	TWA	10 mg/m3	Inhalable dust.	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	Inhalable dust.	
Silica Sand (CAS	TWA	0.1 mg/m3	Respirable dust.	

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational **Environment)**

Components	Туре	Value	Form	
Kaolin clay (CAS 1332-58-7)	TWA	10 mg/m3	Inspirable dust.	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	Inspirable dust.	
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3		

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Kaolin clay (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	Form
Kaolin clay (CAS 1332-58-7)	TWA	2 mg/m3	Respirable dust.
Portland Cement (CAS 65997-15-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide

eyewash station.

Individual protection measures, for example personal protective equipment (PPE)

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear chemical-resistant, impervious gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protectionWear a dust mask if dust is generated above exposure limits. **Thermal hazards**Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

(%)

Solid. Physical state Powder. **Form** Off-white. Colour Not available. Odour **Odour threshold** Not available. Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling range Not available. Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available. Flammability limit - lower

LATICRETE Ultra X8 Polymer Fortified Adhesive

Flammability limit - upper

(%)

Not available.

Not available. Vapour pressure Not available. Vapour density Not available. Relative density

Solubility(ies)

Insoluble. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition** temperature **Viscosity** Not available.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on possible routes of exposure

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Inhalation Skin contact

Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

Swallowing may cause gastrointestinal irritation. Ingestion

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and Symptoms related to exposure

blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

May cause respiratory irritation. **Acute toxicity**

Components	Species	Test results
Calcium formate (CAS 544-17-	-2)	
Acute		
Oral		
LD50	Rat	2650 mg/kg
Kaolin clay (CAS 1332-58-7)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg
Inhalation		
LC50	Rat	> 2 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	

Skin corrosion/irritation Causes skin irritation.

Causes serious eye damage.

Serious eye damage/irritation Respiratory or skin sensitisation

> Respiratory sensitisation No data available.

May cause an allergic skin reaction. Skin sensitisation

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded Carcinogenicity

that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer

risk..." (SCOEL SUM Doc 94-final, June 2003)

ACGIH Carcinogens

Kaolin clay (CAS 1332-58-7) A4 Not classifiable as a human carcinogen. Portland Cement (CAS 65997-15-1) A4 Not classifiable as a human carcinogen.

Silica Sand (CAS 14808-60-7) A2 Suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure.

Due to the physical form of the product it is not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged or repeated exposure may cause lung injury, including silicosis.

Inhalation of high concentrations of quartz dust can lead to the lung disease known as silicosis. Other information

with cough and shortness of breath.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Test results Components **Species**

Kaolin clay (CAS 1332-58-7)

Aquatic Acute

Crustacea LC50 Daphnia magna > 1.1 g/l, 48 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

The product is insoluble in water and will sediment in water systems. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

ADG

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

Safety, health and environmental regulations

National regulations

This Material Safety Data Sheet was prepared in accordance with the Australia National Code of Practice for the Preparation of Material Safety Data Sheets (NOHSC: 2011.)

Australia Medicines & Poisons Appendix B

Kaolin (CAS 1332-58-7)

High Volume Industrial Chemicals (HVIC)

Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7) > 1000000 TONNES See the regulation for additional information. 100000 - 999999 TONNES See the regulation for additional information.

Importation of Ozone Deleting Substances (Customs(Prohibited imports) Regulations 1956, Schedule 10)

Not listed

National Pollutant Inventory (NPI) substance reporting list

Not listed.

Prohibited Carcinogenic Substances

Not regulated.

Prohibited Substances (National Model Regulation for the control of Workplace Hazardous Substances, Schedule 2 NOHSC:1005 (1994) as amended)

Not listed.

Resricted Importation of Organochlorine Chemicals (Customs(Prohibited Imports) Regulations 1956, Schedule 9)

Not listed.

Restricted Carcinogenic Substances

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information

Issue date 20-July-2021

Revision date -

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).