



For The Builders of
A Better World

328

Thin-Set Adhesive



FEATURES

Interior & exterior use
High strength cement based adhesive
High tack, non sag
Extended open time
Economical
Easy to use

BENEFITS

Superior adhesion to a variety of internal and external substrates
Meets and exceeds to requirements of AS ISO 13007.1 & .2 as a C2TES1
Exhibits minimal or no sagging when applied in vertical or inverted applications
Increased productivity and working time
Saves time and money
High workability, easy to mix and trowel

Uses

- Interior and exterior applications
- Wall and floor installations
- Ceramic, porcelain, and natural stone tile

Suitable Substrates

- Concrete & Brick Masonry
- Cement Mortar Beds
- Cement Plaster
- Suitable Waterproof Membranes
- Gypsum Wall Board[^]
- Cement Backer Board[†]
- Cement Terrazzo
- Cement Terrazzo

[^] Interior use only

[†] Consult cement backer board manufacturer for specific installation recommendations and the verify acceptability for exterior use

Packaging

20kg bag; 56 bags per pallet

Colours

White & Grey

Meets and exceeds Applicable Standard

AS ISO 13007.1 & .2

Approximate Coverage per 20kg Bag

6mm x 6mm notched trowel	7 - 8m ²
10mm x 10mm notched trowel	4.5 - 5m ²
12mm x 12mm notched trowel	3.5 - 4m ²

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au

Snap for information.

