



**For The Builders of
A Better World**

PERMACOLOR® New & Improved Grout

PERMACOLOR® Grout is a high performance grout that provides a grout joint that is dense, hard and will resist cracking.



Product Data Sheet 1307



FEATURES

- Superior workability
- Consistent colour
- 1 step – mix with water
- Stain-resistant
- Versatile
- Equipped with antimicrobial properties
- Strong and durable cement-based grout
- Can be used as a coloured adhesive

BENEFITS

- Improved formula makes it easy to spread, work into joints, and clean up.
- No blotchiness, resists efflorescence (compared to other Portland cement-based grout).
- Easy to install, no additive required.
- Easy to clean, highly stain-resistant for a cement-based grout.
- Covers a wide range of joint widths; 1.5 mm – 12 mm.
- Inhibits the growth of stain-causing mould and mildew growth in the grout joints.
- Resists cracking and powdering.
- Mix with 4237 Latex Additive to use as a C2ES1 coloured tile adhesive

Uses

- Ceramic tile and stone applications
- Interior and exterior
- Floors and walls
- Swimming pools

Suitable Substrates

- Marble
- Porcelain tile
- Granite
- Quarry tile
- Ceramic tile
- Glass mosaic
- Stone

Colours

- 44 Bright White
- 88 Silver Shadow
- 89 Smoke Grey
- 78 Sterling Silver
- 17 Marble Beige
- 90 Light Pewter
- 18 Sauterne
- 23 Antique White
- 45 Raven
- 22 Midnight Black
- 96 Steamship*
- 24 Natural Grey
- 60 Dusty Grey
- 42 Platinum
- 03 Silk
- 91 Slate Grey
- 09 Frosty*
- 40 Latte
- 39 Mushroom
- 53 Twilight Blue

*New to the PERMACOLOR colour range

Approximate Coverage Per 10 kg Bag – m²

Tile Size	Joint Width				
	1.5 mm	3 mm	6 mm	9 mm	12 mm
25 x 25 x 6 mm	9.6	5.2	3.0	2.3	1.9
50 x 50 x 6 mm	18.3	9.6	5.2	3.7	3.0
100 x 100 x 8 mm	26.9	13.8	7.2	5.0	3.9
150 x 150 x 9 mm	35.6	18.1	9.3	6.4	4.9
200 x 200 x 9 mm	47.3	23.9	12.2	8.3	6.4
300 x 300 x 9 mm	70.7	35.6	18.1	12.2	9.3
350 x 350 x 9 mm	82.4	41.5	21.0	14.2	10.8
400 x 400 x 9 mm	94.1	47.3	24.0	16.1	12.2
450 x 450 x 9 mm	105.8	53.2	26.8	18.1	13.7
600 x 600 x 9 mm	140.9	70.7	35.6	23.9	18.1

Packaging

- 10 kg bag; 100 bags per pallet
- Available in top 20 colours.

For the latest information on the features and use of this product, consult the product Data Sheet on our website at www.laticrete.com.au

Certain types of stone and tile are more absorbent than others and will trap colour pigment during grouting. Prior to grouting, test for absorption of colour pigment. Porous tiles will need to be sealed prior to grouting, this includes polished porcelain. Care should be taken when using sanded grouts or soft faced tiles as scratching can occur.

Snap for information.

