



NEW RANGE GROUTS AND SEALANTS

COLOURED GROUTS AND SEALANTS

TECHNIQUE AND DESIGN FOR CONTEMPORARY LIVING

52 AVAILABLE COLOURS

For the Builders of a Better World™

A modern bathroom interior featuring a light-colored marble countertop and floor. The walls are covered in large, dark brown marble tiles. A white pedestal sink with a chrome faucet is on the left. A white toilet is in the center. A shower with a chrome showerhead is in the background. A white bathtub is on the right. The text "GROUTS AND SEALANTS" is overlaid in blue at the bottom.

GROUTS AND SEALANTS



TECHNIQUE AND DESIGN FOR CONTEMPORARY LIVING

The perfect synthesis of technology and design for today's living. **52 colours** to meet every design need.

The LATICRETE® product range adapts to the needs of any material and guarantees a higher level of reliability and quality. Choosing LATICRETE® means you can be sure that you have strong, durable and flexible solutions that can always make a difference.

INDEX

PERMACOLOR® SELECT	pag. 4
PERMACOLOR® SELECT FINE	pag. 5
PERMACOLOR®	pag. 6
COLORBASE FS	pag. 7
COLORBASE FL	pag. 8
SPECTRALOCK® PRO PREMIUM GROUT	pag. 9
SPECTRALOCK® PRO PREMIUM TRANSLUCENT GROUT	pag. 10
SPECTRALOCK® 2000 IG	pag. 11
LATASIL™	pag. 13
LATASIL™ AC	pag. 13
COLOUR CHART GROUTS AND SEALANTS	pag. 15



Watch the video



SPECTRALOCK® PRO PREMIUM GROUT | SPECTRALOCK® PRO PREMIUM TRANSLUCENT GROUT | SPECTRALOCK® 2000 IG
PERMACOLOR® SELECT | PERMACOLOR® SELECT FINE | PERMACOLOR® (NEW) | COLORBASE FS (NEW) | COLORBASE FL (NEW)
LATASIL™ | LATASIL™ AC (NEW)



PERMACOLOR® SELECT

Rapid setting cement-based grout for joints from 1.5 mm up to 12 mm



Package: 5.5 kg bag

Unit of sale: box of 4 bags



MICROBAN®

**NO VERTICAL SAG,
NO FADING,
NO EXPIRY.**



Exclusive patented technology of water-soluble pigments **COLOR KIT**

PERMACOLOR® SELECT is a high performance rapid setting cement-based grout that was the first to permit colouring with COLOR KIT – water-soluble pigments, to be added to the neutral base. Easy to mix, use and clean, PERMACOLOR SELECT is for joints on floors, walls and swimming pools.

FEATURES & BENEFITS

- For swimming pools, fountains and other applications in constant immersion
- Low VOC emissions (EC1 Plus) - safe and easy to install
- Requires no additional treatments - contains STONETECH® Sealer Technology
- Contains MICROBAN® anti-microbial protection - mould resistant
- Fibre reinforced - crack and shrink resistant
- Rapid setting - ready for foot traffic in as little as 3 hours
- Neutral base - the colour is obtained by mixing the COLOR KIT with water
- Exclusive Water Dispersion Technology for colour durability and aesthetics
- Complies with class CG2 WA as per EN 13888
- Max grain size: ~ 0.3 mm
- Pot life: ~ 60 min
- Foot traffic: ~ 3 hours
- Available in 52 colours

PERMACOLOR® SELECT FINE

High performance rapid cement-based fine grout for joints from 1 mm to 6 mm



Package: 3.6 kg bag
Unit of sale: box of 6 bags



MICROBAN®

FEATURES & BENEFITS

- For swimming pools, fountains and other applications in constant immersion
- Low VOC emissions (EC1 Plus) - safe and easy to install
- Ideal for extremely delicate surfaces such as prefinished marble
- Requires no additional treatments - contains STONETECH® Sealer Technology
- Contains MICROBAN® anti-microbial protection - mould resistant
- Fibre reinforced - crack and shrink resistant
- Rapid setting - ready for foot traffic in as little as 3 hours
- Neutral base - the colour is obtained by mixing the COLOR KIT with water
- Exclusive Water Dispersion Technology for colour durability and aesthetics
- Complies with class CG2 WA as per EN 13888
- Max grain size: ~ 0.15 mm
- Pot life: ~ 60 min
- Foot traffic: ~ 3 hours
- Available in 52 colours

EASY TO MIX COLOR KIT AVAILABLE IN 52 BRIGHT COLOURS

Exclusive **COLOR KIT** system that permits colouring with pigments contained in water-soluble pods to be mixed with the neutral base.



Choose your
COLOR KIT



Dissolve the Color Kit
IN WATER



Mix with the neutral base
PERMACOLOR® SELECT



And lastly:
GROUT



NEW



Package: 2.5 kg bag
Unit of sale: box of 4 bags



MICROBAN®

PERMACOLOR®

**High-performance rapid cement-based
grout for joints up to 10 mm**

PERMACOLOR® is a high-performance rapid setting cement-based ultra-fine grout for joints up to 10 mm. Easy to mix, use and clean, PERMACOLOR is for joints on floors, walls and swimming pools.

FEATURES & BENEFITS

- For swimming pools, fountains and other applications in constant immersion
- Low VOC emissions (EC1 Plus) - safe and easy to install
- Requires no additional treatments - contains STONETECH® Sealer Technology
- Contains MICROBAN® anti-microbial protection - mould resistant
- Fibre reinforced - crack and shrink resistant
- Rapid setting - ready for foot traffic in as little as 3 hours
- Exclusive Water Dispersion Technology for colour durability and aesthetics
- Complies with class CG2 WA as per EN 13888
- Max grain size: ~ 0.3 mm
- Pot life: ~ 60 min
- Foot traffic: ~ 3 hours
- Available in 30 colours

NEW

COLORBASE FS

Cement-based fine grout for joints from 1 to 8 mm

COLORBASE FS is a cement-based grout with a fine grain size, for making grout joints with glass mosaic, ceramic tiles, stone and marble. For interior and exterior applications, on floors and walls.

FEATURES & BENEFITS

- Complies with class CG2 WA as per EN 13888
- Easy to use and excellent workability
- Low VOC emissions (EC1 Plus)
- With very low water absorption and high abrasion resistance
- Mould resistant
- Max grain size: ~ 0.15 mm
- Pot life: ~ 30 min
- Foot traffic: ~ 24 hours
- Available in 30 colours



Package: 5 kg and 20 kg bag

Unit of sale:

- box of 4 bags of 5 kg each
- 20 kg bag





NEW



Package: 25 kg bag



COLORBASE FL

Cement-based coarse grain grout for joints from 3 to 30 mm

COLORBASE FL is a cement-based grout for joints of from 3 to 30 mm for ceramic tiles, thin brick, stone and marble. For interior and exterior applications, on floors and walls.

FEATURES & BENEFITS

- Complies with class CG2 WA as per EN 13888
- Easy to use and excellent workability
- Low VOC emissions (EC1 Plus)
- With very low water absorption and high abrasion resistance
- Mould resistant
- Max grain size: ~ 0.5 mm
- Pot life: ~ 90 min
- Foot traffic: ~ 6 hours
- Available in 8 colours

SPECTRALOCK® PRO PREMIUM GROUT

Waterproof three-component epoxy grout

SPECTRALOCK® PRO PREMIUM GROUT Three-component epoxy grout with ultra-long pot life for joints from 1.5 to 12 mm in ceramic tiles, mosaics and natural stone, waterproof, stainproof, adjustable consistency, oxide-free, EN 13888 RG, patented technology.



Package: 3.20 kg pail

Part A: 0.35 kg

Part B: 0.35 kg

Part C: 2.50 kg



MICROBAN

FEATURES & BENEFITS

- Ideal for submerged applications: swimming pools, fountains and water features
- High stain resistance
- Thixotropic formula for walls and floors
- Three-component, lets you regulate the consistency
- Maintenance free and does not fade
- Ideal for installations with broad temperature ranges
- Max grain size: ~ 0.3 mm
- Pot life: ~ 80 min
- Foot traffic: ~ 24 hours
- Available in 52 colours





Package: 5.08 kg pail
 Part A: 0.32 kg
 Part B: 0.66 kg
 Part C: 4.10 kg



MICROBAN

SPECTRALOCK® PRO PREMIUM TRANSLUCENT GROUT

Translucent and anti-stain three-component epoxy grout

Translucent version of SPECTRALOCK® PRO PREMIUM GROUT, an epoxy sealant mortar combining a long life and dirt resistance with extreme ease of use.

FEATURES & BENEFITS

- Translucent - lets light through
- Ideal for submerged applications - for swimming pools, fountains and water features
- For many types of tiles
- Strong, long-lasting and resistant to cracking
- Complies with class RG as per EN 13888
- Compressive strength: ~ 55.0 N/mm²
- Water absorption after 240 min: ~ 0.05 g
- Max grain size: ~ 0.3 mm
- Pot life: ~ 80 min
- Foot traffic: ~ 24 hours

SPECTRALOCK® 2000 IG



Three component epoxy grout particularly suited for industrial settings highly resistant to chemical agents

SPECTRALOCK® 2000 IG is an epoxy grout highly resistant to chemical agents, recommended for sealing joints of ceramic tiles of every type. SPECTRALOCK® 2000 IG combines high mechanical strength, durability and extraordinary chemical resistance to the most common corrosive substances, cleaners, foods and beverages.

Package: 10.20 kg pail

Part A: 2x0.52 kg

Part B: 2x0.98 kg

Part C: 2x4x0.90 kg



MICROBAN

FEATURES & BENEFITS

- High chemical resistance
- Excellent temperature resistance - ideal for cold storage rooms
- Equipped with antimicrobial technology
- Highly resistant to bacteria
- Washable with water
- Low VOC emissions (EC1) - better indoor air quality
- Fast curing, even cures at low temperature
- Exceeds ANSI 118.3 (Epoxy) and ANSI 118.5 (Furan)
- Complies with class RG as per EN 13888
- Available in 2 colours







Package: 310 ml cartridge
Unit of sale: box of 12 cartridges



LATASIL™

High performance single-component elastomeric universal silicone sealant with fungicide

LATASIL™ is a silicone sealant with neutral curing, designed to be used with ceramic tiles and stone.

FEATURES & BENEFITS

- Complies with EN 15651 parts 1,2,3 and 4
- Curing time: ~ 15 min
- Setting speed: ~ 2 mm/24 hours
- Universal sealant - ideal for natural stone, sanitary areas, swimming pools, façades, cold storage rooms and more besides
- Superior adhesion, especially on stone, metals and glass
- Antimicrobial and fungicidal - inhibits the onset of mould and growth of bacteria
- Low VOC emissions (EC1 Plus) - safe and easy to install
- Excellent weatherability, resistance to ageing, UV radiation and chemical agents



Package: 310 ml cartridge
Unit of sale: box of 12 cartridges



LATASIL™ AC

Acetic sealant with a low elastic modulus for ceramic tiles and bathroom fixtures

LATASIL™ AC is a silicone sealant with acetic curing, low module, bactericide and fungicide, for ceramic tiles and bathroom fixtures

FEATURES & BENEFITS

- Complies with EN 15651 parts 1, 2 and 3
- Superior adhesion, bactericide and fungicide
- Ideal for ceramic tiles, glass, clinker, bathroom fixtures, aluminium, anodised aluminium, plastic and painted surfaces
- Low VOC emissions (EC1 Plus) - safe and easy to install
- Easy to extrude and smooth
- Skin forming time: approximately 20 min
- Curing speed: approximately 3 mm / 24 hours
- Tensile strength: approximately 0.7 N/mm²
- Extension to break: approximately 250%



COLOUR CHART GROUTS AND SEALANTS

		SPECTRALOCK® PRO PREMIUM GROUT	SPECTRALOCK® 2000 IG	SPECTRALOCK® TRANSLUCENT	PERMACOLOR® SELECT	PERMACOLOR® SELECT FINE	PERMACOLOR®	COLORBASE FS	COLORBASE FL	LATASIL™	LATASIL™ AC
03	SILK	•			•	•					
04	ARCTIC BLUE	•			•	•	•	•			•
05	PASTEL BLUE	•			•	•					
06	LIMEADE	•			•	•					
07	LEMONADE	•			•	•	•	•			•
08	CHERRY RED	•			•	•	•	•			•
13	LICHEN	•			•	•					
14	MOSS	•			•	•					
16	SILTSTONE	•			•	•					
17	MARBLE BEIGE	•			•	•	•	•		•	•
18	SAUTERNE	•			•	•	•	•			•
22	MIDNIGHT BLACK	•			•	•	•	•			•
23	ANTIQUE WHITE	•			•	•	•	•	•		•
24	NATURAL GREY	•	•		•	•	•	• *	•		•
27	HEMP	•			•	•	•	•			•
30	SAND BEIGE	•			•	•	•	•			•
32	TURQUOISE	•			•	•					
33	BOSTON FERN	•			•	•	•	•			•
34	SANDSTONE	•			•	•					
35	MOCHA	•			•	•					
36	COPPER BEACH	•			•	•					
37	CHAMBRAY	•			•	•	•	•			•
38	RIVER ROCK	•			•	•	•	•			•
39	MUSHROOM	•			•	•					
40	LATTE	•			•	•	•	•			•
41	KASHMIR	•			•	•					
42	PLATINUM	•	•		•	•	•	• *			•
43	CHOCOLATE TRUFFLE	•			•	•					
44	BRIGHT WHITE	•			•	•	•	• *	•	•	•
45	RAVEN	•			•	•	•	• *	•	•	•
46	QUARRY RED	•			•	•					
47	CINNAMON	•			•	•					
50	SEA GLASS	•			•	•					
52	TOASTED ALMOND	•			•	•					
53	TWILIGHT BLUE	•			•	•					
55	TAWNY	•			•	•					
56	DESERT KHAKI	•			•	•	•	•			•
57	HOT COCOA	•			•	•					
58	TERRA COTTA	•			•	•	•	•			•
59	ESPRESSO	•			•	•	•	•			•
60	DUSTY GREY	•			•	•	•	•			•
61	PARCHMENT	•			•	•	•	•		•	•
66	CHESTNUT BROWN	•			•	•	•	•			•
67	AUTUMN GREEN	•			•	•					
78	STERLING SILVER	•			•	•	•	•	•	•	•
81	BUTTER CREAM	•			•	•	•	•	•	•	•
85	ALMOND	•			•	•	•	•	•		•
88	SILVER SHADOW	•			•	•	•	•			•
89	SMOKE GREY	•			•	•	•	• *	•	•	•
90	LIGHT PEWTER	•			•	•	•	•			•
91	SLATE GREY	•			•	•					
92	SALTILLO	•			•	•	•	•			•
00	TRANSLUCENT			•							•
		52	2	1	52	52	30	30	8	6	31

* 20 kg format available

The grouts and sealants colour chart is given merely as a guide. LATICRETE® Europe Srl does not warrant colour matching to this colour chart or to any colour guide produced. Actual shade and texture will depend on the product used, job site conditions, lighting, installation techniques and the colour and nature of the coating. Perform an application test outside the work and assess colour suitability after drying. No claims for colour shade variations will be honoured.

YOUR CHOICE OUR MISSION



**For the Builders of a
Better World™**



LATICRETE Europe S.r.l. a socio unico - Via Paletti, snc, 41051
Castelnuovo Rangone MO, Italia +39 059 535540