



# STONETECH® CLEANER ACID

DS-2102-0221

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

STONETECH® CLEANER ACID

## 2. MANUFACTURER

LATICRETE Europe S.r.l. a socio unico  
Via Paletti, snc, 41051

Castelnuovo Rangone MO, Italy

Telephone: +39 059 535540

Email: [info@laticreteurope.com](mailto:info@laticreteurope.com)

Website: [laticrete.eu](http://laticrete.eu)

## 3. PRODUCT DESCRIPTION

STONETECH® CLEANER ACID is a fast-working, water-based acidic cleaner with water-soluble solvents designed to remove polymer modified grout and cement residue from ceramic and porcelain tile. It can also be used to remove or clean efflorescence and limescale.

### Uses

- For interior and exterior use
- Countertops
- Backsplashes
- Bathroom vanities
- Floors
- Walls

### Advantages

- For removing polymer modified grout or cement residue
- Water-based acidic cleaner with water-soluble solvents — fast-acting
- Ideal for removing saline efflorescence or scaling

- Can be diluted to clean difficult grime and stains or used pure for deep cleaning

### Suitable Substrates

- Ceramic Tile
- Porcelain tile
- Quarry Tile

### Packaging

1 lt x 12/box

### Coverage / Consumption

up to 40 m<sup>2</sup> / 1 lt

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).>

### Cautions

Consult SDS for more safety information.

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Storage and Handling Instructions:** Store in a well-ventilated place. Keep container tightly closed. Do not breathe vapours. Use in a well-ventilated area. May cause drowsiness or dizziness. CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. May produce an allergic reaction. KEEP OUT OF THE REACH OF CHILDREN. Do not store above 100 °F (38 °C). Do not mix with other chemicals. Dispose of the contents/containers in accordance with the current legislation on waste treatment. Harmful to aquatic life with long lasting effects.

## 4. TECHNICAL DATA



## Physical Properties

Form:	Liquid
Colour:	Colourless / Light Amber
Odour:	Characteristic
pH:	1
VOC Content:	~365 g/lit

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of use and desired results. Be sure surfaces to be cleaned are swept or vacuumed to remove loose debris. Avoid skin and eye contact. Do not breathe vapours. Use in a well-ventilated area. Keep children and pets out of the area during application and drying.

### Directions

1. Conduct a preliminary test to determine dilution.
2. Use cleaner pure or diluted (maximum 1 part cleaner : 2 parts water). Pour evenly and uniformly on the surface.
3. Wait a few minutes, up to 30 minutes, depending on dirt to be removed. Then scrub with a clean, medium-abrasive sponge (use white pad on polished surfaces). Continue scrubbing while adding water.
4. Remove the residue with a wet vacuum cleaner, sponge, or clean cloth until dry.
5. Rinse area well with clean water.
6. Repeat if necessary.

*Note: Cleaner can also be used with single disc floor cleaner or high-pressure water and vacuum system.*

## 6. AVAILABILITY AND COST

### Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l.:

+39 059 535540

[info@laticreteurope.com](mailto:info@laticreteurope.com)

For on-line distributor information, visit [www.laticrete.eu](http://www.laticrete.eu).

### Cost

Contact LATICRETE EUROPE S.r.l to obtain complete information and cost.

## 7. WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year. Contact Technical

Services for further information. See 10. FILING SYSTEM:

- DS230.13EU: 1 Year Product Warranty (EN)

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade Sealers, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® STONE & TILE CLEANER is recommended.

Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the *TDS 262 Stone and Tile Care Guide*.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling or emailing the Technical Service Hotline:

+39 059 535540

[technicalservices@laticreteurope.com](mailto:technicalservices@laticreteurope.com)

### Technical and Safety Literature

To obtain technical and safety literature, please visit our website at [www.laticrete.eu](http://www.laticrete.eu).

### Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.

## 10. FILING SYSTEM

Additional product information is available on our website at [laticrete.eu](http://laticrete.eu). The following is a list of related documents:

- DS 230.13EU: 1 Year Product Warranty
- DS 2110: STONETECH STONE & TILE CLEANER
- DS 2125: STONETECH HEAVY DUTY EXTERIOR CLEANER

- DS 2150: STONETECH KLENZALL™ CLEANER
- TDS 262: Stone and Tile Care Guide