



# STONETECH® EPOXY GROUT HAZE & COATING STRIPPER

DS-65318-0121

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

STONETECH® EPOXY GROUT HAZE & COATING STRIPPER

## 2. MANUFACTURER

LATICRETE Europe S.r.l. a socio unico  
Via Paletti, snc, 41051  
Castelnuovo Rangone MO, Italy

Telephone: +39 059 535540

Email: [info@laticreteurope.com](mailto:info@laticreteurope.com)

Website: [laticrete.eu](http://laticrete.eu)

## 3. PRODUCT DESCRIPTION

STONETECH® EPOXY GROUT HAZE & COATING STRIPPER is a fast-acting, water-based cleaner that dissolves epoxy grout haze and tough epoxy coatings from vertical and horizontal surfaces in minutes. It is effective even after several days from application of epoxy grout. In 15 minute or less, this heavy duty cleaner wipes away epoxy grout haze and epoxy coatings without harsh solvents. It features a non-runny gel-like solution that adheres well to vertical applications.

### Uses

- Walls
- Floors
- Countertops
- Backsplashes

### Advantages

- Fast-acting — eliminates epoxy grout haze in 15 minutes or less\*

- Safely removes epoxy grout haze and epoxy coatings
- Non-runny — great for vertical and horizontal applications
- Water-based formula
- Low odor and no fumes
- No Methylene Chloride

*\*Do not exceed 15 minutes. Repeated short applications are recommended.*

### Suitable Substrates

- Natural Stone
- Terracotta
- Saltillo
- Ceramic Tile
- Glazed Ceramic
- Porcelain tile
- Glazed Porcelain
- Quarry Tile
- Glass Tile
- Masonry

### Packaging

1 lt x 12/box

### Coverage / Consumption

10-15 m<sup>2</sup> / 1 liter

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).>

### Limitations

- DO NOT exceed 15 minutes after application. Repeated short applications are recommended.
- NOT for use on highly sensitive stone such marble or polished limestone. Always test in a small inconspicuous area, as product can etch or dull stone.

### Cautions

Consult SDS for more safety information.

- If medical advice is needed, have product container or label at hand.

**Storage and Handling Instructions: DANGER:  
CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.**

MAY CAUSE DAMAGE TO ORGANS. Wear protective gloves/protective clothing/eye protection/face protection. Corrosive to the respiratory tract. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals.

#### 4. TECHNICAL DATA



#### Physical Properties

Form:	Gel-like liquid
Colour:	Light yellow
Odour:	Characteristic
pH:	2,5 (+/- 0.5)
VOC Content:	382 g/lit

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

#### 5. INSTALLATION

Read entire label before using. Use only as directed. Always test in a small inconspicuous area before application to determine ease of application and desired results. Be sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area until surface use resumes. Avoid contact with surfaces not intended to be treated.

#### Directions

1. SHAKE WELL BEFORE USING. Do not dilute before applying.
2. Liberally apply an even coat of STONETECH® EPOXY GROUT HAZE & COATING STRIPPER over the area with a paint brush, mop or paint pad. On vertical surfaces, apply from bottom to top. Immediately remove product from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.
3. Let STONETECH® STONETECH® EPOXY GROUT HAZE & COATING STRIPPER penetrate for 5-10 minutes.
4. Do not let product dry on the surface. If it starts to dry, add more to keep surface wet.
5. After 5-10 minutes, agitate surface with a nylon scrub brush or abrasive pad after testing a small area first to make sure that brush or pad will not scratch stone.
6. Wipe up residue with clean, dry cloth or wet mop. A wet/dry vacuum can be used for larger area.
7. Rinse surface well with clean water.

8. More than one application may be required, repeat steps 1 through 7 when necessary.

*Note: Do not exceed 15 minutes during each application as it may damage surface. Repeated short applications are recommended.*

#### 6. AVAILABILITY AND COST

##### Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE EUROPE S.r.l.:

+39 059 535540

[info@laticreteurope.com](mailto:info@laticreteurope.com)

For on-line distributor information, visit [www.laticrete.eu](http://www.laticrete.eu).

##### Cost

Contact LATICRETE EUROPE S.r.l to obtain complete information and cost.

#### 7. WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year. Contact Technical Services for further information. See 10. FILING SYSTEM:

- DS230.13EU: 1 Year Product Warranty (EN)

#### 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance.

Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® STONE & TILE CLEANER is recommended. For tough or difficult to remove soil use STONETECH KLENZALL™ CLEANER, a nylon scrubbing pad or a long handled stiff bristle brush.

Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the *TDS 262 Stone and Tile Care Guide*.

#### 9. TECHNICAL SERVICES

##### Technical Assistance

Information is available by calling or emailing the Technical Service Hotline:

+39 059 535540

[technicalservices@laticreteurope.com](mailto:technicalservices@laticreteurope.com)

##### Technical and Safety Literature

To obtain technical and safety literature, please visit our website at [www.laticrete.eu](http://www.laticrete.eu).

## Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.

## 10. FILING SYSTEM

Additional product information is available on our website at [laticrete.eu](http://laticrete.eu). The following is a list of related documents:

- DS 230.13EU: 1 Year Product Warranty
- DS 2110: STONETECH STONE & TILE CLEANER
- DS 2150: STONETECH KLENZALL™ CLEANER
- TDS 262: Stone and Tile Care Guide