



# STONETECH® EPOXY CARE & CLEAN

DS-65318B-0126

For the Builders of a  
Better World™



## 1. PRODUCT NAME

STONETECH® EPOXY CARE & CLEAN

## 2. MANUFACTURER

LATICRETE EUROPE S.r.l. sole proprietorship  
Via Paletti, snc, 41051  
Castelnuovo Rangone (MO), Italy

Telephone: +39 059 535540

Email: [info@laticreteeurope.com](mailto:info@laticreteeurope.com)

Website: <https://eu.laticrete.com/>

## 3. PRODUCT DESCRIPTION

STONETECH®EPOXY CARE & CLEAN is a fast-acting liquid cleaner suitable for removing post-installation stains and resin residues caused by the application of epoxy sealants such as SPECTRALOCK® PRO PREMIUM GROUT, LATAPOXY® 210 GROUT, SPECTRALOCK® PRO PREMIUM TRASLUCENT GROUT and SPECTRALOCK® 2000 IG from all types of ceramic tiles. It does not contain aggressive solvents but effectively removes epoxy resin stains.

### Uses

- Cleaning epoxy resin stains from ceramic floor tiles, wall tiles, bathroom and kitchen countertops, and kitchen backsplashes after installation.

### Advantages

- Fast-acting cleaner
- Easy to use with spray applicator
- Water-based formula
- Mild odour, no vapours

### Suitable surfaces

- Natural stone
- Glazed terracotta
- Ceramic tiles
- Glazed ceramic
- Porcelain stoneware
- Glazed porcelain
- Glass tiles
- Klinker
- Glass mosaic

### Packaging

Spray dispenser

1,0 l, 4 dispensers per box

### Coverage/Consumption

10 to 15 m<sup>2</sup> per 1,0 l dispenser

### Storage

Twenty-four (24) months in original unopened packaging, stored indoors and off the ground at temperatures between 5°C and 35°C

### Limitations

- Use the cleaner after the grout has completely hardened (approximately 24 hours at a temperature of 23°C and 50% relative humidity) and no later than 48 hours after grouting. For residues left for more than 48 hours, the product may take longer to remove. We do not recommend waiting longer than 72 hours.
- Avoid contact or application with surfaces not intended for treatment.

### Warnings

- Avoid contact with skin and eyes. In case of irritation, wash thoroughly with clean, cool water. In case of contact with eyes, seek medical advice immediately.
- When applying to natural stone, it is advisable to carry out a preliminary test.
- FOR PROFESSIONAL USE

For further information, consult the product safety data sheet.

## 4. TECHNICAL DATA

### Physical properties

Form:	Liquid
Colour:	Whitish
Odour:	Mild

(data measured at +23°C, 50% relative humidity)

The technical data provided is measured under standard laboratory conditions and is subject to change without notice. The actual performance of the product depends on the application conditions on site, the installation method used and the type of covering.

## 5. APPLICATION

Read the label carefully before use. Use only as directed. Ensure that the surfaces to be cleaned are swept or vacuumed to remove dust or debris. Ensure that the work area is well ventilated during application and until the surface is dry. Keep children and pets away from the area during use. Avoid contact or application with surfaces not intended for treatment.

### Application

Use the cleaner after the grout has completely hardened (approximately 24 hours at a temperature of 23°C and 50% relative humidity) and no later than 48 hours after grouting. For residues left for more than 48 hours, the product may need to be left on for longer. We do not recommend waiting longer than 72 hours.

1. Shake well and do not dilute the product before use.
2. Spray STONETECH® EPOXY CARE & CLEAN pure evenly and uniformly onto the surface to be cleaned. Immediately remove the product from untreated surfaces with a damp cloth to avoid potential damage to those surfaces.
3. Leave STONETECH® EPOXY CARE & CLEAN on the surface for at least 15 minutes.
4. Do not allow the product to dry on the surface. Add more to keep the surface wet if necessary.
5. After about 15 minutes, scrub the surface with WHITE FELT or with a single-brush machine fitted with a White Felt disc, after first testing a small area to ensure that the single-brush machine does not damage the surface.
6. Rinse the treated surface thoroughly with clean water using a damp sponge or suitable accessories for collecting liquids (rubber rake or wet vacuum if the surface is large).
7. Dry the surface with a clean cloth or absorbent paper. Do not wait for the rinse water to evaporate as this may leave marks on the surface. If additional applications are necessary, repeat steps 1 to 7.

## 6. AVAILABILITY AND COSTS

### Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE Europe S.r.l. a socio unico:

Telephone: +39 059 535540

Email: [info@laticreteeurope.com](mailto:info@laticreteeurope.com)

Website: <https://eu.laticrete.com/>

### Prices

Contact your nearest LATICRETE EUROPE S.r.l. product dealer for complete pricing information.

## 7. WARRANTY

The supplier guarantees that the product will not deteriorate under normal conditions of use. The warranty is valid for one (1) year. Contact Technical Support for further information.

## 8. MAINTENANCE

LATICRETE® and LATAPOXY® are products of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending of the cleaning products used.

## 9. TECHNICAL SERVICES

### Technical Assistance

For information, contact Technical Service

Telephone: +39 059 535540

Email: [info@laticreteeurope.com](mailto:info@laticreteeurope.com)

### Technical and safety literature

To obtain technical and safety literature, please visit our website: <https://eu.laticrete.com/>

### Warnings

The information and the instructions in the data sheet, although based on knowledge gained through years of applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.

## 10. DOCUMENTATION

Further product information is available on our website at <https://eu.laticrete.com/>.