



WPM TAPE PLV

DS-65326-0522

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

WPM TAPE PLV

2. MANUFACTURER

LATICRETE Europe S.r.l. a socio unico
Via Paletti, snc, 41051

Castelnuovo Rangone MO, Italy

Telephone: +39 059 535540

Email: info@laticreteurope.com

Website: laticrete.eu

3. PRODUCT DESCRIPTION

WPM TAPE PLV is a flexible self-adhering alkali resistant waterproofing tape made of butyl rubber on the upper side and non-woven polyester, used for waterproofing expansion joints, perimetry joints and water overflow points.

WPM is self-adhering, making it easy to apply, and guarantees a seal immediately after application.

Uses

- For interior use only
- For flexible waterproofing of joints, covers, corners and change of plane
- Good for expansion joints, perimeter joints and water outflow points
- Suitable for applications with medium load of non-pressurized water (i.e. showers, bathrooms or kitchens)

Advantages

- Entire width of tape is waterproof and flexible, making it easy to apply
- Alkali resistant
- Self adhering — immediately seals after application
- Compatible with HYDRO BAN SHEET MEMBRANE, AQUA BARRIER and AQUA BARRIER RDY waterproofing products

Suitable Substrates

- Concrete
- Cement Mortar/Render
- Cement Plaster
- Gypsum Wallboard
- Cement Backer Board
- Plastic
- Wood or Metal Studded Walls (Interior Only)

Packaging

L 28753

10 m roll; 500 rolls pallet

Shelf Life

Unlimited. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun).

Limitations

- DO NOT use over structural joints or cracks/joints with vertical differential movement.
- DO NOT expose to negative hydrostatic pressure, rubber solvents or ketones.
- Must be covered with ceramic tile or stone. Use protection board for temporary cover.
- Any joint treated with WPM TAPE PLV must be maintained in the finish with LATASIL silicone sealant.

Cautions

- Apply only over dry substrates as humidity and condensation reduce adhesion performance.
- Apply only over perfectly clean surfaces as dust or dirt reduce adhesion performance.
- Carefully press the entire tape to ensure bond (suggest using a rubber hammer).
- Remove the release liner at temperatures < 28°C.

4. TECHNICAL DATA



VOC/LEED Product Information

- GEV EMICODE: EC1 Plus
- ÉMISSIONS DANS L'AIR INTÉRIEUR: A+

Applicable Standard

- ISO 9001:2015 Quality Management System

Physical Properties

Colour:	Grey	
Width:	120 mm	
Thickness:	0,77 mm	
Weight:	730 g / m ²	
Resistance to Temperature:	-30°C to +60 °C	
Property	Test Method	Values
Burst Pressure (maximum):	Internal	0,4 bar
Longitudinal Breaking Load:	DIN EN ISO 527-3	30 N / 15 mm
Lateral Breaking Load:	DIN EN ISO 527-3	19 N / 15 mm
Longitudinal Resistance to Tearing:	DIN EN ISO 527-3	60%
Lateral Resistance to Tearing:	DIN EN ISO 527-3	80%
Resistance to Water Pressure:	DIN EN 1928 (Version B)	≥ 0,2 bar
Peel Test (PVC):	Internal	≥ 13 N / 20 mm

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

All substrates must be structurally sound, clean and free of dirt, oil, grease, paint, laitance, efflorescence, concrete sealers or curing compounds. Make rough or uneven concrete smooth to a wood float or better finish with a suitable LATICRETE underlayment.

Application

Cut the joint sealing tape to the appropriate size before applying.

Substrate should be above +10°C during installation. Remove the release liner, place the joint sealing tape

into the correct position and press down firmly with a spatula or smooth trowel. Remove all air pockets.

For any sections where two strips of tape will be joined, be certain to overlap the material by 50 mm and press the overlap area to reduce thickness (suggest using a rubber hammer or mallet). Continue with these steps around the perimeter of the installation.

Treat vertical corners with the joint sealing tape in the same manner as the floor-to-wall transitions.

Note: Important, there should not be excessive overlapping.

6. AVAILABILITY AND COST

Availability

LATICRETE® materials are available worldwide. For distributor information, please contact LATICRETE Europe S.r.l. a socio unico:

+39 059 535540

info@laticreteeurope.com

For on-line distributor information, visit www.laticrete.eu.

Cost

Contact LATICRETE Europe S.r.l. a socio unico to obtain complete information and cost.

7. WARRANTY

The supplier warrants that the product will not deteriorate under normal conditions and use. The warranty validity of one (1) year. Contact Technical Services for further information. See 10. FILING SYSTEM:

- DS 230.13EU: 1 Year Product Warranty

8. MAINTENANCE

LATICRETE® and LATAPOXY® are products of high quality designed to achieve lasting installations and avoid maintenance, however performance and durability may depend on properly maintaining products, depending on the cleaning products used.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling or emailing the Technical Service Hotline:

+39 059 535540

technicalservices@laticreteeurope.com

Technical and Safety Literature

To obtain technical and safety literature, please visit our website at www.laticrete.eu.

Warning

The information and the instructions in the data sheet, although based on knowledge gained through years of

applications, are indicative. LATICRETE® is unable to directly control the installation methods and conditions of products and does not assume any liability arising from their implementation. Those who want to use LATICRETE® products should conduct adequate tests to determine the site specifications. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation method and site conditions.

LATICRETE® products are covered by a warranty within the limits of what is established by our general conditions of sale and within the limits of correspondence related to technical specifications and applicable certifications, as expressly indicated in the product data sheets, documentation, or applicable technical documentation.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.eu. The following is a list of related documents:

- DS230.13EU: 1 Year Product Warranty
- DS 410: HYDRO BAN® SHEET MEMBRANE Product Data Sheet
- DS 752: AQUA BARRIER RDY Product Data Sheet
- DS 751: AQUA BARRIER Product Data Sheet
- TDS 192: Installation of Ceramic Tile in Swimming Pools
- TDS 157: Exterior Installation of Tile and Stone Over Occupied Space