



STONETECH® TERRACE PROTECT

DS-65538-0126

For the Builders of a Better World™



- Water-repellent and breathable protective treatment for valuable architectural and decorative elements in historic buildings.

Advantages

- Effective in cracks up to 1 mm wide
- It spreads effectively throughout the entire thickness of the cracks.
- It is water-repellent and prevents water and dirt from penetrating deep into the materials and consequently into the structures immediately after drying.
- It is breathable, allowing water vapour to escape.
- It is transparent, does not alter the colour characteristics of surfaces, does not create surface films and does not yellow.
- It is easy to use and can also be applied in the presence of slight and uniform residual moisture.

Suitable substrates

- Concrete
- Bricks
- Terracotta
- Natural stone
- Artificial stone
- Unglazed tiles
- Porcelain stoneware
- Clinker
- Plaster

Packaging

0.25 l and 1 l bottles and 5 l cans

Coverage/Consumption

From 50 ml/m² to 100 ml/m² depending on the absorption of the substrate.

Storage

Twelve (12) months in original unopened packaging stored off the ground in a cool, dry place. High humidity will reduce the shelf life of the product.

Limitations

- Ensure that subsequent coats are applied when the previous ones are dry.
- DO NOT apply if rain or fog is expected in the next 4-8 hours.
- DO NOT apply at temperatures below +5°C or above +35°C.
- Seal cracks larger than 1 mm and defective joints before application.

1. PRODUCT NAME

STONETECH® TERRACE PROTECT

2. MANUFACTURER

LATICRETE EUROPE S.r.l. a socio unico
Via Paletti, snc, 41051
Castelnuovo Rangone (MO), Italy

Telephone: +39 059 535540

Email: info@laticreteurope.com

Website: <https://eu.laticrete.com/>

3. PRODUCT DESCRIPTION

STONETECH TERRACE PROTECT is a ready-to-use water-based product containing stable functionalised fluoroderivatives, ideal for protecting absorbent and cracked products and substrates, making them water-repellent and chemically resistant. STONETECH TERRACE PROTECT penetrates deep into cracks, solving and preventing water infiltration problems caused by structural settling in joints and tiles.

Uses

- Protects terraces, balconies and cladding in terracotta, clinker, ceramics in general and porcelain stoneware, natural stone, concrete and composite materials.
- It does not promote an environment conducive to the formation of mould and the adhesion of organic dirt on the surfaces to which it is applied.
- Protects walls and floors inside bathrooms and showers from moisture infiltration.

Warnings

- Do not use the product if the packaging is not in perfect condition.
- The surface can only be walked on after it has completely dried.
- Keep out of reach of children.
- For professional use

For further information, consult the product safety data sheet.

4. TECHNICAL DATA

Standard

- ISO 9001:2015: CERT-09019-2001-AQ-BOL-SINCERT

Physical properties

Contents	Homogeneous liquid
Colour	Colourless
Odour	Odourless
Specific gravity (20°C)	1.008 kg/l
pH (20°C)	5.0 +/- 0.5

(data measured at +23°C, 50% relative humidity)

The technical data provided is measured under standard laboratory conditions and is subject to change without notice. The actual performance of the product depends on the application conditions on site, the installation method used and the type of coating.

5. APPLICATION

STONETECH TERRACE PROTECT is ready to use.

Apply a single coat to a clean, dry or evenly damp surface.

Spread the product evenly with a brush or roller on the surface to be treated, applying more generously to joints and cracks.

If applied to low-absorption materials such as porcelain stoneware and glazed materials, remove any excess product from the surface with a dry, clean cloth before it dries completely.

6. AVAILABILITY AND COSTS

Availability

LATICRETE® products are available worldwide. To find your nearest dealer, please contact LATICRETE EUROPE S.r.l.

Telephone: +39 059 535540

Email: info@laticreteeurope.com

Website: <https://eu.laticrete.com/>

Prices

Contact your nearest LATICRETE EUROPE S.r.l. product distributor for complete pricing information.

7. WARRANTY

The supplier guarantees that the product will not deteriorate under normal conditions of use. The warranty is valid for one (1) year. Contact Technical Support for further information.

8. MAINTENANCE

LATICRETE® products are high quality products designed to provide long-lasting, maintenance-free installations; however, durability and performance are strictly dependent on the type of cleaning products used.

9. TECHNICAL SERVICES

Technical Assistance

For information, contact Technical Service

Telephone: +39 059 535540

Email: info@laticreteeurope.com

Technical and safety literature

For technical and safety literature, visit our website:

<https://eu.laticrete.com/>

Warnings

The information and instructions contained in this Technical Data Sheet, although based on knowledge acquired over years of application, are to be considered indicative. LATICRETE® cannot directly control the installation conditions and application methods of the products and therefore assumes no responsibility for their use. Those intending to use LATICRETE® products must conduct adequate site tests to determine their suitability for the intended use. Our products are covered by warranty within the limits established by our general terms and conditions of sale and within the limits of our products' compliance with the applicable technical specifications and certifications, as expressly indicated in the product data sheets or applicable technical documentation expressly provided by us with the products themselves.

10. DOCUMENTATION

Further product information is available on our website

at <https://eu.laticrete.com/>.