



# AQUA BARRIER LASTIK PRIMER

DS-6681-0226

For the Builders of a  
Better World™



## 1. PRODUCT NAME

**AQUA BARRIER LASTIK PRIMER**

## 2. MANUFACTURER

LATICRETE EUROPE S.r.l. sole shareholder  
Via Paletti, snc, 41051  
Castelnuovo Rangone (MO), Italy  
Phone +39 059 535540  
Email [info@laticreteeurope.com](mailto:info@laticreteeurope.com)  
Website: <https://eu.laticrete.com/>

## 3. PRODUCT DESCRIPTION

AQUA BARRIER LASTIK PRIMER is a water-based primer with synthetic resins and additives specifically designed for adhesion to smooth or low-absorbent surfaces.

### Uses

- Anti-dust preparation for substrates before laying prefabricated bituminous membranes
- Anti-dust preparation for substrates before laying AQUA BARRIER LASTIK
- As an adhesion primer on polymer bitumen membranes before applying AQUA BARRIER LASTIK

### Advantages

- Ready to use
- Easy and quick to install, saving considerable time during installation

- Adheres to many substrates commonly used in construction
- Application by brush or roller
- High yield

### Suitable substrates

- Concrete
- Tiles and stone
- Bricks
- Plasterboard
- Wood
- Cement plaster
- Polymer bitumen membranes

### Packaging

5 kg bucket

### Yield/Consumption

From 0.10 kg/m<sup>2</sup> to 0.50 kg/m<sup>2</sup>

From 0.10 kg/m<sup>2</sup> to 0.50 kg/m<sup>2</sup> as a primer on polymer bitumen membranes

### Storage

Twenty-four (24) months in original unopened packaging, stored off the ground in a cool, dry place. High humidity will reduce the shelf life of the product. Do not store at temperatures below 5°C.

### Limitations

- Ensure that subsequent coats are applied when the previous ones are dry.
- Do not apply the product to damp surfaces (residual moisture content below 5%) or very hot surfaces.
- DO NOT apply if rain, fog, or frost is expected.
- DO NOT apply at temperatures below +5°C or above +35°C.
- Avoid application in direct sunlight.

### Warnings

- For further information, consult the product safety data sheet.
- Protect the work from frost and foot traffic until completely hardened.
- DO NOT install at temperatures below +5°C or above +35°C.
- NOT for use as a wear surface.
- Keep out of reach of children.
- **FOR PROFESSIONAL USE**

For further information, consult the product safety data sheet.

## 4. TECHNICAL DATA

### Standard

- ISO 9001:2015: CERT-09019-2001-AQ-BOL-SINCERT

### Physical properties

Contents	Water-based primer
Color	Gray
Density	~ 1550 kg/m <sup>3</sup>
Dry residue (m/m at 130°C)	66 - 74
Brookfield viscosity (at 20°C)	800 – 1500 cP

### Processing characteristics

Drying time	Approximately 60 minutes
Application	Sponge roller, brush
Application temperatures	From +5°C to +35°C

(data measured at +23°C, 50% relative humidity)

The technical data provided is measured under standard laboratory conditions and is subject to change without notice. The actual performance of the product depends on the application conditions on site, the application method used, and the type of coating.

## 5. APPLICATION

### Preparation of substrates

All surfaces must be flat, structurally sound and compact, with no loose parts and free of dust, grease, oil, paint and wax. Surface temperatures must be between 5°C and 35°C.

Ceramic and stone substrates must be clean, mechanically resistant, and perfectly anchored to the substrate.

Check that water drainage points are solid and efficient.

### Application

Mix the product thoroughly before use. Apply AQUA BARRIER LASTIK PRIMER with a sponge roller, brush, or paintbrush in a single coat. The consumption of AQUA BARRIER LASTIK PRIMER may vary depending on the degree of absorption of the substrate.

## 6. AVAILABILITY AND COSTS

### Availability

LATICRETE® products are available worldwide. To find your nearest dealer, contact LATICRETE EUROPE S.r.l.

Phone: +39 059 535540

Email: [info@laticreteurope.com](mailto:info@laticreteurope.com)

Website: <https://eu.laticrete.com/>

### Prices

Contact your nearest LATICRETE EUROPE S.r.l. product dealer for complete pricing information.

## 7. WARRANTY

The supplier guarantees that the product will not deteriorate under normal conditions of use. The

F.7.3.12 – 0315

Technical data sheets are subject to change without notice. For the latest revision, visit <https://eu.laticrete.com/>.

warranty is valid for one (1) year. Contact Technical Service for further information.

## 8. MAINTENANCE

LATICRETE® products are high quality products designed to provide long-lasting, maintenance-free installations; however, durability and performance are strictly dependent on the type of cleaning products used.

## 9. TECHNICAL SERVICES

### Technical Assistance

For information, contact Technical Service.

Phone: +39 059 535540

Email: [info@laticreteurope.com](mailto:info@laticreteurope.com)

### Technical and safety literature

For technical and safety literature, visit our website:

<https://eu.laticrete.com/>

### Warnings

The information and instructions contained in this Technical Data Sheet, although based on knowledge acquired through years of application, are to be considered indicative. LATICRETE® cannot directly control the installation conditions and application methods of the products and therefore assumes no responsibility for their use. Those intending to use LATICRETE® products must conduct adequate field tests to determine suitability for the intended use. Our products are covered by warranty within the limits established by our general terms and conditions of sale and within the limits of our products' compliance with the applicable technical specifications and certifications, as expressly indicated in the product data sheets or applicable technical documentation expressly provided by us with the products themselves.

## 10. DOCUMENTATION

Further product information is available on our website at <https://eu.laticrete.com/>.