



COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: COLORBASE FL G.

24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY

24-FLxx-0005-2-G

Other means of identification:

UFI: X250-T05M-5003-PDSV

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Mortar. For professional users only.

PROC 19: manual mixing with direct contact, only use of an individual protective device (DPI).

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

LATICRETE EUROPE SRL

Via Paletti Snc

41051 Castelnuovo Rangone - ITALY

Phone: 059535540 info@laticreteeurope.com https://eu.laticrete.com/

1.4 Emergency telephone number: NHS Direct (UK): +44 0845 46 47

Europe's emergency number: 112

Company number (08:00 - 18:00 CET): (+39) 059 535540

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger





Hazard statements:

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1B: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Substances that contribute to the classification

Cement, portland, chemicals; Flue dust, portland cement

UFI: X250-T05M-5003-PDSV

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

- CONTINUED ON NEXT PAGE
Date of compilation: 17/03/2020 Revised: 26/05/2022 Version: 2 (Replaced 1) Page 1/11

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



Page 2/11

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS *

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of hydraulic binders, lime, aggregates and additives

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification				
CAS:	65997-15-1	Cement, portland, chemica	ement, portland, chemicals ¹ Self-classified				
Index:	266-043-4 Non-applicable Non-applicable	Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 - Danger	(1)	25 - <40 %		
CAS: EC: Index: REACH:	68475-76-3 270-659-9 Non-applicable 01-2119486767-17-XXXX	Flue dust, portland cement	1	Self-classified			
		Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	<u>(1)</u>	1 - <2 %		
CAS: 1305-62-0		Calcium dihydroxide ²		Self-classified			
Index:	215-137-3 Non-applicable 01-2119475151-45-XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	(1)	<1 %		

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

- CONTINUED ON NEXT PAGE -

² Substance with a Union workplace exposure limit

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 5: FIREFIGHTING MEASURES (continued)

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Use in ventilated areas. Avoid the build up of dust

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-inflammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Keep the container tightly sealed and protected from open air and humidity.

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.





COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Calcium dihydroxide	IOELV (8h)		1 mg/m³
CAS: 1305-62-0 EC: 215-137-3	IOELV (STEL)		4 mg/m³

Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Flue dust, portland cement	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68475-76-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 270-659-9	Inhalation	Non-applicable	4 mg/m³	Non-applicable	0,84 mg/m³
Calcium dihydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1305-62-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-137-3	Inhalation	Non-applicable	4 mg/m³	Non-applicable	1 mg/m³

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Flue dust, portland cement	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68475-76-3	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 270-659-9	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,84 mg/m³
Calcium dihydroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1305-62-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 215-137-3	Inhalation	Non-applicable	4 mg/m³	Non-applicable	1 mg/m³

PNEC:

Identification				
Flue dust, portland cement	STP	6 mg/L	Fresh water	0,282 mg/L
CAS: 68475-76-3	Soil	5 mg/kg	Marine water	0,028 mg/L
EC: 270-659-9	Intermittent	0,282 mg/L	Sediment (Fresh water)	0,875 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,088 mg/kg
Calcium dihydroxide	STP	3 mg/L	Fresh water	0,49 mg/L
CAS: 1305-62-0	Soil	1080 mg/kg	Marine water	0,32 mg/L
EC: 215-137-3	Intermittent	0,49 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Compulsory use of face mask	Filter mask for particles (Filter type: FFP2)	CATIII	EN 149:2001+A1:2009	Replace when an increase in resistence to breathing is observed.

C.- Specific protection for the hands





COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016 +A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	→	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Exposure scenario: PROC19 Professional use of hydraulic materials for building and construction (interior, exterior).

Professional uses of highly polished solids / powders of lime-based substances.

Exposure: <240 minutes.

Localized controls: Localized controls are not applicable. Process only in well-ventilated or outdoor environments (efficiency: 50%).

Respiratory Protection Equipment (RPE): FFP2 Mask

RPE Efficiency - Assigned Protection Factor APF = 20

Additional personal protective equipment (PPE): Eye protection should be worn unless, given the nature and type of application (ie closed process), potential contact with the eyes can not be ruled out. Also, wear face protection, protective clothing, protective gloves and appropriate safety shoes

Environmental exposure controls

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight
V.O.C. density at 20 °C: 0 kg/m³ (0 g/L)
Average carbon number: Non-applicable
Average molecular weight: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 17/03/2020 Revised: 26/05/2022 Version: 2 (Replaced 1) Page 5/11





COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Physical state at 20 °C: Solid

Appearance: Powdery

Colour: According to the markings on the package

Odour: Odourless
Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Product description:

Density at 20 °C: 1050 - 1150 kg/m³
Relative density at 20 °C: -148,9 - 151,1

Dynamic viscosity at 20 °C: Non-applicable *

Kinematic viscosity at 20 °C: Non-applicable *

Kinematic viscosity at 40 °C: Non-applicable *

Concentration: Non-applicable *

pH: 10

Vapour density at 20 °C:

Partition coefficient n-octanol/water 20 °C:

Solubility in water at 20 °C:

Non-applicable *

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Non-applicable *

Non-applicable *

Flammability:

Flash Point:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable *

Non-applicable *

Non-applicable *

Explosive (Solid):

Lower explosive limit: Non-applicable *
Upper explosive limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: >125 µm

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Non-applicable *

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Non-applicable *

Non-applicable *

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 17/03/2020 Revised: 26/05/2022 Version: 2 (Replaced 1) Page 6/11



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Avoid direct impact	Not applicable	Not applicable	Avoid direct impact

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Can react violently	Silicate formation and calcium hydroxide	Not applicable	Not applicable	Base metal salts (Al, NH4,)

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Glass, oxide, chemicals (1)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Contact with human skin, without adequate protection, can result in skin thickening, cracking, or fissuring

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Calcium dihydroxide	LD50 oral	7340 mg/kg	Rat
CAS: 1305-62-0	LD50 dermal	Non-applicable	
EC: 215-137-3	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Calcium dihydroxide	LC50	50,6 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1305-62-0		49,1 mg/L (48 h)	Daphnia magna	Crustacean
EC: 215-137-3	EC50 184,57 mg/L (72 h) Pseudokirchneriella subcapitata A		Algae	

Chronic toxicity:

Identification	Concentration		Species	Genus
Calcium dihydroxide	NOEC	Non-applicable		
CAS: 1305-62-0 EC: 215-137-3	NOEC	32 mg/L	Crangon septemspinosa	Crustacean

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Date of compilation: 17/03/2020 Revised: 26/05/2022 Version: 2 (Replaced 1) Page 8/11



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 12: ECOLOGICAL INFORMATION (continued)

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
17 09 03*	other construction and demolition wastes (including mixed wastes) containing hazardous substances	Dangerous

Product - Cement that has exceeded its shelf life: 10 13 99

Product - Unused residue or dry spillage: 10 13 06

Product - after addition of water, hardened: 10 13 14, 17 01 01

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

UN number or ID number: Non-applicable 14.2 UN proper shipping name: Non-applicable Non-applicable 14.3 Transport hazard class(es): Labels: Non-applicable 14.4 Packing group: Non-applicable

14.5 **Environmental hazards:** No

Special precautions for user

Special regulations: Non-applicable Tunnel restriction code: Non-applicable Physico-Chemical properties: see section 9 Limited quantities: Non-applicable $\textbf{Maritime transport in bulk according} \quad \text{Non-applicable}$

14.7

to IMO instruments:

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

- CONTINUED ON NEXT PAGE -Date of compilation: 17/03/2020 Revised: 26/05/2022 Version: 2 (Replaced 1) Page 9/11





COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number or ID number: Non-applicable
 14.2 UN proper shipping name: Non-applicable
 14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
 14.4 Packing group: Non-applicable

14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: Non-applicable

EmS Codes:

Physico-Chemical properties: see section 9
Limited quantities: Non-applicable
Segregation group: Non-applicable
Maritime transport in bulk according
Non-applicable

to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

14.1 UN number or ID number: Non-applicable Non-applicable 14.2 UN proper shipping name: Non-applicable 14.3 Transport hazard class(es): Labels: Non-applicable 14.4 Packing group: Non-applicable 14.5 **Environmental hazards:**

14.5 Environmental nazarus.

14.6 Special precautions for user

Physico-Chemical properties: see section 9

Maritime transport in bulk according Non-applicable

to IMO instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Calcium dihydroxide (Product-type 2, 3)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

14.7

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- 1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.
- 2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.
- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

COLORBASE FL G. 24 NATURAL GREY; 45 RAVEN; 60 DUSTY GREY 24-FLxx-0005-2-G



SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

· New declared substances

Formaldehyde (50-00-0)

octhilinone (ISO) (26530-20-1)

Cement, alumina, chemicals (65997-16-2)

Substances that contribute to the classification (SECTION 2):

New declared substances

octhilinone (ISO) (26530-20-1)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Hazard statements

Texts of the legislative phrases mentioned in section 2:

H335: May cause respiratory irritation.

H317: May cause an allergic skin reaction.

H315: Causes skin irritation.

H318: Causes serious eye damage.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

STOT SE 3: Calculation method

Skin Sens. 1B: Calculation method

Skin Irrit. 2: Calculation method

Eye Dam. 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product which should not be used for needs other than those specified.

Date of compilation: 17/03/2020 Revised: 26/05/2022 Version: 2 (Replaced 1) Page 11/11

^{**} Changes with regards to the previous version