



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



SECT	TION 1: IDENTIFICATION OF THE SUBST.	ANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING					
1.1	Product identifier:	SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M					
	Other means of identification:						
	UFI:	F8F0-Y012-X001-FX4S					
1.2	Relevant identified uses of the substance or r	nixture and uses advised against:					
	Relevant uses: Cobble & Setts Jointing Compound	nd. For professional users only.					
	Uses advised against: All uses not specified in th	is section or in section 7.3					
1.3	Details of the supplier of the safety data shee	t:					
	LATICRETE EUROPE SRL Via Paletti Snc 41051 Castelnuovo Rangone - ITALY Phone: 059535540 info@laticreteeurope.com https://eu.laticrete.com/						
1.4	Emergency telephone number: Company nur	nber (08:00 - 18:00 CET): (+39) 059 557680 - European emergency number: 112					
SECT	SECTION 2: HAZARDS IDENTIFICATION						

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

#### 2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

Warning

#### Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1A: H317 - May cause an allergic skin reaction.

#### Precautionary statements:

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

#### P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

### Supplementary information:

EUH205: Contains epoxy constituents. May produce an allergic reaction.

Contains Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol.

## Substances that contribute to the classification

2-methylisothiazol-3(2H)-one

F8F0-Y012-X001-FX4S UFI:

#### Other hazards: 2.3

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

#### Non-applicable

#### 3.2 Mixture:

#### Chemical description: Epoxides

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS: EC:	1675-54-3 216-823-5	Bis-[4-(2,3-epoxipropoxi)pl	nenyl]propane 1	Self-classified	
Index:	210-623-5 603-073-00-2 01-2119456619-26-XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	() <b>E</b>	35 - <50 %
CAS: EC:	9003-36-5 701-263-0	Formaldehyde, oligomeric	reaction products with 1-chloro-2,3-epoxypropane and phenol 1	Self-classified	
EC: Index: REACH:	Non-applicable 01-2119454392-40-XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	() <b>L</b>	10 - <20 %
CAS:	68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 1			
EC: Index: REACH:	271-846-8 603-103-00-4 01-2119485289-22-XXXX	Regulation 1272/2008	Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	$\langle \mathbf{\hat{k}} \rangle$	10 - <20 %
CAS:	2682-20-4	2-methylisothiazol-3(2H)-or	ne 1	ATP ATP13	
Index:	220-239-6 613-326-00-9 01-2120764690-50-XXXX	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317; EUH071 - Danger		0,005 - <0,01 %

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

	Identification		M-factor			
2-methylisothiazol-3(2H)-o	ne			Acute	10	
CAS: 2682-20-4	EC: 220-239-6			Chronic	1	
	Identification	Specific concentration limit				
Bis-[4-(2,3-epoxipropoxi)ph CAS: 1675-54-3 EC: 216-823-5	nenyl]propane		% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319			
2-methylisothiazol-3(2H)-o CAS: 2682-20-4 EC: 220-239-6	ne		% (w/w) >=0,0015: Skin Sens. 1A -	H317		

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

#### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

## By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



#### SECTION 4: FIRST AID MEASURES (continued)

#### Non-applicable

#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. **Unsuitable extinguishing media:** 

Non-applicable

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC. Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13

#### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided. C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



## SECTION 7: HANDLING AND STORAGE (continued)

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

## 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

#### DNEL (Workers):

	Short exposure		Long exposure		
Identification	Systemic	Local	Systemic	Local	
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1675-54-3	Dermal	Non-applicable	Non-applicable	0,75 mg/kg	Non-applicable
EC: 216-823-5	Inhalation	Non-applicable	Non-applicable	4,93 mg/m <sup>3</sup>	Non-applicable
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 9003-36-5	Dermal	Non-applicable	Non-applicable	104,15 mg/kg	Non-applicable
EC: 701-263-0	Inhalation	Non-applicable	Non-applicable	29,39 mg/m <sup>3</sup>	Non-applicable
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68609-97-2	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
EC: 271-846-8	Inhalation	Non-applicable	Non-applicable	3,6 mg/m <sup>3</sup>	Non-applicable
2-methylisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2682-20-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 220-239-6	Inhalation	Non-applicable	0,043 mg/m <sup>3</sup>	Non-applicable	0,021 mg/m <sup>3</sup>

#### **DNEL (General population):**

		Sho	Short exposure		Long exposure	
Identification	Systemic	Local	Systemic	Local		
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable	
CAS: 1675-54-3	Dermal	Non-applicable	Non-applicable	0,0893 mg/kg	Non-applicable	
EC: 216-823-5	Inhalation	Non-applicable	Non-applicable	0,87 mg/m <sup>3</sup>	Non-applicable	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	Oral	Non-applicable	Non-applicable	6,25 mg/kg	Non-applicable	
CAS: 9003-36-5	Dermal	Non-applicable	Non-applicable	62,5 mg/kg	Non-applicable	
EC: 701-263-0	Inhalation	Non-applicable	Non-applicable	8,7 mg/m <sup>3</sup>	Non-applicable	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable	
CAS: 68609-97-2	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable	
EC: 271-846-8	Inhalation	Non-applicable	Non-applicable	0,87 mg/m <sup>3</sup>	Non-applicable	
2-methylisothiazol-3(2H)-one	Oral	0,053 mg/kg	Non-applicable	0,027 mg/kg	Non-applicable	
CAS: 2682-20-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 220-239-6	Inhalation	Non-applicable	0,043 mg/m <sup>3</sup>	Non-applicable	0,021 mg/m <sup>3</sup>	



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification					
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	STP	10 mg/L Fresh water		0,006 mg/L	
CAS: 1675-54-3	Soil	0,065 mg/kg	Marine water	0,001 mg/L	
EC: 216-823-5	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,341 mg/kg	
	Oral	0,011 g/kg	Sediment (Marine water)	0,034 mg/kg	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	STP	10 mg/L	Fresh water	0,003 mg/L	
CAS: 9003-36-5	Soil	0,237 mg/kg	Marine water	0 mg/L	
EC: 701-263-0	Intermittent	0,025 mg/L	Sediment (Fresh water)	0,294 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,029 mg/kg	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	STP	10 mg/L	Fresh water	0,106 mg/L	
CAS: 68609-97-2	Soil	1,234 mg/kg	Marine water	0,011 mg/L	
EC: 271-846-8	Intermittent	0,072 mg/L	Sediment (Fresh water)	307,16 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	30,72 mg/kg	
2-methylisothiazol-3(2H)-one	STP	0,23 mg/L	Fresh water	0,00339 mg/L	
CAS: 2682-20-4	Soil	0,047 mg/kg	Marine water	0,00339 mg/L	
EC: 220-239-6	Intermittent	0,00339 mg/L	Sediment (Fresh water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	

#### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	Pictogram PPE		CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

#### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



ECTION 8	8: EXPOSURE CO	NTROLS	/PERSONAL PF	ROTECTION (cc	ontinue	ed)		
	Pictogram		PPE	Labelling		CEN Standard		Remarks
		Anti-s	slip work shoes	CAT II		EN ISO 20347:2012	prolon use	te before any evidence of deterioration. For periods of ged exposure to the product for professional/industrial ors CE III is recommended, in accordance with the plations in EN ISO 20345:2012 y EN 13832-1:2007
F	F Additional emergency measures							
	Emergency measure Standards			Emergency measure	9	Standards		

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>◎</b> + ▼	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

# Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0,22 % weight
V.O.C. density at 20 °C:	2,33 kg/m³ (2,33 g/L)
Average carbon number:	11,89
Average molecular weight:	170,4 g/mol

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical proper	ties:	
Appearance:		
Physical state at 20 °C:	Liquid	
Appearance:	Viscous	
Colour:	Amber	
Odour:	Aminic	
Odour threshold:	Non-applicable *	
Volatility:		
Boiling point at atmospheric pressure:	>100 °C	
Vapour pressure at 20 °C:	2348 Pa	
Vapour pressure at 50 °C:	12371,84 Pa (12,37 kPa)	
Evaporation rate at 20 °C:	Non-applicable *	
Product description:		
Density at 20 °C:	1080,5 kg/m³	
Relative density at 20 °C:	1,08	
Dynamic viscosity at 20 °C:	2794 cP	
Kinematic viscosity at 20 °C:	2705 mm²/s	
Kinematic viscosity at 40 °C:	>20,5 mm²/s	
Concentration:	Non-applicable *	
pH:	7 - 9	
Vapour density at 20 °C:	Non-applicable *	
Partition coefficient n-octanol/water 20 °C:	Non-applicable *	
Solubility in water at 20 °C:	Non-applicable *	
Solubility properties:	Water miscible	
*Not relevant due to the nature of the product, not providing informa	ation property of its hazards.	

- CONTINUED ON NEXT PAGE -



# LATICRETE



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M

SECT	FION 9: PHYSICAL AND CHEMICAL PROPERTIES (conti	nued)
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non Flammable (>60 °C)
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	Non-applicable *
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard classes:	
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing information property	of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

## 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

## 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

## 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:





## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
  - IARC: Bis-[4-(2,3-epoxipropoxi)phenyl]propane (3); Distillates (petroleum), hydrotreated light (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	Acu	ite toxicity	Genus
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 oral	>5000 mg/kg	Rat
CAS: 9003-36-5	LD50 dermal	Non-applicable	
EC: 701-263-0	LC50 inhalation	Non-applicable	
2-methylisothiazol-3(2H)-one	LD50 oral	120 mg/kg	Rat
CAS: 2682-20-4	LD50 dermal	242 mg/kg	Rat
EC: 220-239-6	LC50 inhalation	Non-applicable	

#### 11.2 Information on other hazards:

#### Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

## 12.1 Toxicity:

#### Acute toxicity:

Identification		Concentration	Species	Genus	
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	LC50	2 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 1675-54-3	EC50	1,7 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 216-823-5	EC50	9,4 mg/L (72 h)	Scenedesmus subspicatus	Algae	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LC50	2,54 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 9003-36-5	EC50	5,55 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 701-263-0	EC50	1,8 mg/L (72 h)	Selenastrum capricornutum	Algae	
2-methylisothiazol-3(2H)-one	LC50	4,77 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 2682-20-4	EC50	0,934 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 220-239-6	EC50	Non-applicable			

#### Chronic toxicity:

12.2

12.3

Identification	Concentration		Species	Genus
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	NOEC	Non-applicable		
CAS: 1675-54-3 EC: 216-823-5	NOEC	0,3 mg/L	Daphnia magna	Crustacean
2-methylisothiazol-3(2H)-one	NOEC	4,93 mg/L	Oncorhynchus mykiss	Fish
CAS: 2682-20-4 EC: 220-239-6	NOEC	0,044 mg/L	Daphnia magna	Crustacean

## Persistence and degradability: Substance-specific information:

Identification	Deg	radability	Biodegradability	
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1675-54-3	COD	Non-applicable	Period	28 days
EC: 216-823-5	BOD5/COD	Non-applicable	% Biodegradable	5 %
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	BOD5	Non-applicable	Concentration	3 mg/L
CAS: 9003-36-5	COD	Non-applicable	Period	28 days
EC: 701-263-0	BOD5/COD	Non-applicable	% Biodegradable	0 %
2-methylisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	10 mg/L
CAS: 2682-20-4	COD	Non-applicable	Period	28 days
EC: 220-239-6	BOD5/COD	Non-applicable	% Biodegradable	55,8 %

## Bioaccumulative potential:

#### Substance-specific information:

Identification	[	Bioaccumulation potential		
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	BCF	31		
CAS: 1675-54-3	Pow Log	3		
EC: 216-823-5	Potential	Moderate		
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	BCF	150		
CAS: 9003-36-5	Pow Log	3.6		
EC: 701-263-0	Potential	High		
2-methylisothiazol-3(2H)-one	BCF			
CAS: 2682-20-4	Pow Log	-0.49		
EC: 220-239-6	Potential			

## 12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		ility
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	Кос	450	Henry	Non-applicable
CAS: 1675-54-3	Conclusion	Low	Dry soil	Non-applicable
EC: 216-823-5	Surface tension	Non-applicable	Moist soil	Non-applicable



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



#### SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	Кос	4460	Henry	Non-applicable
CAS: 9003-36-5	Conclusion	Low	Dry soil	Non-applicable
EC: 701-263-0	Surface tension	Non-applicable	Moist soil	Non-applicable
2-methylisothiazol-3(2H)-one	Кос	Non-applicable	Henry	0E+0 Pa⋅m³/mol
CAS: 2682-20-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 220-239-6	Surface tension	Non-applicable	Moist soil	Non-applicable

# 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

## 12.7 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
	It is not possible to assign a specific code, as it depends on the intended use by the user	Hazardous	

## Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant - skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2. Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

## Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

	14.1 14.2	UN number or ID number: UN proper shipping name:	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3- epoxipropoxi)phenyl]propane)						
	14.3	Transport hazard class(es):	9						
· ·		Labels:	9						
	14.4	Packing group:	III						
	14.5	Environmental hazards:	Yes						
	14.6	Special precautions for user							
		Special regulations:	274, 335, 375, 601						
		Tunnel restriction code:							
		Physico-Chemical properties:	see section 9						
		Limited quantities:	5 L						
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable						
Transport of dangerous goods by sea:									
With regard to IMDG	40-20:								



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



ECTION 14: TRANSPORT INFORMATION (continued)						
	14.1	UN number or ID number:	UN3082			
	14.2	UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3- epoxipropoxi)phenyl]propane)			
	4.3	Transport hazard class(es):	9			
		Labels:	9			
	14.4	Packing group:	III			
	14.5	Marine pollutant:	Yes			
	14.6	Special precautions for user				
		Special regulations:	335, 969, 274			
		EmS Codes:	F-A, S-F			
		Physico-Chemical properties:	see section 9			
		Limited quantities:	5 L			
		Segregation group:	Non-applicable			
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable			
Transport of dange	rous go	ods by air:				
With regard to IATA/ICAO 2023:						
	14.1	UN number or ID number:	UN3082			
	• 14.2	UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3- epoxipropoxi)phenyl]propane)			
× •	14.3	Transport hazard class(es):	9			
		Labels:	9			
	14.4	Packing group:	III			
	14.5	Environmental hazards:	Yes			
	14.6	Special precautions for user				
		Physico-Chemical properties:	see section 9			
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable			

## SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 2-methylisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 2-methylisothiazol-3(2H)-one (Product-type 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements							
E2	ENVIRONMENTAL HAZARDS	200	500							
Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):										
Shall not be used in: —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, —tricks and jokes, —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.										

## Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.



## SPECTRALOCK PRO PREMIUM GROUT PARTE B 24-S-0025B-0003-M



#### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878). Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks:

## Non-applicable

#### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

H319: Causes serious eye irritation.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

#### Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1A: H317 - May cause an allergic skin reaction.

#### Classification procedure:

Skin Irrit. 2: Calculation method Skin Sens. 1A: Calculation method Aquatic Chronic 2: Calculation method Eye Irrit. 2: Calculation method

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Dose 50 LC50: Effective concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.