

Version No:02/BH Issue Date: 24-Mar-2023

226 Thick Bed Mortar

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name 226Thick Bed Mortar

Recommended use Cement-based, Tile Bed Mortar (For professional use).

Company Name: LATICRETE MIDDLE EAST LLC

Manufacturer/ Importer/ Supplier/ Distributor information Address P.O. Box. 86028, Ras Al Khaimah, United Arab Emirates

Telephone: +971 7 244 6396

2. HAZARD (s) IDENTIFICATION		
Classification	Skin Corr./Irritation:. Eye Dam./Irritation:. Sensitization, skin: Specific target organ toxicity, single exposure Category 1 Category 1 Category 1 Category 3 Category 1	
Label Element		
Signal Words	Corrosive, Harmful, Health Hazard	
Hazard Statement(s)	H318 Causes serious eye damage. H315 Causes skin irritation. H335 May cause respiratory irritation. H372 Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation)	
Precautionary Statement(s) Prevention	P280 Wear protective gloves and eye/face protection. P271 Use only outdoors or in a well-ventilated area. P260 Do not breath dust/gas/mist/vapors. P270 Do not eat, drink or smoke when using this product. P264 Wash with plenty of water and soap thoroughly after handling.	
Precautionary Statement(s) Response	P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water. P362 + P364 Take off contaminated clothing and wash before reuse.	
Precautionary Statement(s) Storage	P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.	
Precautionary Statement(s) Disposal	P501 Dispose of contents/container to hazardous or special waste collection point.	
Other hazards which do not result in classification	None known.	
Supplemental information	In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns	
Emergency overview	IRRITANT. Irritating to eyes, respiratory system and skin.	

226 Thick Bed Mortar Page 1 of 6



Version No:02/BH Issue Date: 24-Mar-2023

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Name	CAS No	Content (% by wt)
Ordinary Portland cement	65997-15-1	25%
Silica sand	14808-60-7	75%
TOTAL		100%

4. FIRST-AID MEASURES	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues
Skin contact	Take off immediately all contaminated clothing. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse. Get medical attention immediately
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.
Personal protection for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves
Symptoms caused by exposure	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
	Rash. Corrosive effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Medical attention and special treatment	Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for fire

fighters

Firefighting equipment/instructions

General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire

Hazards during fire-fighting: carbon monoxide, carbon dioxide, harmful vapours Evolution of fumes/fog. The substances/groups of substances mentioned can be

released in case of fire. Product is not combustible or explosive.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance

with official regulations.

No unusual fire or explosion hazards noted.

226 Thick Bed Mortar Page 2 of 6



Version No:02/BH Issue Date: 24-Mar-2023

6.ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning

For non-emergency personnel

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure

adequate ventilation. Local authorities should be advised if significant spillages cannot

be contained.

For emergency responders wearing appropriate protective clothing.

Avoid release to the environment. Do not discharge into drains, water courses or onto Environmental precautions

the ground. Environmental manager must be informed of all major releases

Large Spills: Pick up with suitable appliance and dispose of. Pack in tightly closed

containers for disposal..

Small Spills: Pick up with suitable appliance and dispose off.

Never return spills in original containers for re-use. For waste disposal, see Section 13 Other issues relating to spills and releases

of the SDS. Clean up in accordance with all applicable regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid dust formation. The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Segregate from metals. Segregate from acids. Segregate from lyes. Segregate from

oxidants. Segregate from foods and animal feeds.

Conditions for safe storage, including any

incompatibilities

Suitable materials for containers: High density polyethylene (HDPE)

Further information on storage conditions: Containers should be stored tightly sealed in a

dry place.

station.

8 EADUSIIDE	: r	ONITOOL	CI	DEDCUNAL	PROTECTION	

Control parameters	Follow standard monitoring procedures.	
Occupational exposure limits	Portland Cement: PEL 15 mg/m³ EVA Co-Polymer: OEL (USA) Ceiling limit: 5 mg/m³	
Biological limit values	No biological exposure limits noted for the ingredient(s).	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash	

226 Thick Bed Mortan Page 3 of 6



Version No:02/BH Issue Date: 24-Mar-2023

Individual protection measures, for example personal protective equipment (PPE)

Wear safety glasses with side shields Eye/face protection (or goggles). Face-shield. Wear a full-

(or goggles). Face-shield. Wear a full-face respirator, if needed





Skin protection Hand protection

Wear appropriate chemical resistant gloves.



Others	Body protection must be chosen based on level of activity and exposure.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants

9. PHYSICAL AND CHEMICAL PROPERTIES

Powder **Appearance** Grey & White Colour Odour Odorless рΗ Not applicable Melting point/ freezing point Not available Initial boiling point and boiling range Not available Flash point Not flammable Evaporation rate Not applicable Flammability (solid, gas) Not applicable Not applicable Vapor pressure Approx.. 1600 gms/cc Bulk density Solubility (water) Insoluble

10. STABILITY AND REACTIVITY

Auto-ignition temperature

Reactivity No hazardous reactions if stored and handled as prescribed/indicated

Not available

Chemical stability Material is stable under normal conditions

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated. Strong bases are

formed on the addition of water.

Conditions to avoid Avoid dust formation. Avoid humidity

Incompatible materials Strong Bases. Strong acids.

Hazardous decomposition products No hazardous decomposition products if stored and handled as prescribed/indicated

226 Thick Bed Mortar Page 4 of 6



Oral

Dermal

Eye

Other Information

SAFETY DATA SHEET

Version No:02/BH Issue Date: 24-Mar-2023

11. TOXICOLOGIC	AL INFORMATION
-----------------	----------------

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or Information on possible routes of exposure skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact

may be a route of entry for liquefied gases.

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic Acute toxicity/ Effects

after a single skin contact. Virtually nontoxic by inhalation. The statement has been

derived from the properties of the individual components.

Swallowing may cause gastrointestinal irritation

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing

Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause

Assessment of sensitization: Causes skin irritation. Sensitization

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

> Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the

properties of the individual components.

12. ECOLOGICAL INFORMATION	
Aquatic-toxicity	Not expected to be harmful to aquatic organisms
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available for this product
Mobility in soil	The product is not mobile in soil.
Additional information	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this comp
13. DISPOSAL CONSIDERATIONS	
Disposal methods	Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain

some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Completely emptied packaging can be given for recycling.

14. TRANSPORT INFORMATION	
ADG	Not classified as a dangerous good under transport regulations
IMDG	Not classified as a dangerous good under transport regulations
IATA/ ICAO	Not classified as a dangerous good under transport regulations

226 Thick Bed Mortan Page 5 of 6



Version No:02/BH Issue Date: 24-Mar-2023

15. REGULATORY INFORMATION

Safety, health and environmental regulations

Followed National regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication International regulations

Standard, 29 CFR 1910.1200.

16. OTHER INFORMATION

Disclaimer: The information in this (M) SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.

226 Thick Bed Mortar Page 6 of 6