



Globally Proven
Construction Solutions

Admix and Primer

LATICRETE Admix & Primer is a latex primer for use with LATICRETE 86 LatiLevel™ and LATICRETE 84 LatiLevel. It is also used as an admix for LATICRETE 816 LatiPatch™.

Product is for interior use only.



FEATURES/BENEFITS

- Easy to use
- Reduces pinholes
- Allows for proper hydration of self leveling underlayment & overlayment
- Increases bond strength

STANDARDS/CERTIFICATIONS

Meets all Federal, State & Local requirements for VOC. Actual field performance will depend on installation methods and site conditions.

MANUFACTURER

LATICRETE MIDDLE EAST L.L.C.
P.O. Box. 86028, Ras Al Khaimah
United Arab Emirates.

Telephone: +971 7 244 6396
Fax: +971 7 244 5915
Internet: www.laticrete.me

USES

A re-emulsifiable bonding agent designed to be used with LATICRETE Self Leveling Underlayment and Overlayment.

Suitable Substrates

For interior use only

- Concrete
- Cement Backer Board*
- Cement Terrazzo**
- Exterior Glue Plywood
- Ceramic Tile and Stone
- Cement Mortar Beds*

* Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use.

Packaging

20ℓ /pail – 36 Pail per pallet

Approximate Coverage

For extremely porous dry substrates, may be applied full strength, yielding approximately 97 m² per pail or dilute 1:1 by volume with clean potable water to yield approximately 194 m² per pail.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for five (5) year if stored at temperatures >0°C and <40°C.

Limitations

- Interior Use Only
- Do not install when surface temperature is below 4°C or when ambient temperature is expected to be below 10°C during placement or before material takes final set.
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use LATICRETE Hydro ban Waterproofing Membrane.

Cautions

Consult MSDS for more information

- During cold weather, protect finished work from traffic until fully cured.
- Keep out of reach of children.

INSTALLATION SYSTEM

Surface Preparation

All surfaces should be between 4°C and 32°C structurally sound, clean and free of all dirt, oil, grease, loose peeling paint, concrete sealers or curing compounds. Remove all dust by vacuuming. Skim coat existing ceramic tile or stone with a LATICRETE Latex Thin-Set mortar.

Application

Instructions for use as a primer for self-leveling applications: Use LATICRETE Admix and Primer with every application. Shake thoroughly before using. Pour, mop, or spray primer onto the surface. Apply an even thickness to the prepared substrate using a bristle broom. Make sure to work into the substrate, removing any puddles or thick areas. Allow the primer to dry to a clear film (~30 to 45mins depending on the site conditions) before application of underlayment. Very dry or porous slabs will require double priming if diluted with water.

Cleaning

Clean tools with water while primer is fresh

AVAILABILITY AND COST

Availability

LATICRETE and LATAPOXY materials are available worldwide. For distributor information, call:

Telephone: + 971 7 244 6396
Fax: + 971 7 244 5915

For on-line Distributor information, visit LATICRETE at www.laticrete.me

Cost

Contact a LATICRETE Distributor in your area.

WARRANTY

LATICRETE Middle East LLC warrants that LATICRETE Admix and Primer is free from manufacturing defects and will not break down, deteriorate or disintegrate under normal usage for a period of one (1) year from date of purchase subject to the terms and conditions stated.

TECHNICAL SERVICES/ CONTACT

Technical assistance

Information is available by calling:

Telephone: +971 7 244 6396
Fax: +971 7 244 5915

Technical and safety literature

To acquire technical and safety literature, please visit our website at

www.laticrete.me