SAFETY DATA SHEET

1. Identification

Product identifier Enhancer Pro™ Sealer

None. Other means of identification Sealer. Recommended use None known. **Recommended restrictions**

Manufacturer/ Importer/ Supplier/ Distributor information Company

Name LATICRETE MIDDLE EAST LLC

P.O. Box. 86028, Ras Al Khaimah, United Arab Emirates Address

+971 7 244 6396 Telephone Contact person Mohmed Rafig, M

Website www.laticrete.com www.laticrete.me

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Skin corrosion/irritation Category 2

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Hazardous to the aquatic environment, acute **Environmental hazards** Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be

fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly Prevention

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling.

Category 2

Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Response

If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed:

Immediately call a poison center/doctor. Do NOT induce vomiting. Collect spillage.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal Hazard(s) not otherwise Static accumulating flammable liquid can become electrostatically charged even in bonded and

classified (HNOC) grounded equipment.

Enhancer Pro™ Sealer 1/8

922655 Version #: 01 Revision date: -Issue date: 12-February-2015

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Naphtha (petroleum),	64742-48-9	70 - 80
hydrotreated heavy		

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical

attention if any discomfort continues.

Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical Skin contact

attention if irritation develops and persists.

Eye contact Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to

do. Get medical attention immediately.

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person Ingestion

becomes uncomfortable take to hospital along with these instructions. Get medical attention if

symptoms occur.

Most important symptoms/effects, acute and delayed

Skin irritation. Irritation of nose and throat. Irritating to mucous membranes. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Indication of immediate medical attention and special Treat symptomatically.

treatment needed

General information

media

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.

Special protective equipment and precautions for firefighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapor. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Use personal protection recommended in Section 8 of the

Methods and materials for containment and cleaning up ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Following product recovery, flush area with water. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Prevent further leakage or spillage if safe to do so. Do not contaminate water. **Environmental precautions**

922655 Version #: 01 Revision date: -Issue date: 12-February-2015 2/8

7. Handling and storage

Precautions for safe handling

The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Avoid prolonged exposure. Wash thoroughly after handling. Handle and open container with care.

Conditions for safe storage, including any incompatibilities Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3	
		100 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Follow standard monitoring procedures.

Appropriate engineering controls

shower. Individual protection measures, such as personal protective equipment

Eye/face protection

Wear goggles/face shield.

Skin protection

Hand protection Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is

advisable. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves.

> Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that

Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust

limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency

ventilation, or other engineering controls to control airborne levels below recommended exposure

100 ppm

is specifically recommended by the Personal Protective Equipment manufacturer.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory

equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes.

9. Physical and chemical properties

Appearance Clear liquid. Liquid. Physical state

Enhancer Pro™ Sealer SDS ME **Form** Liquid. Clear. Color

Odor Slight hydrocarbon.

Odor threshold Not available. No data available. Melting point/freezing point Not applicable.

Initial boiling point and boiling

range

> 300.2 °F (> 149 °C)

82.4 °F (28.0 °C) Closed Cup Flash point

Evaporation rate Not applicable. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density

Relative density 0.809

Solubility(ies)

Insoluble in water. Solubility (water) Not available. **Partition coefficient**

(n-octanol/water)

Not available. Auto-ignition temperature

> 392 °F (> 200 °C) **Decomposition temperature**

Viscosity Not available.

Other information

VOC (Weight %) 632 g/l

10. Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Stable under normal temperature conditions. Risk of ignition. **Chemical stability**

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, sparks, flames, elevated temperatures.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Vapors may cause drowsiness and dizziness. Inhalation

Causes skin irritation. Skin contact

Eye contact May cause eye irritation on direct contact. Ingestion may cause irritation and malaise. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Irritation of nose and throat. Irritating to mucous membranes.

Information on toxicological effects

May cause discomfort if swallowed. **Acute toxicity**

Enhancer Pro™ Sealer SDS ME

Test Results Components **Species**

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 4.96 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Causes skin irritation. Skin corrosion/irritation Serious eve damage/eve May cause eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not classified. Skin sensitization Not a skin sensitizer. Germ cell mutagenicity Not classified.

Not classified. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious **Further information**

chemical pneumonia. Organic solvents may be absorbed into the body by inhalation and cause

permanent damage to the nervous system, including the brain.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components **Species Test Results**

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Aquatic

IC50 Algae Algae <= 10 mg/l, 72 hours Crustacea EC50 Daphnia <= 10 mg/l, 48 hours Fish LC50 <= 10 mg/l, 96 hours Fish

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

No data available. Mobility in soil

Mobility in general The product is insoluble in water.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Dispose of this material and its container at hazardous or special waste collection point. Do not

incinerate sealed containers. Do not allow this material to drain into sewers/water supplies.

Dispose in accordance with all applicable regulations.

Waste codes should be assigned by the user based on the application for which the product was Hazardous waste code

used.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations. Empty containers should be taken to an approved

waste handling site for recycling or disposal.

Enhancer Pro™ Sealer SDS ME 5/8

14. Transport information

DOT

UN number UN3295

UN proper shipping name Hydrocarbons, liquid, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 144, B1, IB3, T4, TP1, TP29

Packaging exceptions150Packaging non bulk203Packaging bulk242ERG number128

IATA

UN number UN3295

UN proper shipping name Hydrocarbons, liquid, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards Yes
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3295

UN proper shipping name Hydrocarbons, liquid, n.o.s.

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards

Marine pollutant Yes
EmS F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not available.

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Enhancer Pro™ Sealer SDS ME

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA) **US state regulations**

This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. New Jersey Worker and Community Right-to-Know Act

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-February-2015

Revision date Version # 01

Enhancer Pro™ Sealer SDS ME 922655 Version #: 01 Revision date: -Issue date: 12-February-2015 7/8

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings



List of abbreviations

References

HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer

The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.

Enhancer Pro™ Sealer SDS ME