LATICRETE

SAFETY DATA SHEET

1. Identification

Other means of identification None.

Recommended useTreatment of natural stone surfaces.

Recommended restrictions None known.

Manufacturer/ Importer/ Supplier/ Distributor information Company
Name LATICRETE MIDDLE EAST LLC

Address P.O. Box. 86028, Ras Al Khaimah, United Arab Emirates

Telephone +971 7 244 6396 Contact person Mohmed Rafiq. M

Website www.laticrete.com www.laticrete.me

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard

Category 1
Category 2

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be

fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary statement

Impregnator Pro® Sealer

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling.

Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed:

Immediately call a poison center/doctor. Do NOT induce vomiting. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

925556 Version #: 01 Revision date: - Issue date: 17-March-2015

SDS ME

1/8

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Naphtha (petroleum), hydrotreated heavy	64742-48-9	90-98
Partially Fluorinated Acrylic Copolymer	Proprietary	1-5
n-Butyl acetate	123-86-4	1-5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.

Skin contact

Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical attention if irritation develops and persists.

Eve contact

Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

Ingestion

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Skin irritation. Irritation of nose and throat. Irritating to mucous membranes. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapor. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Use personal protection recommended in Section 8 of the SDS.

Impregnator Pro® Sealer SDS ME

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Following product recovery, flush area with water. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

The product is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not handle or store near an open flame, heat or other sources of ignition. Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Avoid prolonged exposure. Wash thoroughly after handling. Handle and open container with care.

Conditions for safe storage, including any incompatibilities

Follow rules for flammable liquids. Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

8. Exposure controls/personal protection

Occupational exposure limits

controls

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3	
•		100 ppm	
n-Butyl acetate (CAS 123-86-4)	PEL	710 mg/m3	
,		150 ppm	
US. ACGIH Threshold Limi	t Values		
Components	Туре	Value	
n-Butyl acetate (CAS 123-86-4)	STEL	200 ppm	
,	TWA	150 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	400 mg/m3	
,		100 ppm	
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3	
		200 ppm	
	TWA	710 mg/m3	
		150 ppm	
ogical limit values	No biological exposure limits noted for the ingredient(s).		
osure guidelines	Follow standard monitoring procedures.		
propriate engineering	Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust		

Impregnator Pro® Sealer SDS ME

ventilation, or other engineering controls to control airborne levels below recommended exposure

limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency

shower.

Individual protection measures, such as personal protective equipment

Wear goggles/face shield. Eye/face protection

Skin protection

Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is Hand protection

advisable. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves.

> Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that

is specifically recommended by the Personal Protective Equipment manufacturer.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory

equipment.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks considerations

and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes.

9. Physical and chemical properties

Appearance Liquid. Liquid. Physical state Liquid. **Form** Color Colorless.

Odor Mild hydrocarbon. Not available. Odor threshold Not available. pН Not available. Melting point/freezing point 339.8 °F (171 °C) Initial boiling point and boiling

range

Flash point 125.6 °F (52.0 °C) Closed Cup

Evaporation rate Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available.

Not available. Vapor pressure Not available. Vapor density

Relative density 0.761

Solubility(ies)

Slightly soluble. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition** temperature **Viscosity** Not available.

Other information

VOC (Weight %) 748 q/l

Impregnator Pro® Sealer SDS ME

10. Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Stable under normal temperature conditions. Risk of ignition. Chemical stability

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, sparks, flames, elevated temperatures.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Vapors may cause drowsiness and dizziness. Inhalation

Causes skin irritation. Skin contact

May cause eye irritation on direct contact. Eye contact Ingestion may cause irritation and malaise. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Irritation of nose and throat. Irritating to mucous membranes.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components **Test Results** Species

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Acute

Dermal

> 2000 mg/kg LD50 Rabbit

Inhalation

Rat LC50 > 4.96 mg/l, 4 Hours

Oral

Rat LD50 > 5000 mg/kg

n-Butyl acetate (CAS 123-86-4)

Acute

Inhalation

LC50 Rat 2000 ppm, 4 Hours

Oral

LD50 Rat 10768 mg/kg

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye May cause eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not a skin sensitizer.

Not classified. Germ cell mutagenicity Not classified. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity -

May cause drowsiness or dizziness.

single exposure

Specific target organ toxicity -Not classified.

repeated exposure **Aspiration hazard**

May be fatal if swallowed and enters airways.

Impregnator Pro® Sealer SDS ME 5/8

925556 Version #: 01 Revision date: -Issue date: 17-March-2015 Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components Species Test Results

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Aquatic

 Algae
 IC50
 Algae
 10 mg/l, 72 hours

 Crustacea
 EC50
 Daphnia
 10 mg/l, 48 hours

 Fish
 LC50
 Fish
 10 mg/l, 96 hours

Persistence and degradability No.

No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

n-Butyl acetate (CAS 123-86-4) 1.78

Mobility in soil No data available.

Mobility in general The product is insoluble in water.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Dispose of this material and its container at hazardous or special waste collection point. Do not

incinerate sealed containers. Do not allow this material to drain into sewers/water supplies.

Dispose in accordance with all applicable regulations.

Hazardous waste code Waste codes should be assigned by the user based on the application for which the product was

used.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations. Empty containers should be taken to an approved

waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN3295

UN proper shipping name

Transport hazard class(es)

Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, n-Butyl acetate)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 144, B1, IB3, T4, TP1, TP29

Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242
ERG number 128

IATA

UN number UN3295

UN proper shipping name Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, n-Butyl acetate)

Transport hazard class(es)

Class 3

Subsidiary risk -

Subsidiary risk Label(s) 3
Packing group III
Environmental hazards Yes
ERG Code 3L

Impregnator Pro® Sealer SDS ME

925556 Version #: 01 Revision date: - Issue date: 17-March-2015

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3295

UN proper shipping name Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy, n-Butyl acetate)

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III
Environmental hazards

Marine pollutant Yes
EmS F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

This material contains one or more substances which requires export notification under TSCA

Section 12(b) and 40 CFR Part 707 Subpart D:

Partially Fluorinated Acrylic Copolymer

PMN Number: P-08-0643

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

n-Butyl acetate (CAS 123-86-4) LISTED

Not available.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulationsThis product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

n-Butyl acetate (CAS 123-86-4)

Impregnator Pro® Sealer SDS ME

US. New Jersey Worker and Community Right-to-Know Act

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

n-Butyl acetate (CAS 123-86-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

n-Butyl acetate (CAS 123-86-4)

US. Rhode Island RTK

n-Butyl acetate (CAS 123-86-4)

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

17-March-2015 Issue date

Revision date Version # 01

United States & Puerto Rico

NFPA ratings



List of abbreviations

HSDB® - Hazardous Substances Data Bank References

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

Issue date: 17-March-2015

Impregnator Pro® Sealer SDS ME

Version #: 01 Revision date: -

925556

No

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).