



SAFETY DATA SHEET

1. Identification

Product identifier Oil Stain Remover
Other means of identification None.
Recommended use Pultice cleaner for natural stone surfaces.

Manufacturer/ Importer/ Supplier/ Distributor information Company

Name LATICRETE MIDDLE EAST LLC
Address P.O. Box. 86028, Ras Al Khaimah, United Arab Emirates
Telephone +971 7 244 6396
Contact person Mohmed Rafiq. M
Website www.laticrete.com www.laticrete.me

Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Skin corrosion/irritation Category 2
Sensitization, skin Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 1

Hazardous to the aquatic environment, long-term hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Wash thoroughly after handling. Avoid breathing vapors. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment.

Response In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Collect spillage. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Not classified.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium Carbonate	1317-65-3	40 - 50
Limonene	5989-27-5	40 - 50
Naphtha (petroleum), hydrotreated heavy	64742-48-9	5 - 10
Isopropyl alcohol	67-63-0	< 2
Quartz	14808-60-7	< 0.3

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Skin contact	Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin rash or an allergic skin reaction develops, get medical attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.
Most important symptoms/effects, acute and delayed	Symptoms may include redness, drying and cracking of the skin.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Extinguish with carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	By heating and fire, irritating vapors/gases may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.
General fire hazards	The product is flammable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep away from sources of ignition - No smoking. Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Do not discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

7. Handling and storage**Precautions for safe handling**

Do not breathe mist or vapor. Do not get in eyes, on skin, on clothing. Persons susceptible for allergic reactions should not handle this product. Ground container and transfer equipment to eliminate static electric sparks, especially during transfer of material. Use non-sparking tools when opening or closing containers. Use with adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a cool and well-ventilated place. Store away from incompatible materials (See Section 10).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Isopropyl alcohol (CAS 67-63-0)	PEL	980 mg/m ³	
		400 ppm	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m ³	
		100 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Isopropyl alcohol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total
Isopropyl alcohol (CAS 67-63-0)	STEL	1225 mg/m ³	
		500 ppm	
		980 mg/m ³	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	400 ppm	
		400 mg/m ³	
		100 ppm	
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Limonene (CAS 5989-27-5)	TWA	165.5 mg/m ³
		30 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Slurry.
Physical state	Liquid.
Form	Paste.
Color	Grey.
Odor	Lemon.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	120.2 °F (49.0 °C) Closed Cup
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	1.237
Solubility(ies)	
Solubility (water)	No data available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

Other information

VOC (Weight %) 51.6 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability Material is stable under normal conditions.
Possibility of hazardous reactions Will not occur.
Conditions to avoid Contact with incompatible materials.
Incompatible materials Strong oxidizing agents. Strong acids.
Hazardous decomposition products At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological information**Information on likely routes of exposure**

Inhalation In high concentrations, vapors may irritate throat and respiratory system and cause coughing.
Skin contact Causes skin irritation.
Eye contact May cause eye irritation.
Ingestion Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include redness, drying and cracking of the skin.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components	Species	Test Results
Isopropyl alcohol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12800 mg/kg
<i>Oral</i>		
LD50	Rat	4.7 g/kg
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 4.96 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	May cause eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	No data available.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity

Not classified. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

IARC Monographs. Overall Evaluation of Carcinogenicity

Limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.
 Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity No data available.
Specific target organ toxicity - single exposure No data available.
Specific target organ toxicity - repeated exposure No data available.
Aspiration hazard Not classified.
Chronic effects Prolonged or repeated contact may dry skin and cause irritation.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Isopropyl alcohol (CAS 67-63-0)		
Aquatic		
Fish	LC50 Bluegill (<i>Lepomis macrochirus</i>)	> 1400 mg/l, 96 hours
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)		
Aquatic		
Algae	IC50 Algae	<= 10 mg/l, 72 hours
Crustacea	EC50 Daphnia	<= 10 mg/l, 48 hours
Fish	LC50 Fish	<= 10 mg/l, 96 hours

Persistence and degradability The product is not readily biodegradable.

Bioaccumulative potential Has the potential to bioaccumulate.

Partition coefficient n-octanol / water (log Kow)

Isopropyl alcohol (CAS 67-63-0) 0.05
 Limonene (CAS 5989-27-5) 4.232

Mobility in soil No data available.

Mobility in general No data available.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 °F

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number UN2319
UN proper shipping name Terpene hydrocarbons, n.o.s. (Naphtha (petroleum), hydrotreated heavy, Limonene)
Transport hazard class(es)
 Class 3
 Subsidiary risk -
 Label(s) 3
Packing group III
Environmental hazards
 Marine pollutant Yes
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions B1, IB3, T4, TP1, TP29
Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN2319
UN proper shipping name Terpene hydrocarbons, n.o.s. (Naphtha (petroleum), hydrotreated heavy, Limonene)
Transport hazard class(es)
 Class 3
 Subsidiary risk -
 Label(s) 3
Packing group III
Environmental hazards Yes
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN2319
UN proper shipping name TERPENE HYDROCARBONS, N.O.S. (Naphtha (petroleum), hydrotreated heavy, Limonene)
Transport hazard class(es)
 Class 3
 Subsidiary risk -
 Label(s) 3
Packing group III
Environmental hazards
 Marine pollutant Yes
EmS F-E, S-D
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This product is a liquid and when transported in bulk is covered under MARPOL 73/78 Annex II. This product is listed in the IBC Code.
Ship type: 3
Pollution category: Y

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)
Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations WARNING: This product contains chemical(s) known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Calcium Carbonate (CAS 1317-65-3)
Isopropyl alcohol (CAS 67-63-0)
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)
Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Calcium Carbonate (CAS 1317-65-3)
Isopropyl alcohol (CAS 67-63-0)
Limonene (CAS 5989-27-5)
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)
Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium Carbonate (CAS 1317-65-3)
Isopropyl alcohol (CAS 67-63-0)
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)
Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Isopropyl alcohol (CAS 67-63-0)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 18-December-2014

Revision date -

Version # 01

NFPA ratings



List of abbreviations

References HSDB® - Hazardous Substances Data Bank
Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.