



# LATASIL™ 9118 Primer

LATASIL™ 9118 Primer is a one component primer designed to increase adhesion of LATASIL to various substrates.

**Globally Proven  
Construction Solutions**



## FEATURES/BENEFITS

- Ready to use
- Fast dry time
- Durable bond is unaffected by water

## PACKAGING

- 240 ml bottle; 5 bottles per carton.

## USES

- Increases adhesion and bond strength for dependable long lasting installations.
- For all underwater and permanent wet area applications such as pools, fountains, showers, tubs, spas, saunas and steam rooms.
- Ideal for stone applications.
- Ideal for harsh environment.

## SUITABLE SUBSTRATES

- PVC
- Stone
- Ceramic/masonry
- Metals/steel
- Porcelain

## MANUFACTURER

LATICRETE New Zealand  
3 /118 Asquith Avenue, Mt. Albert,  
Auckland, 1023, New Zealand

Telephone: +64 9 394 1900

Internet: [nz.laticrete.com](http://nz.laticrete.com)

### Shelf Life

When stored in original, unopened containers at or below 32 °C, shelf life is 6 months from date of manufacture. Container should be kept tightly sealed when not in use.

### Approximate Coverage

Each 240ml can, will cover approximately 100 linear meters of joint work with a nominal 6 – 10mm high joint flanks.

Coverage will vary depending on porosity of tile to be covered and method of application.

### Limitations

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane
- Flammable—cannot be shipped air freight.

### Cautions

Before using any LATICRETE product:

- Read and understand the Product Data Sheet and Safety Data Sheet.
- Avoid direct contact with eyes. If contact with eyes occurs, immediately flush with water and seek medical attention.
- Avoid prolonged exposure to skin. In case of skin contact, wash affected area as soon as possible.
- Keep away from heat, sparks and open flames.
- Use with adequate ventilation, avoid prolonged breathing of vapours.
- Flammable—store in safe location.
- Test a small area when applying to stone for compatibility.
- Keep out of reach of children.

## INSTALLATIONS

### Surface Preparation

- Thoroughly clean all surfaces of dust, dirt tar, oils, and other debris. Remove rust and scale from metal surfaces by abrasive cleaning or wire brushing. Masonry surfaces should also be wire brushed and blown with compressed air to remove dust.
- Thoroughly clean and degrease all surfaces with an industrial solvent such as naphtha, mineral spirits, xylene, toluene or MEK on a clean oil-free rag.

### Application

- Sealant must be installed in the manner indicated for intended performance.
- Consult LATICRETE Technical Services for specific sealant installation applications.
- Apply LATASIL 9118 Primer to clean, dry surfaces by brushing, dipping, or spraying.
- Apply a thin layer evenly to the substrate-do not apply too thick as bond will break.
- Take care not to contaminate the veneer surface.
- Allow the primer to dry until all the solvent evaporates and is dry to the touch (generally 30 – 60 minutes at 21 °C. Drying time depends on temperature, humidity conditions and the porosity of the substrate.
- Apply sealant as directed, refer to DS-1074 for more information.

## AVAILABILITY AND COST

### Availability

LATICRETE and LATAPOXY® materials are available worldwide.

For Distributor information:

Telephone: +64 9 394 1900

For online distributor information, visit LATICRETE at [nz.laticrete.com](http://nz.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## MAINTENANCE

LATICRETE and LATAPOXY grouts, sealers and sealants require routine maintenance and cleaning with a neutral pH detergent and water. See TDS 1113 for more information.

All other LATICRETE and LATAPOXY non-finish materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

## TECHNICAL SERVICES

### Technical assistance

Information is available by calling:

Telephone: +64 9 394 1900

### Technical and safety literature

To acquire technical and safety literature, please visit our website at [nz.laticrete.com](http://nz.laticrete.com)

## DISCLAIMER

- The information contained in this document is given in good faith and to the best of our knowledge is true and accurate.
- This information is subject to change without notice and it is the responsibility of the user to obtain up to date and current information.
- The use of this product is beyond our control and liability is assumed by the user when used incorrectly and not in accordance with LATICRETE guidelines.
- The manufacturer is not responsible for any loss or damage arising from incorrect usage of this product.
- The specifier or other party responsible for the project must ensure that the details in this data sheet are appropriate for the intended application and that additional detailing is performed for specific design or any areas that fall outside the scope of this specification.
- Efflorescence is a normal condition of Portland cement and is not covered by any warranty. The use of LATAPOXY 310 Stone Adhesive, LATAPOXY 300 Adhesive, SPECTRALOCK® PRO Premium Grout<sup>1</sup> and SPECTRALOCK 2000 IG will not contribute to any noticeable efflorescence.

### LATICRETE New Zealand

3 /118 Asquith Avenue, Mt. Albert,  
Auckland, 1023, New Zealand

+64 9 394 1900

[nz.laticrete.com](http://nz.laticrete.com)