



Globally Proven  
Construction Solutions

# Product Statement of Conformity LATICRETE Tile & Stone Adhesives

## PSoC-1002-NZ

<b>Product name:</b>	LATICRETE Tile & Stone Adhesives
<b>Product Line:</b>	Adhesives
<b>Product Description and its intended use:</b>	<p>257 TITANIUM™ - The ultimate lightweight, polymer fortified, thin-set adhesive for the installation of ceramic, stone and glass tiles. Formulated without sand. 257 TITANIUM is designed with key features to facilitate the installation of porcelain panels &amp; slabs, ceramic tile, stone, quarry tile, pavers, brick and glass tile. 257 TITANIUM features long open time, good adjustability, superior adhesion, maximum coverage and easier handling. Rated for interior, exterior and immersed installations.</p> <p>4-XLT Adhesive is a multi-use, polymer fortified adhesive mortar. 4-XLT offers non-sag wall installations, large heavy tile mortar build-up of up to 19 mm and thin-set applications. Rated for interior and exterior installations.</p> <p>LATAFLEX Gold Adhesive is a polymer fortified bagged cementitious thin-set powder to be mixed with water to install ceramic tile and natural stone using the thin-set method of installation. Rated for interior and exterior installations.</p> <p>335 Adhesive is a premium, flexible, high performance thin-bed adhesive for installing a wide range of tiles and stone including low absorption ceramic tile, porcelain tile, natural and manufactured stone using thin-set method of installation. Rated for interior, exterior and immersed installations.</p> <p>335 RAPID adhesive is a premium, flexible, high performance, rapid setting, bagged cementitious powder to be mixed with water to install low absorption ceramic tile, porcelain tile and natural stone using the thin-set method of installation. Rated for interior and exterior installations.</p> <p>335 LITE Adhesive is a premium, lightweight, high performance thin-set adhesive for the installation of large format ceramic, porcelain &amp; stone tile. Formulated without sand. 335 LITE is designed with key feature like long open time, good adjustability and great workability. Rated for interior, exterior and immersed installations.</p> <p>254 PLATINUM Rapid is the ultimate one-step, polymer fortified, thin-set mortar for interior and exterior installation of ceramic tile, stone, quarry tile, pavers and brick. 254R PLATINUM Rapid is designed to mix with water and provides reduced curing times.</p>

4-XLT Rapid Adhesive is a fast setting, multi-use, polymer fortified adhesive mortar for large format tile installations. 4-XLT Rapid offers tremendous utility for non-sag wall installations, Large and Heavy Tile and thin-set applications on floors. Rated for interior and exterior installations.

253 GOLD Rapid - 253R GOLD Rapid is a fast setting, bagged cementitious powder to be mixed only with water to install ceramic tile, porcelain tile and stone using the thin-set method of installation. Rated for interior and exterior installations.

LATAPOXY 300 Adhesive is a 100% solid, 3-part epoxy adhesive for chemical-resistant installations of quarry tile, porcelain, brick, and packing house tile. Superior strength and workability. Prevents curling of water sensitive marbles and agglomerates. Will not stain white or light-coloured stone. Can be used for installing rubber and bond strip wood flooring and laminate flooring to many substrates. Rated for interior and exterior installations.

---

<b>LATICRETE Product:</b>	11 kg 257 TITANIUM (white) 22.7 kg 4-XLT (white) 22.7 kg 4-XLT (grey) 20 kg LATAFLEX GOLD (off white) 20 kg 335 Adhesive (off white) 20 kg 335 RAPID (grey) 11 kg 335 LITE (off white) 11.3 254 PLATINUM Rapid (White) 22.7 kg 4-XLT RAPID (grey) 22.7 kg 4-XLT RAPID (white) 22.7 kg 253 GOLD RAPID (grey)
---------------------------	---

---

**Place of Manufacture:** 29 Telford Rd,  
Virginia, QLD 4014  
Australia.

One LATICRETE Park North,  
Bethany CT 06524-3423  
USA.

---

<b>Legal and trading name of manufacturer:</b>	LATICRETE Australia Pty Ltd LATICRETE International Inc.
--	---

---

<b>Legal and trading name of the importer:</b>	LATICRETE New Zealand Ltd
--	---------------------------

---

<b>Address for service:</b>	3/118 Asquith Avenue Mount Albert, Auckland 1023
-----------------------------	---

---

<b>Website:</b>	<a href="http://nz.laticrete.com">nz.laticrete.com</a>
-----------------	--

---

<b>Email Address:</b>	<a href="mailto:sales@laticrete.co.nz">sales@laticrete.co.nz</a>
-----------------------	--

---

<b>Phone:</b>	+64 9 394 1900
<b>NZBN:</b>	9429051840761
<b>Relevant Building Code Clauses:</b>	Clause B2 DURABILITY: Performance B2.3.1 (B), 15 years. Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.
<b>Statement on how the building product is expected to contribute to compliance:</b>	<p>Clause B2 DURABILITY: Performance B2.3.1 (B), 15 years.</p> <p>LATICRETE Adhesives are designed to fix ceramic tiles, brick, glass tiles and natural stones for duration longer than Performance B2.3.1 (B), 15 years period under normal usage, as specified. The LATICRETE adhesives listed, exceed the requirements of AS ISO13007.1 &amp; 2. Some also exceed the requirements of AS ISO13007.5 and ANSI A118.15, 11 &amp; 4.</p> <p>Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1 These are low VOC products that contain no aromatic solvents and meet the requirements of Performance F2.3.1 when used in accordance with our MSDS &amp; WHS guidelines. Some adhesives are formulated without sand.</p>
<b>Limitations on the use of the building product:</b>	<p>Must be installed with product data sheets, technical data sheets and LATICRETE® specifications. Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Substrate deflection under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/720 for thin bed stone installations where L=span length (except where local building codes specify more stringent deflection requirements).</p> <p>Tile/Stone/Glass and their fixing and grouting mortars do not constitute a waterproof barrier. Specify &amp; detail LATICRETE HYDRO BAN® Liquid Applied Waterproof Membrane System where a waterproof installation is required.</p> <p>Use white coloured adhesives for installing white or light-coloured marble or stone. Use LATAPOXY 300 Adhesive for installing green marble or water sensitive stone. Refer to product data sheets for individual product limitations.</p>
<b>Design requirements that would support the use of the building product</b>	<p>Where specific designed characteristics of a tile adhesive are required, e.g., immersed, chemical resistance or greater resistance to differential movement.</p> <p>Where tile adhesives tested to AS ISO13007.1 &amp; 2 are required.</p> <p>Where an adhesive is required to be part of a full system.</p> <p>Where tile adhesives are tested compatible to waterproof membrane systems in accordance to AS ISO13007.5.</p> <p>When bonding to difficult substrates.</p> <p>Where permanent immersed installations are required.</p> <p>Where medium bed adhesives are required for large format work.</p>
<b>Installation requirements:</b>	Refer to product data sheet for installation instructions. All work must be completed in accordance with product data sheets, technical data sheets, LATICRETE specifications and AS 3958: 2023.
<b>Maintenance Requirements:</b>	LATICRETE non-finish materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

---

**Is the building product /  
building product line subject  
to warning or ban under  
section 26?:**

---

No

LATICRETE New Zealand Ltd • 3 /118 Asquith Avenue, Mt. Albert, Auckland, 1023, New Zealand  
+64 9 394 1900 | [sales@laticrete.co.nz](mailto:sales@laticrete.co.nz) | [nz.laticrete.com](http://nz.laticrete.com)

©2024 LATICRETE New Zealand Ltd All trademarks shown are the intellectual properties of their respective owners