



Globally Proven
Construction Solutions

Product Statement of Conformity

LATICRETE Grout Systems

PSoC-1004-NZ

Product name:	LATICRETE Grout Systems
Product Line:	Tile & Stone Grout
Product Description and its intended use:	<p>LATICRETE PERMACOLOR® is a cement-based grout for tile and stone installations. Provides consistent colour, and antimicrobial protection to resist stain-causing mould and mildew.</p> <p>LATICRETE SPECTRALOCK® PRO Premium Grout* is a patented, high performance epoxy grout which offers excellent colour uniformity, durability and stain protection.</p>
LATICRETE Product:	<p>2544 PERMACOLOR® Grout 5kg Bright White 2518 PERMACOLOR Grout 5kg Sauterne 2542 PERMACOLOR Grout 5kg Platinum 2588 PERMACOLOR Grout 5kg Silver Shadow 2589 PERMACOLOR Grout 5kg Smoke Grey 2590 PERMACOLOR Grout 5kg Light Pewter 2578 PERMACOLOR Grout 5kg Sterling Silver 2524 PERMACOLOR Grout 5kg Natural Grey 2545 PERMACOLOR Grout 5kg Raven 2522 PERMACOLOR Grout 5kg Midnight Black 2585 PERMACOLOR Grout 10kg Almond 2517 PERMACOLOR Grout 10kg Marble Beige 2540 PERMACOLOR Grout 10kg Latte 2535 PERMACOLOR Grout 10kg Mocha 2560 PERMACOLOR Grout 10kg Dusty Grey 2522 PERMACOLOR Grout 10kg Midnight Black</p> <p>SPECTRALOCK® PRO Premium – Parts AB Liquids Only 0.56kg 4/carton 1244 SPECTRALOCK PRO Premium Grout - Part C 1kg Bright White 1218 SPECTRALOCK PRO Premium Grout - Part C 1kg Sauterne 1285 SPECTRALOCK PRO Premium Grout - Part C 1kg Almond 1223 SPECTRALOCK PRO Premium Grout - Part C 1kg Antique White 1217 SPECTRALOCK PRO Premium Grout - Part C 1kg Marble Beige 1240 SPECTRALOCK PRO Premium Grout - Part C 1kg Latte 1235 SPECTRALOCK PRO Premium Grout - Part C 1kg Mocha 1242 SPECTRALOCK PRO Premium Grout - Part C 1kg Platinum 1209 SPECTRALOCK PRO Premium Grout - Part C 1kg Frosty 1288 SPECTRALOCK PRO Premium Grout - Part C 1kg Silver Shadow 1289 SPECTRALOCK PRO Premium Grout - Part C 1kg Smoke Grey 1290 SPECTRALOCK PRO Premium Grout - Part C 1kg Light Pewter 1278 SPECTRALOCK PRO Premium Grout - Part C 1kg Sterling Silver 1224 SPECTRALOCK PRO Premium Grout - Part C 1kg Natural Grey</p>

1245 SPECTRALOCK® PRO Premium Grout - Part C 1kg Raven
 1260 SPECTRALOCK PRO Premium Grout - Part C 1kg Dusty Grey
 1222 SPECTRALOCK PRO Premium Grout - Part C 1kg Midnight Black
 SPECTRALOCK® PRO Premium – Parts AB Liquids Only 1.8kg pail
 1244 SPECTRALOCK PRO Premium Grout - Part C 4kg Bright White
 1218 SPECTRALOCK PRO Premium Grout - Part C 4kg Sauterne
 1285 SPECTRALOCK PRO Premium Grout - Part C 4kg Almond
 1223 SPECTRALOCK PRO Premium Grout - Part C 4kg Antique White
 1217 SPECTRALOCK PRO Premium Grout - Part C 4kg Marble Beige
 1240 SPECTRALOCK PRO Premium Grout - Part C 4kg Latte
 1235 SPECTRALOCK PRO Premium Grout - Part C 4kg Mocha
 1242 SPECTRALOCK PRO Premium Grout - Part C 4kg Platinum
 1209 SPECTRALOCK PRO Premium Grout - Part C 4kg Frosty
 1288 SPECTRALOCK PRO Premium Grout - Part C 4kg Silver Shadow
 1289 SPECTRALOCK PRO Premium Grout - Part C 4kg Smoke Grey
 1290 SPECTRALOCK PRO Premium Grout - Part C 4kg Light Pewter
 1278 SPECTRALOCK PRO Premium Grout - Part C 4kg Sterling Silver
 1224 SPECTRALOCK PRO Premium Grout - Part C 4kg Natural Grey
 1245 SPECTRALOCK PRO Premium Grout - Part C 4kg Raven
 1260 SPECTRALOCK PRO Premium Grout - Part C 4kg Dusty Grey
 1222 SPECTRALOCK PRO Premium Grout - Part C 4kg Midnight Black

Place of Manufacture:

29 Telford Rd,
 Virginia, QLD 4014
 Australia.

One LATICRETE Park North,
 Bethany CT 06524-3423
 USA.

Legal and trading name of manufacturer:

LATICRETE Australia Pty Ltd
 LATICRETE International Inc.

Legal and trading name of the importer:

LATICRETE New Zealand Ltd

Address for service:

3/118 Asquith Avenue
 Mount Albert, Auckland 1023

Website:

nz.laticrete.com

Email Address:

sales@laticrete.co.nz

Phone:

+64 9 394 1900

NZBN:

9429051840761

Relevant Building Code Clauses:

Clause B2 DURABILITY: Performance B2.3.1 & B2.3.2
 Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1

Statement on how the building product is

B2 – LATICRETE grouts are tested to perform in accordance with ISO 13007.3 & 4 Ceramic tiles – grouts and adhesive.

expected to contribute to compliance:

F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1

These are low VOC products that contain no aromatic solvents and meet the requirements of Performance F2.3.1 when used in accordance with our MSDS & WHS guidelines.

Limitations on the use of the building product:

- Must be installed with product data sheets, technical data sheets and LATICRETE specifications.
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers brick and stone are not designed as replacements for waterproofing membranes. When a waterproof membrane is required, use LATICRETE HYDRO BAN Waterproof System.
- Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Substrate deflection under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/720 for thin bed stone installations where L = span length.
- Consult individual product data sheets for curing time of grout. Protect work until fully cured.
- Grout may scratch soft glazed or polished surfaces. Conduct a test area to verify results.

Design requirements that would support the use of the building product

Where greater chemical resistance is required for heavy duty installations.
Where consistent colour and consistency is required.
Where grout for immersed installations is required.
Where a wide range of colours are required.

Installation requirements:

Refer to product data sheet for installation instructions. All work must be completed in accordance with product data sheets, technical data sheets, LATICRETE specifications and AS 3958: 2023.

Contact LATICRETE for free training, particularly where a trained LATICRETE SPECTRALOCK PRO Premium Grouter is a condition of warranty.

Maintenance Requirements:

As grouts form part of a system with tiling, it is recommended to maintain grout in accordance with TDS1113 found at nz.laticrete.com

Is the building product / building product line subject to warning or ban under section 26?:

No

*United States Patent No.: 6,881,768 (and other Patents).