

Product Technical Statement LATICRETE Thick Bed Mortars, Screeds & Renders

PTS-1001-NZ

Product name:	LATICRETE Thick Bed Mortars, Screeds & Renders
Product Line:	Substrate Preparation
Product Description	A layer of cementitious material that is applied to a substrate to dimensionally
and its intended use:	correct a surface in preparation for a variety of finishes. LATICRETE 3701 FMB is used
	under wall and floor coverings and LATICRETE Waterproof membrane to provide a
	suitable substrate for coverings to be installed. Used to create falls in wet areas and
	concrete balconies prior to membrane application. Can be used from feather edge to
	desired thickness.
LATICRETE Product:	LATICRETE 3701 Fortified Mortar Bed (Product Landing Page Link)
Place of Manufacture:	29 Telford Rd,
	Virginia, QLD 4014
	Australia
Legal and trading	LATICRETE Australia Pty Ltd
name of	
manufacturer:	
Legal and trading	LATICRETE New Zealand Ltd
name of the importer:	
Address for service:	3/118 Asquith Avenue
	Mount Albert, Auckland 1023
Website:	<u>nz.laticrete.com</u>
Email Address:	sales@laticrete.co.nz
Phone:	+64 9 394 1900
NZBN:	9429051840761
Relevant Building	Clause B2 DURABILITY: Performance B2.3.1 (B), 15 years.
Code Clauses:	Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.
Statement on how the	Clause B2 DURABILITY: Performance B2.3.1 (B), 15 years.
building product is	This product is expected to exceed the requirements of Performance B2.3.1 requirements under
expected to contribute	normal conditions.
to compliance:	
	Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1
	These are low VOC products that contain no aromatic solvents and meet the
	requirements of Performance F2.3.1 when used in accordance with our SDS & WHS
	guidelines.
	°

Quality Assurance	There are no local standards for testing tiling underlayment mortars and renders. However, LATICRETE tests to ASTM C270 for compressive strength, flexural strength, set times, service rating and the like, to maintain product integrity and quality.
Limitations on the use	- Not for use over expansion joints or structural movement cracks.
of the building product:	- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproof membranes. When a waterproof membrane is required, use LATICRETE HYDRO BAN Waterproof Membrane.
	- Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Substrate deflection under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/720 for thin bed stone installations where L = span length.
Design requirements	Use to patch concrete prior to rendering or screeding.
that would support	Suitable for installations where "Extra Heavy Duty" service load resistance is required.
the use of the	Suitable for installations that require high strength and flexibility.
building product	Suitable for bonded and unbonded mortar applications.
	Suitable for installations requiring thin levelling.
	A part of a system approach to installation.
	Suitable for immersion.
Installation	LATICRETE 3701 FMB can be installed over the following substrates:
requirements:	
	- Concrete
	- Concrete block
	- Ceramic tile and stone
	- Cement mortar beds
	- Cement backer board**
	- Brick and concrete masonry
	- Cement plaster
	- Cement terrazzo
	- Exterior glue plywood^
	^ Interior use only with wire reinforcing
	** Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use.
	Refer to product data sheet for installation instructions. All work must be completed in accordance with product data sheets, technical data sheets, LATICRETE specifications and AS 3958: 2023.

Maintenance	All LATICRETE non-finish materials require no maintenance but
Requirements:	installation performance and durability may depend on properly maintaining products
	supplied by other manufacturers.
Is the building product /	No
building product line subject	
to warning or ban under	
section 26?:	
Product support:	Email: TechnicalSupport@laticrete.co.nz
	Telephone: +64 9 394 1900
	Technical and safety literature; To acquire technical and safety literature,
	Visit Website: <u>nz.laticrete.com</u>