



# Pro-Mix Station

**NEW**

A successful job depends upon optimized mixing time, reduced spillage, and consistent results of the end product, and the Pro-Mix Station provides an ideal and safe solution to meet these demands.

As a pourable cart, the Pro-Mix Station contains the material, eliminates harmful dust, and provides combined batch consistency. The removable drill allows for the mixing of tile/stone adhesive and repair mortars. The Pro-Mix Station can be used with many LATICRETE® products, such as self-leveling underlayment, overlayer, and epoxies.

| FEATURES                      | BENEFITS                                    |
|-------------------------------|---|
| 3 bag capacity                | Up to 1500 lb (680 kg)/hr output            |
| 14.5 amp/110 V drill          | Powerful electric motor                     |
| 2 speeds: 0-250 and 0-580 RPM | Able to adjust based on product consistency |
| 2 mixing paddles              | Higher (SLU's) and low viscosity mortars    |
| Rotating caster wheels        | Easy mobility                               |
| Pourable and dust extractor   | Contractor safety                           |
| Steel frame                   | Longevity                                   |

**Item #**  
7319-MIXER-CR

**Packaging**  
Packaged in 2 boxes  
Pallet Quantity: 4 units

**Weight**  
Unit: 65 lbs (29.5 kg)  
Pallet: 310 lbs (140.6 kg)



Assembly is required.





# Pro-Mix Station

**NUEVO**

Un trabajo exitoso depende de un tiempo de mezcla optimizado, un derrame reducido y resultados consistentes del producto final, y la estación Pro-Mix proporciona una solución ideal y segura para satisfacer estas demandas.

Como carrito vertible, la Pro-Mix Station contiene el material, elimina el polvo dañino y proporciona una consistencia combinada del lote. El taladro extraíble permite mezclar adhesivo para baldosas/piedras y morteros de reparación. La estación Pro-Mix Station se puede utilizar con muchos productos LATICRETE®, como contrapisos autonivelantes, recubrimientos y epoxis.

| CARACTERÍSTICAS                  | BENEFITS  |
|----------------------------------|---|
| Capacidad para 3 bolsas          | Salida de hasta 1500 lb (680 kg)/h                    |
| Taladro de 14,5 amperios/110 V   | Potente motor eléctrico                               |
| 2 velocidades: 0-250 y 0-580 RPM | Capaz de ajustarse según la consistencia del producto |
| 2 paletas mezcladoras            | Morteros de mayor (SLU's) y baja viscosidad           |
| Ruedas giratorias                | Fácil movilidad                                       |
| Extractor de polvo y vertido     | Seguridad del contratista                             |
| Estructura de acero              | Vida útil   |

**Artículo número**  
7319-MIXER-CR

**Presentación**  
Empaquetado en 2 cajas  
Cantidad de palet: 4 unidades

**Peso**  
Unidad: 29.5 kg (65 libras)  
Tarima: 140.6 kg (310 libras)



Se requiere ensamblaje.

