



# STONETECH® Oil Stain Remover

DS-214-0120

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

STONETECH® Oil Stain Remover

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: [laticrete.com](http://laticrete.com)

## 3. PRODUCT DESCRIPTION

STONETECH® Oil Stain Remover is the ready-to-use, problem solving solution to removing deep-set oil-based stains from natural stone, masonry and grout. Just stir, apply and wait to pull out tough, deep-set organic oil and grease stains and avoid costly restoration fees.

### Uses

- Countertops
- Floors
- Walls
- Interior and exterior

### Advantages

- For natural stone, masonry and grout
- Pulls out deep-set oil and grease stains
- Ready-to-use, just stir and apply
- Leaves no permanent residue

### Suitable Substrates

- Marble
- Granite
- Quartzite
- Limestone
- Travertine
- Slate
- Sandstone
- Concrete
- Grout (Cement-based grout for natural stone)

### Packaging US

- ST322-0603-11: 3oz (88.7ML) CAN - 6 units / case
- ST322-0616-11: Pint /16oz (473ML) (PINT) - 6 units / case

### CANADA

- ST357-0603-11: 3oz (88.7ML) CAN - 6 units / case

### Approximate Coverage

- ½-1 ft<sup>2</sup> (0.05 – 0.09 m<sup>2</sup>) of surface at ¼" (6mm) thickness per pint (473 mL).
- 15-30 in<sup>2</sup> (97-194 cm<sup>2</sup>) of surface at ¼" (6mm) thickness per 3oz. can (88.7 mL).

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >32°F (0°C) and <110°F (43°C).

### Cautions

- Consult SDS for more safety information.
- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin rash or an allergic skin reaction develops, get medical attention.
- Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses,

- if present and easy to do. Continue rinsing. Get medical attention.
- Ingestion: Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.

#### 4. TECHNICAL DATA



**VOC/LEED Product Information**  
Not Regulated

#### Physical Properties

Form	Paste
Color	Grey
Odor	Lemon

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

#### 5. INSTALLATION

##### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine that the desired results will be achieved. Make sure surface is clean, dry, and free of waxes and coatings. Ensure that area is well-ventilated and keep children and pets away from the area during application and until surface is clean and dry.

##### Directions

1. Using a plastic or wood spatula, stir thoroughly to mix the paste.
2. Apply a 1/4" (6mm) thick layer of paste to the stain. Ensure that the paste extends at least 1–2" (25–50mm) beyond the edge of the stain.
3. Do not cover.
4. Allow 48–72 hours for paste to completely dry.
5. Using a plastic spatula, remove dried product and discard.
6. Allow solvent to completely dry from the stone.
7. If stain is not completely gone after drying, repeat process.
8. Clean up residue and tools with mineral spirits.

9. Once the surface is dry, reseal the cleaned area with a STONETECH Sealer (e.g. STONETECH® BulletProof® Sealer).

#### 6. AVAILABILITY AND COST

##### Availability

LATICRETE materials are available worldwide.

##### For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [laticrete.com](http://laticrete.com)

##### Cost

Contact a LATICRETE Distributor in your area.

#### 7. WARRANTY

See 10. FILING SYSTEM:

#### 8. MAINTENANCE

Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

#### 9. TECHNICAL SERVICES

##### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

##### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [laticrete.com](http://laticrete.com).

#### 10. FILING SYSTEM

Additional product information is available on our website at [laticrete.com](http://laticrete.com). The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- TDS 262: Stone and Tile Care Guide
- DS 282.0: STONETECH® BulletProof® Sealer

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2020 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.