



STONETECH® Natural Stone Countertop Sealer

DS 289.0-0616

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STONETECH® Natural Stone Countertop Sealer

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: www.laticrete.com

3. PRODUCT DESCRIPTION

A water-based, easy-to-use countertop sealer that offers heavy duty protection against most water and oil-based stains.

Uses (Interior and Exterior Use)

- Countertops
- Backsplashes
- Shower walls
- Walls

Advantages

- Advanced protection against water and oil-based stains
- Preserves natural look of stone
- Water-based formula
- Interior and exterior use
- Can be applied to damp surfaces
- Also great for vertical applications.

Recommended Surfaces:

Natural stone such as:

- Marble
- Granite
- Limestone
- Quartzite
- Bluestone

- Travertine
- Sandstone
- Slate
- Flagstone

Item Numbers and Packaging

D14924348 – 24 fl.oz. (709 ml) spray bottle, 6 units per Case, 576 units per Pallet

**Not available for sale in Canada*

Approximate Coverage

- Up to 170 ft² /24 fl oz bottle (15.8 m² / 709 ml) for a single coat application

Expected Wear

- Up to 5 years on interior surfaces
- Up to 3 years on exterior surfaces

For best results, reapply annually.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

VOC Content

<400 g/L (excluding water) for EPA Purposes

<10 g/L (including water) for LEED and U.S. State purposes (Low Solids Coating)

Storage and Handling Instructions

Avoid prolonged exposure to vapors. Use in a well-ventilated area. Do not ingest. Avoid contact with eyes and skin. **KEEP OUT OF THE REACH OF CHILDREN.** Do not freeze or store above 100°F(38°C). Do not mix with other chemicals. Do not release to natural waterways.

Cautions

Consult SDS for more safety information.

- Inhalation: In high concentrations, vapors may be irritating to the respiratory system.
- Skin contact: May cause skin irritation
- Eye contact: May cause eye irritation
- Ingestion: May cause discomfort if swallowed
- Keep out of reach of children.

4. TECHNICAL DATA

Physical Properties

Form	Liquid
Color	Pale Amber
Odor	Mild
pH	9 – 11
Specific Gravity	1.009

Working Properties

Full Cure	24 – 72 hours
-----------	---------------

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean and free of waxes and coatings. Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F (10°C and 26°C). Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

Application

1. Shake well before use.
2. Mask off surfaces not intended to be treated.
3. Liberally spray an even coat of STONETECH® Natural Stone Countertop Sealer.
4. Allow sealer to penetrate the surface for 10-15 minutes. During this time, keep the surface wet with sealer, adding more sealer as needed. **DO NOT ALLOW SEALER TO COMPLETELY DRY ON THE SURFACE.**
5. Thoroughly wipe dry the entire surface with clean absorbent towels.
6. A second coat may be needed for porous, absorbent surfaces. If a second coat is required, it should be applied within the 30-40 minutes from the initial application as directed in steps 3-5.
7. Should a sealer residue appear, rewet the impacted section of the surface with sealer. Agitate the surface with a white nylon scrubbing pad to loosen residue and wipe dry with a clean, absorbent towel.
8. A full cure is achieved in 24-72 hours. Use of the treated surface may resume in 6-8 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure has been achieved.
9. Clean tools used during application with water.

Cleaning

Clean tools used during application with water

6. AVAILABILITY AND COST

Availability

LATICRETE®, STONETECH and LATAPOXY® materials are available worldwide.

For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at www.stonetech.com or www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at www.laticrete.com or www.stonetech.com.

10. FILING SYSTEM

Additional product information is available on our website at www.stonetech.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 211.0: STONETECH Stone & Tile Cleaner

DS 215.0: STONETECH KlenzAll Cleaner

TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com
©2016 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.