



# LATICRETE® Granite & Marble Countertop Sealer

DS 376.0-0616

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

LATICRETE® Granite & Marble Countertop Sealer

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010  
Toll Free: +1.888.786.6343  
Fax: +1.203.393.1684  
Website: [www.laticrete.com](http://www.laticrete.com)

## 3. PRODUCT DESCRIPTION

LATICRETE® Granite & Marble Countertop Sealer is a water-based, easy-to-use countertop sealer that offers heavy duty protection against most water and oil-based stains while preserving the natural beauty of the stone.

### Uses (Interior and Exterior Use)

- Countertops
- Backsplashes

### Advantages

- Provides protection against oil and water-based stains
- Preserves natural look and beauty of stone
- Easy to use, water-based formula
- Interior and exterior use

### Recommended Surfaces:

Natural stone such as:

- Marble
- Granite
- Limestone
- Bluestone
- Travertine
- Sandstone
- Slate
- Saltillo Tile

- Flagstone

### Item Numbers and Packaging

D14980041 – 24 oz Spray Bottle (710 mL), 6 units per Case, 504 units per Pallet

### Approximate Coverage

- Up to 90 ft<sup>2</sup>/24 oz (8.3 m<sup>2</sup>/710 mL) bottle for a two coat application

### Expected Wear

- Up to 5 years on interior surfaces
- Up to 3 years on exterior surfaces

For frequently used surfaces, annual sealing is recommended

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

### VOC Content

<235 g/L excluding water (For EPA purposes)

<5 g/L including water (Low Solids Coating)

### Storage and Handling Instructions

Avoid prolonged exposure to vapors. Use only in a well-ventilated area. Avoid contact with eyes and skin. KEEP OUT OF THE REACH OF CHILDREN. Do not mix with other chemicals. Do not freeze or store above 100°F (38°C). Do not release to natural waterways.

### Cautions

Consult SDS for more safety information.

- Ingestion: Rinse mouth. Do not induce vomiting. Call poison control center. Call a physician.
- Keep out of reach of children and pets.

## 4. TECHNICAL DATA

### Physical Properties

Form	Liquid
Color	Pale Amber
Odor	Mild
pH	9 – 11

### Working Properties

Full Cure	24 – 72 hours
Surface Use	6 – 8 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean and free of waxes and coatings. LATICRETE® Granite and Marble Countertop Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F (10°C and 26°C). Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until treated surface is dry.

### Application

1. Shake well before use.
2. Mask off surfaces not intended to be treated.
3. Liberally spray an even coat of LATICRETE® Granite & Marble Countertop Sealer to surface being treated.
4. Allow Sealer to penetrate the surface for 10 – 15 minutes while. During this time, keep the surface wet with sealer, adding more sealer as needed. **DO NOT ALLOW SEALER TO COMPLETELY DRY ON THE SURFACE.** Remove excess sealer by wiping surface thoroughly with clean, dry towels.
5. A second coat may be needed for porous, absorbent surfaces. If a second coat is required, it should be applied 30 – 40 minutes after the initial application as directed in steps 2 – 3.
6. Following the final application, wipe entire surface with clean, dry towels to remove any excess sealer. Should a sealer residue appear, reapply a thin coat of sealer, wait 2–3 minutes, and then rub lightly with a white nylon pad. Wipe again thoroughly with clean, dry towels.
7. A full cure is achieved in 24 – 72 hours. Use of the treated surface may resume in 6 – 8 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure has been achieved.
8. Clean tools used during application with water.

## 6. AVAILABILITY AND COST

### Availability

LATICRETE®, STONETECH® and LATAPOXY® materials are available worldwide.

### For Distributor Information, Call:

Toll Free: +1.888.786.6343  
Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [www.stonetech.com](http://www.stonetech.com) or [www.laticrete.com](http://www.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as LATICRETE® Stone & Tile

Floor Cleaner is recommended. For tough or difficult to remove soil use LATICRETE® Heavy Duty Tile & Grout Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2  
Telephone: +1.203.393.0010, ext. 235  
Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com](http://www.laticrete.com) or [www.stonetech.com](http://www.stonetech.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [www.stonetech.com](http://www.stonetech.com). The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty  
DS 370.5: LATICRETE® Stone & Tile Floor Cleaner  
DS 372.5: LATICRETE® Heavy Duty Tile & Grout Cleaner