



# LATICRETE® Stone Sealer

DS 376.5-0616

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

LATICRETE® Stone Sealer

## 2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010

Toll Free: +1.888.786.6343

Fax: +1.203.393.1684

Website: [www.laticrete.com](http://www.laticrete.com)

## 3. PRODUCT DESCRIPTION

LATICRETE® Stone Sealer is designed to protect both the stone and grout in one application, keeping them looking fresh and new, and easy to clean. LATICRETE® Stone Sealer is intended for interior and exterior use, protecting against water-based and oil-based stains.

### Uses (Interior and Exterior Use)

- Countertops
- Backsplashes
- Floors
- Walls
- Bathrooms

### Advantages

- Standard protection against water-based and oil-based stains
- Protects the natural look of stone
- Easy-to-use, water-based formula
- Interior and exterior use
- Seals natural stone and grout in one step

### Recommended Surfaces:

Natural stone and grout surfaces such as:

- Marble
- Granite
- Limestone
- Slate
- Travertine

### Item Numbers and Packaging

D14924524 - Quart - 32 oz (946 mL), 4 units per Case, 640 units per Pallet

D14924509 - Gallon (3.8 L), 4 units per Case, 160 units per Pallet

### Approximate Coverage

Up to 450 ft<sup>2</sup>/Gallon (41.8 m<sup>2</sup>/ 3.8 L) for a two-coat application

Up to 115 ft<sup>2</sup>/Quart (11m<sup>2</sup>/946 ml) for a two coast application

### Expected Wear

- Up to 2 years on interior surfaces
- Up to 1 year on exterior surfaces

For best results, reapply annually.

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

### VOC Content

<250 g/L (excluding water) For EPA Purposes

<5 g/L (including water) Low Solids Coating

### Storage and Handling Instructions

Avoid prolonged exposure to vapors. Use only in a well-ventilated area. Do not ingest. Avoid contact with eyes and skin. KEEP OUT OF REACH OF CHILDREN. Do not freeze or store above 100°F (38°C). Do not mix with other chemicals. Do not release to natural waterways.

### Cautions

Consult SDS for more safety information.

- Ingestion: Rinse mouth. Do not induce vomiting. Seek medical attention if discomfort persists.
- Keep out of reach of children and pets.

## 4. TECHNICAL DATA

### Physical Properties

Form	Liquid
Color	Pale Amber
Odor	Mild
pH	9 – 11

### Working Properties

Full Cure	24 – 72 hours
Surface Use	6-8 hours

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area with a 24 hour cure time to determine ease of application and desired results. Allow new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean and free of waxes and coatings. LATICRETE® Stone Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F (10°C and 26°C). Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until foot traffic resumes.

### Directions

1. Ensure cap is closed and sealed; shake well before use.
2. Mask off surfaces not intended to be treated.
3. Liberally apply an even coat of LATICRETE® Stone Sealer using a paint pad, roller, brush or low-pressure sprayer.
4. Allow Stone Sealer to penetrate the surface for 10 – 15 minutes. During this time, keep the surface wet with sealer, adding more sealer as needed. **DO NOT ALLOW SEALER TO COMPLETELY DRY ON THE SURFACE.**
5. Thoroughly wipe dry the entire surface with clean absorbent towels.
6. A second coat may be needed for porous, absorbent surfaces. If a second coat is required, it should be applied within 30 – 40 minutes from the initial application as directed in steps 3 – 5.
7. Should a sealer residue appear, rewet the impacted section of the surface with sealer. Agitate the surface with a white nylon scrubbing pad to loosen residue and wipe dry with a clean, absorbent towel.
8. A full cure is achieved in 24 – 72 hours. Use of the treated surface may resume in 6 – 8 hours. If use of the surface must resume sooner, cover the treated surface with red rosin paper to protect it until full cure has been achieved.
9. Clean tools used during application with water.

### Cleaning

Clean tools used during application with water

## 6. AVAILABILITY AND COST

### Availability

LATICRETE®, STONETECH® and LATAPOXY® materials are available worldwide.

### For Distributor Information, Call:

Toll Free: +1.888.786.6343

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [www.stonetech.com](http://www.stonetech.com) or [www.laticrete.com](http://www.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer used, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as LATICRETE® Stone & Tile Floor Cleaner is recommended. For tough or difficult to remove soil use LATICRETE® Heavy Duty Tile & Grout Cleaner and a stiff nylon brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: +1.888.786.6343, ext. 2

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com](http://www.laticrete.com) or [www.stonetech.com](http://www.stonetech.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [www.stonetech.com](http://www.stonetech.com). The following is a list of related documents:

DS 230.13: LATICRETE® Product Warranty

DS 370.5: LATICRETE® Stone & Tile Floor Cleaner

DS 372.5: LATICRETE® Heavy Duty Tile & Grout Cleaner