

Concrete - Slab-On-Grade or Suspended - Unbonded Thick Bed ES-F111

	Drawing No. ES F111
Concrete	
Cleavage Membrane 4 mil Polyethylene or 15	lb Builder's Felt
Wire Reinforcing 16 Gauge, 2" x 2" (50mr Welded, Galvanized Mesh -	m x 50mm)
LATICRETE [®] 3701 Fortified Mortar Bed —	
LATICRETE 254 Platinum –	
Ceramic Tile or Stone —	
LATICRETE SpectraLOCK PF Premium Grout; or, LATICRETE PermaColor™ Gr	
	Revision Date: 5/12 Scale: N.T.S.
AS A PROFESSIONAL COURTESY, LATICRETE OFFERS TECHNICAL SERVICES FREE OF CHARGE. THE USER MAINTAINS ALL RESPONSIBILITY FOR VERIFYING THE APPLICABILITY AND SUITABILITY OF THE TECHNICAL SERVICE OR INFORMATION PROVIDED.	(C)2012 LATICRETE INTERNATIONAL, NC. ALL RIGHTS RESERVED. THE RIGHT TO UTILIZE LATICRETE DETAILS FOR GOMMERCIAL PURPOSES IS GRAVITED EXCLUSIVELY TO CONTRACTORS, ARCHTECTS, QUANTY SURVEYORS, ENONEMEST, AND SPECIFICATIONS WITTERS, LATICRETE (R), LATAPOYT (R) ARE REQUISITENCE TRACEARKS OF LATICRETE INTERNATIONAL, INC. US & FOREIGN PATIENT AND TRACEMENT OFFICES, WARCA REGISTROAL ALL OTHER TRADEMENTS ARE

NOTE: "For complete application information and limitations consult related Product Data Sheets and Execution Statements related to this detail, and applicable industry standards."

