

Form

Rev: A

Page: 1 of 6

Date: 07/03/2023

1. **PRODUCT IDENTIFICATION**

TRADE NAME (as labeled): LATAPOXY® 310 Stone Adhesive Part A Rapid

CHEMICAL FAMILY: Amine Mixture

MANUFACTURER'S/ DISTRIBUTOR'S NAME: LATICRETE South East Asia Pte Ltd

38 Sungei Kadut,

Street 2 (Level2 A3),

Singapore 729245.

Phone number for additional information: (65) 6515 3028

Date prepared or revised: 07/03/2023

2. <u>COMPOSITION INGREDIENTS</u>

CHEMICAL NAMES	CAS NUMBERS	PERCENT
Calcium carbonate	471-34-1	14 - 18
Bis[(dimethylamino)methyl]phenol	71074-89-0	6 - 8
2,4,6-Tris(dimethylaminomethy I)phenol	90-72-2	3 - 5

3. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure. (Possible Longer

Term Effects): N/A

SIGNS AND SYMPTOMS OF EXPOSURE (Acute effects)

Inhalation : Vapors may cause headache, fatigue, dizziness and nausea.

Ingestion : May cause burns of the gastrointestinal tract if swallowed.

Skin Contact : Causes skin burns.

Eye Contact : Causes serious eye damage.



Form

Rev: A

Page: 2 of 6

Date: 07/03/2023

4. FIRST AID: EMERGENCY PROCEDURES

Eye Contact : Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get medical attention

immediately.

Skin Contact : Take off immediately all contaminated clothing. Chemical burns must be treated

by a physician. Wash contaminated clothing before reuse. Get medical attention

immediately.

Inhaled : Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical attention if any discomfort continues.

Swallowed : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that

stomach content doesn't get into the lungs. Get medical attention if any

discomfort continues.

Most important symptoms/effects, acute and delayed : Corrosive effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media : Alcohol resistant foam. Water fog. Dry chemical powder.

Carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use water jet as an extinguisher, as this will

spread the fire.

Specific hazards arising from the chemical : Heating may cause the release of ammonia

vapors.

Special protective equipment and precautions for firefighters : Self-contained breathing

apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions : In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers



Rev: A

Form

Page: 3 of 6

Date: 07/03/2023

6. <u>ACCIDENTAL RELEASE MEASURES</u>

Personal precautions, protective equipment and emergency procedures : Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions : Avoid release to the environment. Do not discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

7. HANDLING AND STORAGE

Keep container tightly closed. Store in a cool and well-ventilated place. Store away from incompatible materials

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Appropriate engineering controls : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Respiratory protection (type) : In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/face protection (type) : Wear safety glasses with side shields (or goggles). Face-shield. Wear a full-face respirator, if needed.

Gloves (specify material) : When mixing by hand appropriate impervious gloves are recommended. Because a wide variety



Form

Rev: A

Page: 4 of 6

Date: 07/03/2023

of protective gloves exist, consult glove manufacturer for recommendations

Other clothing and equipment : Wear appropriate chemical resistant clothing.

Work practices, hygienic practices : Normal good housekeeping

Other handling and storage requirements

: Store in cool, dry, well ventilated area below 32°C.

Do not freeze.

Protective measures during maintenance of contaminated equipment : See above

9. PHYSICAL AND CHEMICAL PROPERTIES

	Αı	ρĮ	oe	ar	ar	<u>ice</u>
--	----	----	----	----	----	------------

Physical state : Solid.
Form : Paste.
Color : Light red.

Odor : Ammonia.

Flash point : Non flammable.

Relative density : 1.5 g/ml

Solubility(ies) : Insoluble

10. STABILITY AND REACTIVITY

Stability	: X	Stable	Unstable

Conditions to avoid : Heat, flames and sparks. Contact with incompatible materials.

Incompatibility (materials to avoid) : Alkaline metals. Oxidizing agents. Strong acids.

Hazardous decomposition products (including combustion products): (from burning, heating, or reaction with other materials). Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides.

11. TOXICOLOGY INFORMATION

Components Species Test Result



Rev: A

Form

Page: 5 of 6

Date: 07/03/2023

Calcium carbonate (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/kg

12. ECOLOGICAL INFORMATION

Dispose in compliance with local, state, and federal regulations.

13. <u>DISPOSAL CONSIDERATIONS</u>

Dispose in compliance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT

UN number : UN3263

UN proper shipping name : Corrosive solid, basic, organic, n.o.s.

(Bis[(dimethylamino)methyl]phenol)

Transport hazard Class(es)
Class : 8
Subsidiary risk : Label(s) : 8
Packing Group : |||

Environmental hazards

Marine pollutant : No

Special precautions for user: Read safety instructions, SDS and emergency

procedures before handling.

Special provisions: IB8, IP2, IP4, T3, TP33

Packaging exceptions :154
Packaging non bulk : 212
Packaging bulk : 240

IATA

UN number : UN3263

UN proper shipping name: Corrosive solid, basic, organic, n.o.s.

(Bis[(dimethylamino)methyl]phenol)

Transport hazard class(es)



Form

Rev: A

Page: 6 of 6

Date: 07/03/2023

Class : 8
Subsidiary class(es) : Packing group : III
Environment Hazard : No
Labels required : 8
ERG Code : 8L

Special precautions for user

: Read safety instructions, SDS and emergency

procedures before handling.

IMDG

UN number : UN3263

UN proper shipping name : CORROSIVE SOLID, BASIC, ORGANIC, N.O.S.

(Bis[(dimethylamino)methyl]phenol)

Transport hazard class(es)

Class : 8
Subsidiary class(es) : Labels required : 8
Packing group : ||||

Environmental hazards

Marine Pollutant : No

EmS : F-A, S-B

Special precautions for user

procedures before handling.

: Read safety instructions, SDS and emergency

Transport in bulk according to : This substance/mixture is not intended

Annex II of MARPOL 73/78 and to be transported in bulk.

the IBC Code

15. <u>REGULATORY INFORMATION</u>

SARA 311/312 Hazardous Chemical : Yes

16. OTHER INFORMATION

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.