

1. **PRODUCT IDENTIFICATION**

TRADE NAME (as labeled): Mortar Primer EP & Mortar EP Part A

CHEMICAL FAMILY: Epoxy Resin

MANUFACTURER'S/ DISTRIBUTOR'S NAME:

LATICRETE South East Asia Pte Ltd

38 Sungei Kadut,

Street 2 (Level 2 A3),

Singapore 729245.

Phone number for additional information: (65) 6515 3028

Date prepared or revised: 05/09/2023

2. <u>COMPOSITION INGREDIENTS</u>

Chemical Names	CAS NUMBERS	CAS NUMBERS
2,2-Bis(4'-glycidyloxyphenyl) propane	1675-54-3	100

3. HEALTH HAZARD INFORMATION

GHS Classification

- Skin corrosion/irritation: Category 2
- Serious eye damage/ irritation: Category 2
- Skin sensitization: Category 1
- Chronic aquatic toxicity: Category 2





Signal Words

- Warning

Hazard Statements

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H411 Toxic to aquatic life with long lasting effects

Precautionary statements

Prevention

- P261 Avoid breathing dust/fume/gas/vapors/spray
- P264 Wash hands thoroughly after handling
- P272 Contaminated work clothing should not be allowed out of the workplace
- P273 Avoid release to the environment
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

- P302+P352 IF ON SKIN: Wash with plenty of soap and water
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing
- P321 Specific treatment
- P332+P313 If skin irritation. Get medical attention.
- P333+P313 If skin irritation or rash occurs. Get medical attendant
- P337+P313 If eye irritation persist. Get medical attention
- P362+P364 Take off contaminated clothing and wash before reuse
- P391 Collect spillage

Storage

Not applicable

Disposal

- P501 Dispose of contents/container in accordance with local/regional /national/international regulations.



4. FIRST AID: EMERGENCY PROCEDURES

- Eye Contact : Do not rub your eyes. Immediately flush eyes with plenty of water at least 15 minutes and call a doctor/physician. Go to the hospital immediately if symptoms (flare, irritate) occur. Remove contact lenses if worn.
- Skin Contact : Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing thoroughly before re-using. Go to the hospital immediately if symptoms (flare; irritate) occur. Wash thoroughly after handling.
- Inhaled : Take specific treatment if needed. When exposed to large amounts of steam and mist, move to fresh air.
- Ingestion : Please be advised by doctor whether induction of vomit is demanded or not. Rinse your mouth with water immediately.
- Delayed and immediate effects and also chronic effects from short and long term exposure: Not available
- Notes to physician: Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIRE FIGHTING MEASURES

Suitable (Unsuitable) extinguishing media	: Avoid use of water jet for extinguishing. Dry chemical, carbon dioxide, regular foam extinguishing agent, spray.
Hazards arising from chemical	: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.
Special firefighting procedures	: Avoid inhalation of materials or combustion by products. Cool containers with water until well after fire is out. Do not approach the tank surrounded by fire until it is extinguished. In case of conflagration, use automatic fire sprinkler. Major fire may require withdrawal, allowing the object itself to burn. Keep unauthorized personnel out.



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Do not touch spilled material. Stop leak if you can do it without risk. Handle the damaged containers or spilled material after wearing appropriate protective equipment. Move container to safe area from the leak area. Must work against the wind, let the upwind people to evacuate. Remove all sources of ignition.

Environmental precautions:

If large amount have been spilled, inform the relevant authorities. Prevent runoff and contact with waterways, drain or sewers.

Methods and materials for containment and cleaning up:

Appropriate container for disposal of spilled material collected. Dike for later disposal. Disposal of waste shall be in compliance with the Wastes Control Act. Large spill: Stay upwind and keep out of low areas. Dike for later disposal. Notify the central and local government if the emission reach the standard threshold.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with incompatible materials. Avoid direct physical contact. Comply with all applicable laws and regulations for handling. Dealing only with a well-ventilated place. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage: Avoid direct sunlight. Check regularly for leaks. Do not apply any physical shock to container. Do not apply direct heat. Do not use damaged containers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Exposure limits : ACGIH TLV Not applicable. OSHA PEL - Not applicable.
- Engineering controls : Business owner is recommended to maintain below recommended expose limits for the working place with general exhaust of gas/vapor/mist/fume.

	Form	
		Rev: B
LATICRETE		Page: 5 of 11
		Date: 27/02/2019
	Safety Data Sheet	
Globally Proven Construction Solutions		

Respiratory protection	: Air-purifying respirator with high-efficiency particulate filtering. Any air-purifying respirator with a full facepiece and an organic vapor canister. Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s). Any chemical cartridge respirator with organic vapor cartridge(s). Any respiratory protection with a electromotion fan(for dust, mist, fume-purifying). Consider warning properties before use. Dust, mist, fume-purifying respiratory protection For Unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive- pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece. Respiratory protection is ranked in order from minimum to maximum. Self-contained breathing apparatus with a corpuscle filter of high efficiency. Under conditions of frequent use or heavy exposure, respiratory protection may be needed.
Eye protection	: Provide an emergency eye wash station and quick drench shower in the immediate work area. Wear primary eye protection such as splash resistant safety googles with a secondary protection face shield.

Hand protection	: Wear appropriate chemical resistant glove.
Skin protection	: Wear appropriate chemical resistant protective clothing.
Others	: Not applicable.

9. PHYSICAL AND CHEMICAL PROPERTIES

Relative density	: 1.17
Melting point or range, °C	: N/A
Boiling point or range, °C	: > 200 °C



Safety Data Sheet

Form

Rev: B

Page: 6 of 11

Date: 27/02/2019

Globally Proven Construction Solutions

PH	: N/A
Viscosity	: 12-14 Pa.s (at 25°C)
Flash point	: 259 °C
Solubility in water	: N/A
Vapor density	: about 0.009kg/m ³ (at 23°C)
Vapor pressure	: < 0.01Pa (at 20°C)
Appearance and odor	: Pale Yellow liquid (viscous), not available.

10. STABILITY AND REACTIVITY

Chemical stability	: The product is stable under normal conditions of use, storage and handling conditions.
Possibility of hazardous reactions	: Hazardous polymerization will not occur.
Conditions to avoid	: Accumulation of electrostatic charges, heating, flames and hot surfaces. Contact with incompatible materials and conditions.
Incompatibility materials	: Not available.

Hazardous decomposition products : May emit flammable vapor if involved in fire.

11. TOXICOLOGY INFORMATION

Information on the likely routes of exposure:

- **Respiratory tracts**
- Not available.

Oral

- Not available

Eye-Skin

- Causes skin irritation. May cause an allergic skin reaction.



Delayed and immediate effects and also chronic effects from short and long term exposure: Acute toxicity

- Oral
 - [2,2-Bis(4'-glycidyloxyphenyl)propane] : LD50 11,300 mg/kg rat (HSDB)
- Dermal
 - [2,2-Bis(4'-glycidyloxyphenyl)propane] : LD50 >23,200 mg/kg Rabbit (IARC, NITE)
- Inhalation
 Not available

Skin corrosion/irritation:

- Cause skin irritation

Serious eye damage/irritation

- Causes serious eye irritation.

Respiratory sensitization

- Not available

Skin sensitization

- May cause an allergic skin reaction

Carcinogenicity

IARC

- [2,2-Bis(4'-glycidyloxyphenyl)propane] : Group 3

OSHA

Not available

ACGIH

Not available

NTP

- Not available
- EU CLP

- Not available

Germ cell mutagenicity

- Not available

Reproductive toxicity

- Not available

STOT-single exposure

- Not available



STOT-repeated exposure

- Not available

Aspiration hazard

- Not available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Fish

 [2,2-Bis(4'-glycidyloxyphenyl)propane] : LC50 1.5 mg/L 96 hr Oncorhynchus mykiss (ECHA)

Crustacea

 [2,2-Bis(4'-glycidyloxyphenyl)propane] : EC50 1.7 mg/L 48 hr Daphnia magna (ECHA)

Algae

[2,2-Bis(4'-glycidyloxyphenyl)propane] : EC50 9.4 mg/L 72 hr, NOEC 4.2 mg/L
 72 hr Scenedesmus capricornutum (ECHA)

Persistence and degradability

Persistence

- [2,2-Bis(4'-glycidyloxyphenyl)propane] : log Kow 2.64 ~ 3.78 (25 °C) (ECHA)

Degradability

- Not available

Bioaccumulative potential

Bioaccumulative potential - [2,2-Bis(4'-glycidyloxyphenyl)propane] : Log BCF 1.11 ± 0.75, BCF 31 (OASIS CATABOL QSAR estimate, ECHA) Biodegradation - [2,2-Bis(4'-glycidyloxyphenyl)propane] : 0 (%) 28 day (NITE)

Mobility in soil

- Not available



Other adverse effects - Not available

13. DISPOSAL CONSIDERATIONS

Disposal instructions : It shall be treated by incineration. Oil water separation technology shall be applied as pre-waste treatment if it is applicable. Stabilization and minimization treatment by incineration or similar method can be applied, if more than two kinds of designated wastes are in mixture state and it is impractical to separate them.

Special precautions for disposal : Anyone with business license number who generates industrial wastes shall treat the waste by him/herself or by entrusting to the legal entities who treat the wastes, recycle the wastes of others or install and operate the waste treatment facilities according to the Wastes Control Act. Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

UN No. (IMDG CODE/IATA DGR) 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(2,2-Bis(4'glycidyloxyphenyl)propane)

Hazard Class 9

IMDG CODE/IATA DGR Packing group III

Marine pollutant Applicable



Special precautions for user related to transport or transportation measures Local transport follows in accordance with Dangerous goods Safety Management Law. Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements. EmS FIRE SCHEDULE: F-A (General fire schedule). EmS SPILLAGE SCHEDULE: S-F (Water-soluble marine pollutants).

15. <u>REGULATORY INFORMATION</u>

POPs Management Law - [2,2-Bis(4'-glycidyloxyphenyl)propane] : Not applicable

Information of EU Classification Classification - [2,2-Bis(4'-glycidyloxyphenyl)propane] : H315,H317,H319

U.S. Federal regulations

OSHA PROCESS SAFETY (29CFR1910.119) - Not applicable

CERCLA Section 103 (40CFR302.4) - Not applicable

EPCRA Section 302 (40CFR355.30) - Not applicable

EPCRA Section 304 (40CFR355.40) - Not applicable

EPCRA Section 313 (40CFR372.65) - Not applicable

Rotterdam Convention listed ingredients - Not applicable

Stockholm Convention listed ingredients - Not applicable

Montreal Protocol listed ingredients - Not applicable



16. OTHER INFORMATION

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.