



For the Builders  
of a Better World™

Form

Rev: A  
Page: 1 of 7  
Date: 21/08/2024

# Safety Data Sheet

## 1. PRODUCT IDENTIFICATION

TRADE NAME (as labeled): Mortar UT HF Part B

MANUFACTURER'S/ DISTRIBUTOR'S NAME: LATICRETE South East Asia Pte Ltd  
38 Sungei Kadut Street 2  
(Level 2 A3)  
Singapore 729245.

Phone number for additional information: (65) 6515 3028

Date prepared or revised: 21/08/2024

## 2. COMPOSITION INGREDIENTS

Chemical Names	CAS NUMBERS	%
DIPHENYLMETHANE DIISOCYANATE, POLYMERIC/4,4'- METHYLENEDIPHENYL DIISOCYANATE	9016-87-9 / 101-68-8	100

## 3. HEALTH HAZARD INFORMATION

CLASSIFICATION: SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
AQUATIC HAZARD (LONG-TERM) - Category 3

HAZARD PICTOGRAMS :



SIGNAL WORD : WARNING



For the Builders  
of a Better World™

Form

Rev: A  
Page: 2 of 7  
Date: 21/08/2024

# Safety Data Sheet

## HAZARD STATEMENTS

: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

## PRECAUTIONARY STATEMENTS

### Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Avoid release to the environment. Do not breathe vapor or spray. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

### Response

: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

### Storage

: Store locked up. Store in a well-ventilated place. Keep cool.

### Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

## 4. FIRST AID: EMERGENCY PROCEDURES

Inhalation : Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.



**For the Builders  
of a Better World™**

Form

Rev: A

Page: 3 of 7

Date: 21/08/2024

# Safety Data Sheet

**Skin Contact** : Flush from skin with water. Then wash thoroughly with soap and water. Remove contaminated clothing. Wash contaminated clothing before re-use.

**Eye Contact** : Flush immediately with large amount of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

**Ingestion** : If swallowed, obtain medical treatment immediately.

## Effects of Overexposure

**Inhalation** : Irritation of respiratory tract. Prolonged inhalation may lead to mucous membrane irritation, fatigue, drowsiness, dizziness and/or light headedness, headache, uncoordination, nausea, vomiting, blurred vision, coughing, difficulty with speech, central nervous system depression, intoxication tightness of chest, anesthetic effect or narcosis, difficulty of breathing, allergic response, tremors, liver damage, kidney damage, pulmonary edema, pneumoconiosis, loss of consciousness, respiratory failure, asphyxiation, death. Possible sensitization to respiratory tract.

**Skin Contact** : Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, blistering, severe skin irritation. Possible sensitization to skin.

**Eye Contact** : Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis, blurred vision, tearing of eyes, redness of eyes, severe eye irritation, corneal injury.

**Ingestion** : Ingestion may cause lung inflammation and damage due to aspiration of material into lungs, mouth and throat irritation, mucous membrane irritation, drowsiness, dizziness and/or lightheadedness, headache, nausea, vomiting, diarrhea, gastrointestinal disturbances, abdominal pain, central nervous system depression, anesthetic effect or narcosis, liver damage kidney damage, pulmonary edema, convulsions, loss of consciousness.

**Medical Conditions Aggravated by Exposure** : Eye, skin, respiratory disorders, kidney disorders, liver disorders.



For the Builders  
of a Better World™

Form

Rev: A

Page: 4 of 7

Date: 21/08/2024

# Safety Data Sheet

## 5. FIRE FIGHTING MEASURES

- Extinguishing Media** : Dry chemical or foam water fog. Carbon dioxide. Closed containers may explode when exposed to extreme heat or fire. Vapors may ignite explosively at ambient temperatures. Vapors are heavier than air and may travel long distances to a source of ignition and flash back. Vapors can form explosive mixtures in air at elevated temperatures. Closed containers may burst if exposed to extreme heat or fire. May decompose under fire conditions emitting irritant and/or toxic gases.
- Fire Fighting Instruction** : Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus.
- Hazardous decomposition or combustion products** : Carbon monoxide, carbon dioxide, oxides of nitrogen, acrid fumes, oxide of sulfur, ammonia, oxygen, toxic gases, barium compounds, smoke and soot, unidentified organic compounds.

## 6. ACCIDENTAL RELEASE MEASURES

- Methods for Cleaning Up** : Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Ventilate area with explosive-proof equipment. Spills may be collected with absorbent materials. Use non-sparking tools. Evacuate all unnecessary personnel. Place collected material in proper container. Complete personnel protective equipment must be used during cleanup. Large spills – shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent to pick up excess residue. Keep salvageable material and rinse water out of sewers and water

## 7. HANDLING AND STORAGE

- Handling and Storage** : Store below 30°C. Keep away from heat, sparks and open flame. Keep from freezing. Keep away from sunlight, heat and all sources of ignition.



For the Builders  
of a Better World™

Form

Rev: A

Page: 5 of 7

Date: 21/08/2024

# Safety Data Sheet

Other Precautions : Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions that result formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection. Empty containers may contain hazardous residues. Ground equipment when transferring to prevent accumulation of static charge.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory Protection : Control environmental concentrations below applicable exposure standards when using this material. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR1910.134 For selection of Respirators (Canadian z94.4).

Ventilation : Provide dilution ventilation or local exhaust to ensure concentration are kept below explosion limit. Use explosion-proof equipment. Use non-sparking equipment.

Personal Protective Equipment : Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing, face shield, aprin, boots.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : Liquid

Colour : Brownish

Odour : Characteristic

Specific Gravity : 1.20-1.25

% Volatile by Weight : 0 - 2%

Flash Point : 220°C



**For the Builders  
of a Better World™**

Form

Rev: A  
Page: 6 of 7  
Date: 21/08/2024

# Safety Data Sheet

## 10. STABILITY AND REACTIVITY

Under Normal Conditions : Stable see section 5 firefighting measures

Materials to avoid : Oxidizers, acids, bases, amines, aluminium, peroxides, nitric acid, phosphorus, caustics.

Conditions to avoid : Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame, ignition sources.

Hazardous Polymerization : Will not occur.

## 11. TOXICOLOGY INFORMATION

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Other effects of overexposure may include toxicity to liver, kidney, central nervous system, blood.

## 12. ECOLOGICAL INFORMATION

N/A

## 13. DISPOSAL CONSIDERATIONS

Waste Disposal : Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

## 14. TRANSPORT INFORMATION

UN Number : None

UN Proper Shipping Name : None

Transport Hazard Class : None

Packing Group : None

Environmental Hazard : No

Transport Within User's : Always transport in closed containers that are upright and secure.

