	Form	
		Rev: B
LATICRETE		Page: 1 of 7
LANGRETE		Date: 07/06/2019
	Safety Data Sheet	
®	Carety Data Officer	
Globally Proven Construction Solutions		
Construction Solutions		

1. **PRODUCT IDENTIFICATION**

TRADE NAME (as labeled): SPECTRALOCK® PRO NS Grout Part B

CHEMICAL FAMILY: Epoxy Resin

MANUFACTURER'S/ DISTRIBUTOR'S NAME:

LATICRETE South East Asia Pte Ltd

(Level2, A3)

38 Sungei Kadut, Street 2


Singapore 729245

Phone number for additional information: +(65) 6515 3028 Date prepared or revised: 07/06/2019

2. <u>HAZARDOUS INGREDIENTS</u>

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
Propane, 2,2-bis[p- (2,3epoxypropoxy) phenyl]-, polymers	25085-99-8	45-52	N/A	N/A	N/A
phenyij-, polymers			N/A	N/A	N/A
Reaction product: Bisphenol F- (epichlorhydrin); Epoxy	28064-14-4	10-17	N/A	N/A	N/A
Alkyl(C12-14) glycidyl ether	68609-97-2	7-14	N/A	N/A	N/A
Xylenes	1330-20-7	0.1-0.2	100 ppm	100 ppm	N/A

N/A = Not applicable or available



3. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: May cause irritation of respiratory tract

Contact with skin or eyes	÷	Minor transient irritation for eye contact. No corneal injury likely. May cause allergic skin reaction. Prolonged exposure not likely to cause skin irritation. Skin sensitizer.
Absorbed through skin	:	Not likely to absorb through skin in toxic amount in a single prolonged exposure. LD 50 for skin absorption for rabbits = 20,000mg/kg
Swallowed	:	Causes gastrointestinal irritation and possible burn if swallowed.

SUSPECTED CANCER AGENT?

x NO: This product's ingredients are not found in the lists below.

4. FIRST AID: EMERGENCY PROCEDURES

Eye Contact	:	Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	:	Remove product and immediately flush affected area with water for at least 15 minutes. Remove contaminated clothing and shoes. Launder contaminated clothing prior to reuse. See a physician if irritation persists.
Inhaled	:	Move patient to fresh air. If breathing has stopped or is labored give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be indicated. Prevent aspiration of vomit. Turn victim's head to the side. Seek medical advice.
Swallowed	:	If swallowed, call a physician immediately. Do not induct vomiting only. Never give anything by mouth to unconscious person.

	Form	
		Rev: B
LATICRETE		Page: 3 of 7
LANGRETE		Date: 07/06/2019
	Safety Data Sheet	
®	Calley Data Officer	
Globally Proven Construction Solutions		
Construction Solutions		

5. <u>FIRE FIGHTING MEASURES</u>

Flash Point method: Non-fla	mmable)	
Auto ignition temperature, °F	F: N/A		
Flammable limits in air, volu	me %:	Lower (LEL)	Upper (UEL)
Fire extinguishing materials:			
Water spray	<u> </u>	Carbon Dioxide	Other:
<u>X_</u> Foam		X Dry Chemical	

Special fire fighting procedures: Firefighters should wear butyl rubber boots, gloves, and body suit and a self- contained breathing apparatus. If water pollution occurs notify appropriate authorities

Unusual fire and explosion hazards: May generate toxic or irritating combustion products. Sudden reaction and fire may result if product is mixed with an oxidizing agent. may generate toxic nitrogen oxide gases. May generate ammonia gases. Personnel in vicinity and downwind should be evacuated.

6. ACCIDENTAL RELEASE MEASURES

Spill response procedures (include employee protection measures): Wear goggles and face shield. Stop the leak, if possible. Ventilate the space involved. Soak up in absorbent material or scrape up. Residual can be removed with hot water and a nonionic surfactant. Construct a dike to prevent spreading (includes molten liquids until they freeze). Collect run-off water and transfer to drums or tanks for later disposal.

Preparing wastes for disposal (container types, neutralization, etc.): N/A

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

7. <u>HANDLING AND STORAGE</u>

Store in cool areas. Excess heating over long periods of time degrades the resin.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation and engineering controls: Normal



Form

Rev: **B** Page: 4 of 7 Date: 07/06/2019

Safety Data Sheet

Globally Proven Construction Solutions

Respiratory protection (type): NIOSH approved dust masks if exposure limit are exceeded.

Eye protection (type): Safety glasses or goggles

Gloves (specify material): Impervious gloves

Other clothing and equipment: long sleeved clothing

Work practices, hygienic practices: Normal good housekeeping

Other handling and storage requirements: N/A

Protective measures during maintenance of contaminated equipment: See above.

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor density (air=1): N/AMelting point or range, °F: >32Specific gravity: 1.12g/ccBoiling point or range, °F: >212Solubility in water: solubleEvaporation rate (butyl acetate = 1): N/AVapor pressure, mmHg at 20°C: N/AVOC: <1%</td>Appearance and odor: opaque liquid.HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist): N/A

10. STABILITY AND REACTIVITY

Stability:


<u>x</u> Stable _____ Unstable

Conditions to avoid: Stable at ambient temperatures. Excess heating over long periods of time degrades the resin.

Incompatibility (materials to avoid): Bases

Hazardous decomposition products (including combustion products): (from burning, heating, or reaction with other materials).

Incomplete pyrolosis or combustion results in phenolics, carbon monoxide, carbon dioxide, and water.



Thermal decomposition should be traced as a potentially hazardous substance.

Hazardous polymerization: _____ May occur __x__Will not occur

Conditions to avoid: N/A

11. TOXICOLOGY INFORMATION

Acute Dermal Toxicity (LD50, Rabbit) > 2000mg/kg

12. ECOLOGICAL INFORMATION

N/A

13. DISPOSAL CONSIDERATIONS

Dispose in compliance with local, state, and federal regulations.

14. TRANSPORT INFORMATION :

DOT

UN number: UN proper shipping name:	UN3082 Environmentally hazardous substance, liquid, n.o.s. (Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin, Propane, 2,2-bis[p-(2,3- epoxypropoxy)phenyl]-, polymers)
Transport hazard class(es):	
Class:	9
Subsidiary risk:	-
Label(s)	9
Packing group	
Special precautions for use	
Special provisions	8, 146, 335, IB3, T4, TP1, TP29
Packaging exceptions	155
Packaging non bulk	203
Packaging bulk	241
ΙΑΤΑ	
UN number:	UN3082
UN proper shipping name:	Environmentally hazardous substance, liquid, n.o.s. (Reaction product: Bisphenol F-(epichlorhydrin); epoxy resin, Reaction




Form

Rev: **B** Page: 6 of 7 Date: 07/06/2019

Safety Data Sheet

Globally Proven Construction Solutions

	product: Bisphenol F-(epichlorohydrin); epoxy resin)
Transport hazard class(es) Class: Subsidiary Risk: Labels: Packing Group: Environmental hazards: ERG Code: Special precautions for use	9 - 9 III Yes 9L r: Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Reaction product: Bisphenol F-(epichlorohydrin); epoxy resin, Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for use	r: Read safety instructions, SDS and emergency procedures before Handling
Transport in bulk according Annex II of MARPOL 73/78 and the IBC Code	to This substance/mixture is not intended to be transported in bulk.
General information	IATA classification is not relevant as the material is not transported by air



15. <u>REGULATORY INFORMATION</u>

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

16. <u>REGULATORY INFORMATION</u>

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.