



LATASIL™ 9118 Primer

Latasil 9118 Primer is a one component primer designed to increase adhesion of Latasil to various substrates.

Globally Proven
Construction Solutions



FEATURES/BENEFITS

- Ready to use
- Fast dry time
- Durable bond is unaffected by water

USES

- Increases adhesion & bond strength for dependable long lasting installations.
- For all underwater and permanent wet area applications such as pools, fountains, showers, tubs, spas, saunas and steam rooms.
- Ideal for stone applications.
- Ideal for harsh environment.

MANUFACTURER/ DISTRIBUTED BY

LATICRETE South East Asia Pte Ltd (Level 2, A3)
No. 38 Sungei Kadut, Street 2, Singapore 729245
Telephone: +65 6515 3028 Fax: +65 6515 3037
Internet: se.laticrete.com

Suitable Substrates

- PVC
- Stone
- Ceramic/masonry
- Metals/steel
- Porcelain

Packaging

8 oz. (240 ml) bottle; 5 bottles per carton

Approximate Coverage

Each bottle will cover approximately 350 linear feet or 106 linear meters.

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for six (6) months* if stored at temperature $>0^{\circ}\text{C}$ and $<40^{\circ}\text{C}$.

* High humidity will reduce the shelf life of bagged product.

Limitations

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane.
- Flammable—cannot be shipped air freight

Cautions

Consult MSDS for more safety information.

- Avoid direct contact with eyes. If contact with eyes occurs, immediately flush with water and seek medical attention.
- Avoid prolonged exposure to skin. In case of skin contact, wash affected area as soon as possible.
- Keep away from heat, sparks and open flames.
- Use with adequate ventilation, avoid prolonged breathing of vapors.
- Flammable—store in safe location.
- Test a small area when applying to stone for compatibility.
- Keep out of reach of children.

INSTALLATION SYSTEM

Preparation

- Thoroughly clean all surfaces of dust, dirt tar, oils, and other debris. Remove rust and scale from metal surfaces by abrasive cleaning or wire brushing. Masonry surfaces should also be wire brushed and blown with compressed air to remove dust.
- Thoroughly clean and degrease all surfaces with an industrial solvent such as naphtha, mineral spirits, xylene, toluene or MEK on a clean oil-free rag.

Application

- Sealant must be installed in the manner indicated for intended performance.

- Consult the following LATICRETE details at se.laticrete.com for specific sealant installation applications:
 - Shower Receptor—Waterproofing—Cement Backer Unit Walls ES B415
 - Shower Receptor—Waterproofing Above Mortar Bed ES B421
 - Bathtub/Shower Wall Waterproofing ES B412
 - Waterproofing Membrane—Typical Pipe Penetration ES WP300
 - Drain Detail—Exploded View ES WP302
 - Waterproofing and Secondary Waterproofing Membrane —Drain Detail ES WP303
 - Swimming Pool—Tank ES P601
 - Swimming Pool—Pool Deck/Trench Drain ES P601c
 - For underwater applications and steam rooms, polyethylene foam backer rod is recommended. Use polyethylene tape on joints too shallow to accommodate foam rod. Polyethylene backer rod is a “closed” cell which is water repellent.
- Apply Latasil 9118 Primer to clean, dry surfaces by brushing, dipping, or spraying.
- Apply a thin layer evenly to the substrate—do not apply too thick as bond will break.
- Take care not to contaminate the veneer surface.
- Allow the primer to dry until all the solvent evaporates and is dry to the touch (generally 30–60 minutes at 21°C). Drying time depends on temperature, humidity conditions and the porosity of the substrate.
- Apply sealant as directed (see Data Sheet 6200.1).

AVAILABILITY AND COST

Availability

LATICRETE and LATAPOXY materials are available worldwide. For distributor information, call:

Telephone: (65) 6515-3028

Fax: (65) 6515-3037

For on-line distributor information, visit LATICRETE at se.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

WARRANTY

LATICRETE International warrants that Latasil 9118 Primer is free from manufacturing defects and will not break down, deteriorate or disintegrate under normal usage for a period of one (1) year from date of purchase subject to terms and conditions stated.

MAINTENANCE

LATICRETE and LATAPOXY grouts require routine cleaning with a neutral pH soap and water. All other LATICRETE and LATAPOXY materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

TECHNICAL SERVICES/ CONTACT

Technical Assistance

Information is available by calling:

LATICRETE South East Asia Pte Ltd
(Level 2, A3)
No. 38 Sungei Kadut, Street 2,
Singapore 729245
Telephone: (65) 6515-3028
Fax: (65) 6515-3037
Email: enquiry@laticrete.com.sg

Technical and safety literature

To acquire technical and safety literature, please visit our website at
se.laticrete.com