



# STONETECH® Epoxy Grout Haze & Coating Stripper

Globally Proven  
Construction Solutions

STONETECH Epoxy Grout Haze & Coating Stripper is specifically formulated to safely break down coatings and epoxy grout haze.



## FEATURES/BENEFITS

- Removes tough coatings, lacquers, and varnishes
- Low odor and non-flammable water-based formula
- Professional strength

## USES

- Countertops
- Backsplashes
- Floors
- Walls

## MANUFACTURER/ DISTRIBUTED BY

LATICRETE South East Asia Pte Ltd (Level 2, A3)  
No. 38 Sungei Kadut, Street 2, Singapore 729245  
Telephone: +65 6515 3028 Fax: +65 6515 3037  
Internet: [se.laticrete.com](http://se.laticrete.com)

## Recommended Surfaces

Natural stone masonry and tile surfaces such as:

- Marble
- Slate
- Saltillo tile
- Ceramic and Porcelain tile

Not intended for use on surfaces other than stone, tile and masonry.

## Item Numbers and Packaging

- Sample 2oz (59mL), 12 units per Case
- Quart 32 oz (946 mL), 6 units per Case, 600 units per Pallet
- Gallon (3.8ℓ), 4 units per Case, 160 units per Pallet

## Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >10°C and <32°C.

## VOC Content

6.4% US(Consumer Products)

## Cautions

Consult SDS for more safety information.

- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Wash off with soap and water. Get medical attention if symptoms occur.
- Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.
- Ingestion: Rinse mouth. Do not induce vomiting. Get medical attention if any discomfort continues.

## Storage and Handling Instructions

- CAUTION: MAY BE HARMFUL IF SWALLOWED. CAUSES EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY IRRITATION. Do not ingest. Avoid prolonged exposure to vapors. Use in a well-ventilated area. Rubber gloves and eye protection should be worn during handling and application to prevent skin and eye contact. KEEP OUT OF THE REACH OF CHILDREN. Do not freeze or store above 38°C. Do not mix with other chemicals. Do not flush unused product to natural waterways or sanitary sewer system. Dispose of in accordance with waste disposal regulations.

## TECHNICAL DATA

### Physical Properties

Form	Liquid
Color	Clear
Odor	Mild
pH	11.5

## INSTALLATION

### Surface Preparation

Read entire label before using. Use only as directed. Test in a small inconspicuous area to determine ease of application and desired results. Be sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area until surface use resumes. Avoid contact with surfaces not intended to be treated. Avoid applying in direct sunlight. Should not be used in extreme temperatures. Recommended application temperature range is 10 °C to 32.2 °C.

### Directions

1. SHAKE WELL BEFORE USING. Do not dilute before applying.
2. Wear rubber gloves and eye protection during handling and application to prevent skin and eye contact.
3. Liberally apply an even coat of STONETECH® Epoxy Grout Haze & Coating Stripper over the required area with a paint brush, mop or paint pad. DO NOT APPLY WITH A SPRAYER. Immediately remove STONETECH Epoxy Grout Haze & Coating Stripper from unintended surfaces with a wet cloth to prevent potential damage to those surfaces.

4. Application time will vary depending on type of coating being removed. Approximate application times are as follows:

Coating Type	Application Time
Sealer, wax & varnish	30 to 60 minutes
Polyurethane & acrylic	1 to 2 hours
Epoxy grout haze	1 to 2 hours

5. Do not let STONETECH Epoxy Grout Haze & Coating Stripper dry on the surface. If it starts to dry, add additional product to keep surface wet.
6. Agitate surface with a nylon scrub brush or pad after testing a small area first to make sure that brush or pad will not scratch stone. Surface can be wet with water to enable easier removal of coating.
7. Wipe up residual STONETECH Epoxy Grout Haze & Coating Stripper with clean, dry clothes or wet mop. A wet/dry vacuum can be used for larger area.
8. Rinse surface well with clean water.
9. More than one application may be required, repeat steps 3 through 8 when necessary.
10. Surface traffic may begin 2 hours after removal of coating.

## AVAILABILITY AND COST

### Availability

LATICRETE® materials are available worldwide. For distributor information, call:

**Telephone:** (65) 6515-3028

**Fax:** (65) 6515-3037

For on-line distributor information, visit LATICRETE at [se.laticrete.com](http://se.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## WARRANTY

Subject to the conditions and limitations stated below, LATICRETE South East Asia Pte Ltd warrants that its products will be free from manufacturing defects and will not break down or deteriorate under normal usage for a period of one (1) year from the date of purchase when installed in accordance with the written specifications of LATICRETE and industry standard guidelines.

## MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the Sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, and a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results.

## TECHNICAL SERVICES/ CONTACT

### Technical Assistance

Information is available by calling:

LATICRETE South East Asia Pte Ltd  
(Level 2, A3)  
No. 38 Sungei Kadut, Street 2,  
Singapore 729245  
Telephone: (65) 6515-3028  
Fax: (65) 6515-3037  
Email: [enquiry@laticrete.com.sg](mailto:enquiry@laticrete.com.sg)

### Technical and safety literature

To acquire technical and safety literature, please visit our website at [se.laticrete.com](http://se.laticrete.com)