



Globally Proven
Construction Solutions

Waterproofing/Anti-Fracture Fabric

Waterproofing/Anti-Fracture Fabric is a thin, flexible non-woven fabric designed for use specifically with LATICRETE waterproofing membranes. The Waterproofing/Anti-Fracture Fabric adds strength to load-bearing waterproofing membranes specifically for the special requirements of ceramic tile, stone and brick installations. A self-curing liquid rubber polymer and a reinforcing fabric are quickly applied to form a flexible, seamless waterproofing membrane that bonds to a wide variety of substrates.



FEATURES/BENEFITS

- Required for use with HYDRO BARRIER™ in coves, corner and changes of plain for waterproofing applications
- Can be used with HYDRO BAN® for added strength
- Interior and exterior use
- Vertical and horizontal surfaces (including ceilings)
- Provides added strength to installation areas with added stress

USES

- Swimming pools, fountains & water features
- Shower pans, stalls and tub surrounds
- Bathrooms & laundries (industrial, commercial & residential)
- Spas and hot tubs
- Kitchens & Food Processing Areas
- Terraces & balconies over unoccupied spaces
- Countertops
- Facades
- Steam rooms (when used in conjunction with a vapor barrier)

MANUFACTURER/DISTRIBUTED BY

LATICRETE South East Asia Pte Ltd (Level 2, A3)
No. 38 Sungei Kadut, Street 2, Singapore 729245
Telephone: +65 6515 3028 Fax: +65 6515 3037
Internet: se.laticrete.com

Suitable Substrates

- Concrete
- Cement Mortar Beds
- Cement Plaster
- Concrete and Brick Masonry
- Exterior Glue Plywood*
- Gypsum Wallboard*
- Ceramic Tile and Stone**
- Cement Terrazzo**
- Cement Backer Board***

* Interior use only.

** If skim coated with LATICRETE® Latex Thin-Set Mortar;

***Consult cement backer board manufacturer and LATICRETE Technical Department for specific installation recommendations and to verify acceptability for exterior use.

Packaging

Long Fabric (big roll + small roll):

29 m x 0.965 m/roll + 23 m x 0.15 m /roll

Short Fabric (small roll):

23 m x 0.15 m /roll

Approximate Coverage

See data sheets for the specific Waterproofing Membrane being used

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >32°F (0°C) and 110°F (43°C).

Limitations

- Do not use with a LATICRETE waterproofing membrane as a primary roofing membrane over occupied space
- Use LATAPOXY® 300 Adhesive for installing green marble or water sensitive stone, resin-backed stone or tile and
- agglomerates.
- Do not use with a LATICRETE waterproofing membrane over expansion joints, structural cracks or cracks with vertical differential movement
- Do not use with a LATICRETE waterproofing membrane over cracks >1/8" (3 mm) in width
- Do not use with a LATICRETE waterproofing membrane as a vapor barrier (especially in steam rooms)
- Not for use with a LATICRETE waterproofing membrane directly over OSB, particle board, luan, Masonite®, or hardwood floors.
- Use white mortar for white or light-colored marble or stone.
- Do not expose unprotected LATICRETE waterproofing membrane to sun or weather for >30 days
- Do not expose LATICRETE waterproofing membrane to negative hydrostatic pressure, excessive vapor transmission, rubber solvents or ketones
- LATICRETE waterproofing membrane must be covered with ceramic tile, stone, brick, concrete, screeds, terrazzo or other traffic-bearing course. Use protection board for temporary cover.

- Obtain approval by local building code authority before using LATICRETE waterproofing membrane in shower pan applications.
- Do not install LATICRETE waterproofing membrane directly over single layer wood floors, plywood tubs/showers/ fountains or similar constructs

Note: Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Substrate deflection under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/480 for thin bed stone installations where L=span length.

Cautions

Consult specific LATICRETE® waterproofing membrane MSDS for more safety information. Protect from traffic or water until fully cured

TECHNICAL DATA

Applicable Standards

See the individual LATICRETE waterproofing membrane data sheets for specific technical data.

INSTALLATION

Surface Preparation

Surface temperature must be 50–90°F (10–32°C) during application and for 24 hours after installation for installations of HYDRO BAN or HYDRO BARRIER. All substrates must be structurally sound, clean and free of dirt, oil, grease, paint, laitance, efflorescence, concrete sealers or curing compounds. Make rough or uneven concrete smooth to a wood float or better finish with a LATICRETE Underlayment. Do not level with gypsum or asphalt based products. Maximum deviation in plane must not exceed 1/4" in 10 ft (6 mm in 3 m) with no more than 1/16" in 1 ft

(1.5 mm in 0.3 m) variation between high spots. Dampen hot, dry surfaces and sweep off excess water—installation may be made on a damp surface. New concrete slabs shall be damp cured and a minimum of 14 days old before application. Maximum amount of moisture in the concrete substrate should not exceed 5 lbs./1000 square feet (2.26 kg/92.9 m²) 24 hrs. per ASTM F-1869 or 75% relative humidity as measured with moisture probes.

1. Installer must verify that deflection under all live, dead and impact loads of interior plywood floors does not exceed industry standards of L/360 for ceramic tile and brick or L/480 for stone installations where L=span length.
2. Minimum construction for interior plywood floors:
SUBFLOOR: 5/8" (15 mm) thick exterior glue plywood, either plain with all sheet edges blocked or tongue and groove, over bridged joints spaced 16" (400 mm) o.c. maximum; fasten plywood 6" (150 mm) o.c. along sheet ends and 8" (200 mm) o.c. along intermediate supports with 8d ring-shank, coated or hot dip galvanized nails (or screws); allow 1/8" (3 mm) between sheet ends and 1/4" (6 mm) between sheets edges; all sheet ends must be supported by a framing member; glue sheets to joints with construction adhesive;
UNDERLAYMENT: 5/8" (15 mm) thick exterior glue plywood fastened 6" (150 mm) o.c. along sheet ends and 8" (200 mm)

o.c. in the panel field (both directions) with 8d rings-shank, coated or hot dip galvanized nails (or screws); allow 1/8" (3 mm) to 1/4" (6 mm) between sheets and 1/4" (6 mm) between sheet edges and any abutting surfaces; offset underlayment joints from joints in subfloor and stagger joints between sheet ends; glue underlayment to subfloor with construction adhesive. Refer to Technical Data Sheet 152 "Requirements for Direct Bonding of Ceramic or Stone Tiles Over Wood Floors" for complete details.

Protection

Provide protection for newly installed membrane, even if covered with a thin bed ceramic tile, stone or brick installation, against exposure to rain or other water for a minimum of 5 days @ 70°F (21°C) and 50% RH.

Flood Testing

Allow membrane to cure fully before flood testing, see the specific LATICRETE waterproofing membrane data sheet being used for information concerning flood testing. Cold and/or wet conditions will require a longer curing time.

Installing Finishes

Once the LATICRETE waterproofing membrane has dried to the touch, ceramic tile, stone or brick may be installed by the thin bed method with a LATICRETE Latex Thin-Set Mortar. Allow the LATICRETE waterproofing membrane to fully cure as indicated in the specific membrane's product data sheet before covering with concrete, thick bed mortar, screeds, toppings, coatings, epoxy adhesives, terrazzo or moisture sensitive resilient or wood flooring.

DO NOT use solvent-based adhesives or organic adhesives (mastics) directly on a LATICRETE waterproofing membrane.

Drains & Penetrations

Follow the specific LATICRETE waterproofing membrane data sheet for applications around drains and penetrations.

Control Joints

Ceramic tile, stone and brick installations must include sealant filled joints over any control joints in the substrate. However, the sealant filled joints can be offset horizontally, by as much as one tile width from the substrate control joint location, to coincide with the grout joint pattern.

Expansion Joints

Ceramic tile, stone and brick installations must include expansion joints at coves, corners, other changes in substrate plane and over any expansion joints in the substrate. Expansion joints in ceramic tile, stone or brickwork are also required at perimeters, at restraining surfaces, at penetrations and at the intervals described in Tile Council of North America, Inc. (TCNA) Handbook Installation Method EJ171. Use Latasil™ and backer rod.

Cleaning

While wet, LATICRETE waterproofing membranes can be washed from tools with water.

AVAILABILITY AND COST

Availability

LATICRETE and LATAPOXY materials are available worldwide. For distributor information, call:

Telephone: (65) 6515-3028

Fax: (65) 6515-3037

For on-line distributor information, visit LATICRETE at se.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

WARRANTY

LATICRETE South East Asia Pte Ltd warrants that **WATERPROOFING/ANTI-FRACTURE FABRIC** is free from manufacturing defects and will not break down, deteriorate or disintegrate under normal usage for a period of one (1) year from date of purchase subject to the terms and conditions stated.

MAINTENANCE

LATICRETE® and LATAPOXY® grouts require routine cleaning with a neutral pH cleaner (e.g STONETECH® Stone & Tile Cleaner) and water. All other LATICRETE and LATAPOXY materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

TECHNICAL SERVICES/ CONTACT

Technical Assistance

Information is available by calling:

LATICRETE South East Asia Pte Ltd
(Level 2, A3)

No. 38 Sungei Kadut, Street 2,
Singapore 729245

Telephone: (65) 6515-3028

Fax: (65) 6515-3037

Email: enquiry@laticrete.com.sg

Technical and safety literature

To acquire technical and safety literature, please visit our website at se.laticrete.com